

# Package ‘MsBackendRawFileReader’

May 26, 2022

**Type** Package

**Title** Mass Spectrometry Backend for Reading Thermo Fisher Scientific  
raw Files

**Version** 1.3.0

**Depends** R (>= 4.1), methods, Spectra (>= 1.5.8)

**Imports** MsCoreUtils, S4Vectors, IRanges, rawrr (>= 1.3.6), utils,  
BiocParallel

**Suggests** BiocStyle (>= 2.5), ExperimentHub, MsBackendMgf, knitr,  
lattice, mzR, protViz (>= 0.7), rmarkdown, tartare (>= 1.5),  
testthat

**Description** implements a MsBackend for the Spectra package using  
Thermo Fisher Scientific's NewRawFileReader .Net libraries.  
The package is generalizing the functionality introduced by the rawrr package  
(Kockmann T. et al. (2020) <[doi:10.1101/2020.10.30.362533](https://doi.org/10.1101/2020.10.30.362533)>)  
Methods defined in this package are supposed to extend the Spectra  
Bioconductor package.

**URL** <https://github.com/fgcz/MsBackendRawFileReader>

**BugReports** <https://github.com/fgcz/MsBackendRawFileReader/issues>

**Encoding** UTF-8

**NeedsCompilation** yes

**biocViews** MassSpectrometry, Proteomics, Metabolomics

**RoxygenNote** 7.1.2

**License** GPL-3

**SystemRequirements** mono-runtime 4.x or higher (including System.Data  
library) on Linux/macOS, .Net Framework (>= 4.5.1) on Microsoft  
Windows.

**VignetteBuilder** knitr

**Collate** 'hidden\_aliases.R' 'AllGenerics.R'  
'MsBackendRawFileReader-functions.R' 'MsBackendRawFileReader.R'  
'benchmark.R' 'zzz.R'

**git\_url** <https://git.bioconductor.org/packages/MsBackendRawFileReader>

**git\_branch** master

**git\_last\_commit** e2b206e

**git\_last\_commit\_date** 2022-04-26

**Date/Publication** 2022-05-26

**Author** Christian Panse [aut, cre] (<<https://orcid.org/0000-0003-1975-3064>>),  
Tobias Kockmann [aut] (<<https://orcid.org/0000-0002-1847-885X>>)

**Maintainer** Christian Panse <cp@fgcz.ethz.ch>

## R topics documented:

ioBenchmark	2
MsBackendRawFileReader	3
MsBackendRawFileReader-class	4

<b>Index</b>	<b>5</b>
--------------	----------

---

ioBenchmark	<i>RawFileReader_read_peaks benchmark</i>
-------------	---

---

### Description

derives numbers to evaluate time performance for reading a single spectrum in dependency from the chunk size (how many spectra are read in one function call) for reading different numbers of overall spectra.

### Usage

```
ioBenchmark(
  nv = c(1000, 5000, 10000),
  sizev = c(8, 16, 32, 64, 128, 256, 8, 16, 32, 64, 128, 256, 8, 16, 32, 64, 128, 256,
  8, 16, 32, 64, 128, 256, 8, 16, 32, 64, 128, 256, 8, 16, 32, 64, 128, 256),
  rawfile
)
```

### Arguments

nv	number of spectra to be read.
sizev	number of spectra write and parsed in one single junk.
rawfile	the Thermo Fisher Scientific raw file.

### Value

data.frame

**Examples**

```
eh <- ExperimentHub::ExperimentHub()
EH4547 <- normalizePath(eh[["EH4547"]])
(rawfileEH4547 <- paste0(EH4547 , ".raw"))
if (!file.exists(rawfileEH4547 )){
  file.link(EH4547 , rawfileEH4547)
}
S <- ioBenchmark(1000, c(128, 256, 128, 256), rawfile=rawfileEH4547)
```

---

MsBackendRawFileReader

*MsBackendRawFileReader*

---

**Description**

MsBackendRawFileReader

**Usage**

```
MsBackendRawFileReader()
```

```
## S4 method for signature 'MsBackendRawFileReader'
filterScan(object, filter = character(), ...)
```

```
## S4 method for signature 'MsBackendRawFileReader'
scanType(object, ...)
```

**Arguments**

object	MsBackendRawFileReader object
filter	filter string
...	Arguments to be passed to methods.

**Value**

a MsBackendRawFileReader object.

a character vector of scan types.

**Examples**

```
beRaw <- Spectra::backendInitialize(MsBackendRawFileReader::MsBackendRawFileReader(),
  files = rawrr::sampleFilePath())
beRaw |> MsBackendRawFileReader::filterScan('Ms')
beRaw <- Spectra::backendInitialize(MsBackendRawFileReader::MsBackendRawFileReader(),
  files = rawrr::sampleFilePath())
scanType(beRaw) |> head()
```

---

MsBackendRawFileReader-class

*RawFileReader-based backend*

---

### **Description**

The ‘MsBackendRawFileReader’ inherits all slots and methods from the base ‘MsBackendDataFrame’ (in-memory) backend. It overrides the base ‘mz’ and ‘intensity’ methods as well as ‘peaksData’ to read the respective data from the original raw data files.

The validator function has to ensure that the files exist and that required column names are present.

The ‘backendInitialize’ method reads the header data from the raw files and hence fills the ‘spectra-Data’ slot.

### **Author(s)**

Christian Panse (2019-2021)

### **Examples**

```
beRaw <- Spectra::backendInitialize(MsBackendRawFileReader::MsBackendRawFileReader(),
  files = rawrr::sampleFilePath())
beRaw
Spectra::msLevel(beRaw)
```

# Index

`filterScan`, `MsBackendRawFileReader`-method  
(`MsBackendRawFileReader`), [3](#)

`ioBenchmark`, [2](#)

`MsBackendRawFileReader`, [3](#)

`MsBackendRawFileReader`-class, [4](#)

`scanType`, `MsBackendRawFileReader`-method  
(`MsBackendRawFileReader`), [3](#)