

# Package ‘octad.db’

April 18, 2024

**Title** Open Cancer TherApeutic Discovery (OCTAD) database

**Version** 1.5.0

**Description** Open Cancer TherApeutic Discovery (OCTAD) package implies sRGES approach for the drug discovery. The essential idea is to identify drugs that reverse the gene expression signature of a disease by tamping down over-expressed genes and stimulating weakly expressed ones. The following package contains all required precomputed data for whole OCTAD pipeline computation.

**License** Artistic-2.0

**Encoding** UTF-8

**LazyData** false

**Roxygen** list(markdown = TRUE)

**RoxygenNote** 7.2.1

**Depends** R (>= 4.2.0), ExperimentHub

**biocViews** ExperimentData, CancerData, ExperimentHub, SequencingData, ExpressionData

**VignetteBuilder** knitr

**Suggests** knitr, rmarkdown

**git\_url** <https://git.bioconductor.org/packages/octad.db>

**git\_branch** devel

**git\_last\_commit** e7762ec

**git\_last\_commit\_date** 2023-10-24

**Repository** Bioconductor 3.19

**Date/Publication** 2024-04-18

**Author** E. Chekalin [aut, cre],  
S. Paithankar [aut],  
B. Zeng [aut],  
B. Glicksberg [ctb],  
P. Newbury [ctb],  
J. Xing [ctb],  
K. Liu [ctb],

A. Wen [ctb],  
 D. Joseph [ctb],  
 B. Chen [aut]

**Maintainer** E. Chekalin <eygen.chekalin@gmail.com>

## Contents

get_ExperimentHub_data . . . . .	2
octad.db . . . . .	3
<b>Index</b>	<b>5</b>

---

get\_ExperimentHub\_data  
*Download file from Experimental Hub*

---

### Description

Download file from Experimental Hub.

### Usage

```
get_ExperimentHub_data(file=NULL)
```

### Arguments

file                    file id do download it from Experimental Hub archive

### Value

Returns a data.frame object depends on the call

### See Also

[octad.db](#).

### Examples

```
phenoDF=get_ExperimentHub_data("EH7274") #load data.frame with samples included in the OCTAD database.
head(phenoDF)
```

---

`octad.db`*Open Cancer Therapeutic Discovery (OCTAD) database package*

---

## Description

This is a support package for the main package `octad` which can be obtained [here](#)

## Details

Package includes all required data for drug repurposing OCTAD pipeline. Initialization of the pipeline starts with listing all available samples:

```
phenoDF=.eh[["EH7274"]] #load data.frame with samples included in the OCTAD database. head(phenoDF)
#list all data included within the package
```

Besides, the package includes examples of the output from `diffExp` and `runsRGES` functions from the `octad` package along with description of the data: `res=octad.db::res_example` #load example `res` from `octad.db` ?`res_example` `sRGES=octad.db::sRGES_example` #load example `sRGES` from `octad.db` ?`sRGES_example`

`CCLC.log2.read.count.matrix` log2-transformed matrix containing expression of 56,318 genes in 1,019 cell lines provided in CCLC database `CCLC.overlaps` log2-transformed matrix containing expression of 56,318 genes in 51 cell lines present in both LINCS and CCLC databases `CCLC.sample.meta` data.frame containing cell lines name and tissue of origin from CCLC database `CTRPv2.sensprof` Cancer Therapeutics Response Portal (CTRP) data.frame containing AUC and IC50 for every drug-cell line pair `EncoderDF` a data.frame (64 features by 19127 samples) computed from `autoEncoder` for every sample in the OCTAD database `compd_sets_ChemCluster` list of compounds and their clusters based on chemical structures `compd_sets_mesh` list of compounds and their associations with 662 pharmacological MeSH Terms provided in PubChem `fda_drugs` data.frame of FDA approved drugs containing name, target and clinical phase `lincs_sig_info` data.frame for LINCS signatures including experiment id, cell line used in the experiment, perturbation name, perturbation type, dose and time `lincs_signatures` Differential expression of 978 genes in 416,560 experiments `merged_gene_info` data.frame with the annotation of 75,078 genes which could be used for identifier mapping `octad.LINCS.counts` expression matrix of 965 genes and 19127 samples in OCTAD database (965 genes were profiled in LINCS) `phenoDF` data.frame with samples from the OCTAD database including tissue of origin, sample type (tumor-derived or healthy-derived), cancer, original source (e.g. TCGA), mutation and stage data if available `random_gsea_score` pre-computed permuted gsea scores for chembl, mesh and ChemCluster databases that are used for drug enrichment analysis `tsne` 2 dimension tSNE for every sample in the OCTAD database along with `sample.id`, cancer type and source of the initial data `octad.counts.and.tpm` h5 expression (TPM and raw counts) matrix of 60,498 genes and 19,127 samples

The code can be viewed at the GitHub repository, which also lists the contributor code of conduct:

<https://bioconductor.org/packages/octad> or <https://github.com/Bin-Chen-Lab/octad> for the pipeline package

## References

Zeng, B., Glucksberg, B.S., Newbury, P., Chekalin, E., Xing, J., Liu, K., Wen, A., Chow, C. and Chen, B., 2021. OCTAD: an open workspace for virtually screening therapeutics targeting precise

cancer patient groups using gene expression features. Nature protocols, 16(2), pp.728-753. <https://www.nature.com/articles/s41596-020-00430-z>

# Index

\* **get\_ExperimentHub\_data**  
    [get\\_ExperimentHub\\_data, 2](#)

[get\\_ExperimentHub\\_data, 2](#)

[octad.db, 2, 3](#)