

Package ‘DiffLogo’

September 4, 2024

Type Package

Title DiffLogo: A comparative visualisation of biooligomer motifs

Version 2.28.0

Date 2015-02-12

Author c(

```
person(` `Martin", ` `Nettling", role = c(` `aut", ` `cre"), email = ` `mar-
tin.nettling@informatik.uni-halle.de"),
person(` `Hendrik", ` `Tretler", role = c(` `aut", ` `cre"), email = ` `hendrik.tretler@ipb-
halle.de"),
person(` `Jan", ` `Grau", role = c(` `aut", ` `ctb"), email = ` `grau@informatik.uni-halle.de"),
person(` `Andrey", ` `Lando", role = c(` `aut", ` `ctb"), email = ` `dronte@autosome.ru"),
person(` `Jens", ` `Keilwagen", role = c(` `aut", ` `ctb"), email = ` `jens.keilwagen@julius-
kuehn.de"),
person(` `Stefan", ` `Posch", role = ` `aut", email = ` `posch@informatik.uni-halle.de"),
person(` `Ivo", ` `Grosse", role = ` `aut", email = ` `grosse@informatik.uni-halle.de"))
```

Depends R (>= 3.4), stats, cba

Imports grDevices, graphics, utils, tools

Suggests knitr, testthat, seqLogo, MotifDb

Maintainer Hendrik Tretler<hendrik.tretler@gmail.com>

Description DiffLogo is an easy-to-use tool to visualize motif differences.

License GPL (>= 2)

URL <https://github.com/mgledi/DiffLogo/>

BugReports <https://github.com/mgledi/DiffLogo/issues>

biocViews Software, SequenceMatching, MultipleComparison,
MotifAnnotation, Visualization, Alignment

Collate 'alphabet.R' 'baseDistrs.R' 'diffSeqLogo.R' 'preconditions.R'
'seqLogo.R' 'stackHeights.R' 'utilities.R'
'diffSeqLogoSupport.R' 'pwmAlignment.R'

RoxygenNote 6.1.1

git_url <https://git.bioconductor.org/packages/DiffLogo>

git_branch RELEASE_3_19

git_last_commit 7ff879d

git_last_commit_date 2024-04-30

Repository Bioconductor 3.19

Date/Publication 2024-09-04

Contents

| | |
|---|----|
| alignPwmSets | 3 |
| Alphabet | 4 |
| ASN | 4 |
| baseDistributionPwm | 5 |
| calculatePvalue | 5 |
| createDiffLogoObject | 6 |
| differenceOfICs | 8 |
| diffLogo | 9 |
| diffLogoFromPwm | 10 |
| diffLogoTable | 11 |
| diffLogoTableConfiguration | 12 |
| DNA | 13 |
| drawDiffLogoTable | 14 |
| enrichDiffLogoObjectWithPvalues | 15 |
| enrichDiffLogoTableWithPvalues | 16 |
| extendPwmsFromAlignmentVector | 17 |
| FULL_ALPHABET | 18 |
| getAlphabetFromCharacters | 18 |
| getAlphabetFromSequences | 19 |
| getPwmFromAlignment | 19 |
| getPwmFromAlignmentFile | 20 |
| getPwmFromFastaFile | 21 |
| getPwmFromFile | 21 |
| getPwmFromHomerFile | 22 |
| getPwmFromPfmOrJasparFile | 22 |
| getPwmFromPwmFile | 23 |
| getSequencesFromAlignmentFile | 23 |
| getSequencesFromFastaFile | 24 |
| informationContent | 25 |
| localPwmAlignment | 25 |
| lossOfAbsICDifferences | 26 |
| multipleLocalPwmsAlignment | 27 |
| normalizedDifferenceOfProbabilities | 28 |
| normalizePWM | 29 |
| prepareDiffLogoTable | 30 |
| probabilities | 31 |
| pwmDivergence | 31 |
| pwmsDistanceMatrix | 32 |

alignPwmSets 3

| | |
|--|----|
| reverseAlignmentVector | 33 |
| RNA | 33 |
| seqLogo | 34 |
| shannonDivergence | 35 |
| sumOfAbsICDifferences | 36 |
| sumOfAbsProbabilityDifferences | 37 |
| sumProbabilities | 38 |
| switchDirection | 38 |
| twoSetsAveragePwmDivergenceFromAlignmentVector | 39 |

Index 40

alignPwmSets *Multiple PWMs alignment*

Description

Align two sets of pwms

Usage

```
alignPwmSets(left_pwms_set, left_alignment, right_pwms_set,  
             right_alignment, try_reverse_complement)
```

Arguments

`left_pwms_set` list of pwms(matrixes)
`left_alignment` alignment of left_pwms_set.
`right_pwms_set` list of pwms;
`right_alignment`
 alignment of right_pwms_set.
`try_reverse_complement`
 if true(default), also try reverse complement.

Value

list - alignment of concatenation of left_pwms_set and right_pwms_set

Author(s)

Lando Andrey

| | |
|----------|-----------------------|
| Alphabet | <i>built alphabet</i> |
|----------|-----------------------|

Description

builds an object of class Alphabet from the given set of symbols and colors

Usage

```
Alphabet(chars, cols, supportReverseComplement)
```

Arguments

| | |
|--------------------------|--|
| chars | set of symbols |
| cols | set of colors; one for each symbol |
| supportReverseComplement | boolean whether the alphabet supports reverse complementation (like DNA/RNA) or not (like ASN) |

Value

the Alphabet object

Author(s)

Martin Nettling

Examples

```
DNA = Alphabet(c("A", "C", "G", "T"), c("green4", "blue", "orange", "red"), TRUE)
```

| | |
|-----|---------------------|
| ASN | <i>ASN alphabet</i> |
|-----|---------------------|

Description

the amino acid alphabet (20 symbols), i.e. A, C, D, E, F, G, H, I, K, L, M, N, P, Q, R, S, T, V, W, Y

Usage

```
ASN
```

Format

An object of class Alphabet of length 4.

Author(s)

Martin Nettling

Examples

ASN

baseDistributionPwm *Generates a PWM*

Description

Generates a PWM consisting of only the uniform distribution or the given base_distribution (if defined).

Usage

```
baseDistributionPwm(pwm_length, alphabet_length,
  base_distribution = NULL)
```

Arguments

pwm_length the number of positions
 alphabet_length the alphabet size
 base_distribution optional base distribution for each PWM position

Value

a PWM

calculatePvalue *p-value that two PWM-positions are from the same distribution*

Description

Calculates the p-value for the null-hypothesis that two given probability vectors p1, p2 calculated from n1/n2 observations arise from the same distribution

Usage

```
calculatePvalue(p1, p2, n1, n2, stackHeight = shannonDivergence,
  numberOfPermutations = 100, plotGammaDistributionFit = FALSE)
```

Arguments

p1 first probability vector with one probability for each symbol of the alphabet
p2 second probability vector with one probability for each symbol of the alphabet
n1 number of observations for the calculation of p1
n2 number of observations for the calculation of p2
stackHeight function for the calculation of a divergence measure for two probability vectors
numberOfPermutations the number of permutations to perform for the calculation of stackHeights
plotGammaDistributionFit if TRUE the fit of a gamma distribution to the sampled stackHeights is plotted

Value

a numeric p-value

Author(s)

Hendrik Treutler

Examples

```

p1 <- c(0.2, 0.3, 0.1, 0.4)
p2 <- c(0.2, 0.1, 0.3, 0.4)
n1 <- 100
n2 <- 200
numberOfPermutations = 100
plotGammaDistributionFit = TRUE

pValue <- calculatePvalue(p1 = p1, p2 = p2, n1 = n1, n2 = n2, stackHeight = shannonDivergence, numberOfPermutations

```

createDiffLogoObject *DiffLogo object*

Description

Creates a DiffLogo object

Usage

```

createDiffLogoObject(pwm1, pwm2, stackHeight = shannonDivergence,
  baseDistribution = normalizedDifferenceOfProbabilities,
  alphabet = DNA, align_pwm = FALSE,
  unaligned_penalty = divergencePenaltyForUnaligned,
  try_reverse_complement = TRUE, base_distribution = NULL,
  length_normalization = FALSE, unaligned_from_left = 0,
  unaligned_from_right = 0)

```

Arguments

| | |
|------------------------|--|
| pwm1 | representation of the first position weight matrix (PWM) of type pwm, data.frame, or matrix |
| pwm2 | representation of the second position weight matrix (PWM) of type pwm, data.frame, or matrix |
| stackHeight | function for the height of a stack at position i |
| baseDistribution | function for the heights of the individual bases |
| alphabet | of type Alphabet |
| align_pwm | if True, will align and extend pwms. |
| unaligned_penalty | is a function for localPwmAlignment. |
| try_reverse_complement | if True, alignment will try reverse complement pwms |
| base_distribution | is a vector of length nrow(pwm) that is added to unaligned columns of pwms for comparing. If NULL, uniform distribution is used |
| length_normalization | If true, will minimize the average divergence between PWMs. Otherwise will minimize the sum of divergences between positions. In both cases unaligned positions are compared to base_distribution and are counted when computing the alignment length. |
| unaligned_from_left | the number of unaligned positions on the left |
| unaligned_from_right | the number of unaligned positions on the right |

Value

DiffLogo object

Author(s)

Martin Nettling

Examples

```

motif_folder= "extdata/pwm"
motif_names = c("HepG2", "MCF7", "HUVEC", "ProgFib")
motifs = list()
for (name in motif_names) {
  fileName = paste(motif_folder, "/", name, ".pwm", sep="")
  file = system.file(fileName, package = "DiffLogo")
  motifs[[name]] = getPwmFromPwmFile(file)
}

pwm1 = motifs[[motif_names[[1]]]]

```

```

pwm2 = motifs[[motif_names[[2]]]]

diffLogoObj = createDiffLogoObject(pwm1 = pwm1, pwm2 = pwm2)
diffLogo(diffLogoObj)

```

| | |
|-----------------|---|
| differenceOfICs | <i>normalized information content differences</i> |
|-----------------|---|

Description

information content differences normalized by the sum of absolute information content differences for the given pair of probability vectors

Usage

```
differenceOfICs(p1, p2)
```

Arguments

| | |
|----|--|
| p1 | probability vector representing the first symbol distribution |
| p2 | probability vector representing the second symbol distribution |

Value

a vector with one result for each symbol

Author(s)

Martin Nettling

Examples

```

motif_folder= "extdata/pwm"
motif_names = c("HepG2","MCF7","HUVEC","ProgFib")
motifs = list()
for (name in motif_names) {
  fileName = paste(motif_folder,"/",name,".pwm",sep="")
  file = system.file(fileName, package = "DiffLogo")
  motifs[[name]] = getPwmFromPwmFile(file)
}

pwm1 = motifs[[motif_names[[1]]]]
pwm2 = motifs[[motif_names[[2]]]]

diffLogoFromPwm(pwm1 = pwm1, pwm2 = pwm2, baseDistribution = differenceOfICs)

```

`diffLogo`*Draw DiffLogo*

Description

Draws the difference of two sequence logos.

Usage

```
diffLogo(diffLogoObj, ymin = 0, ymax = 0, sparse = FALSE,  
diffLogoConfiguration = list())
```

Arguments

| | |
|------------------------------------|---|
| <code>diffLogoObj</code> | a DiffLogoObject created by the function <code>createDiffLogoObject</code> |
| <code>ymin</code> | minimum value on the y-axis |
| <code>ymax</code> | maximum value on the y-axis |
| <code>sparse</code> | if TRUE margins are reduced and tickmarks are removed from the logo |
| <code>diffLogoConfiguration</code> | list of configuration parameters (see function <code>diffLogoTableConfiguration(...)</code>) |

Value

none (draws difference logo)

Author(s)

Martin Nettling

Examples

```
motif_folder= "extdata/pwm"  
motif_names = c("HepG2", "MCF7", "HUVEC", "ProgFib")  
motifs = list()  
for (name in motif_names) {  
  fileName = paste(motif_folder, "/", name, ".pwm", sep="")  
  file = system.file(fileName, package = "DiffLogo")  
  motifs[[name]] = getPwmFromPwmFile(file)  
}  
  
pwm1 = motifs[[motif_names[[1]]]]  
pwm2 = motifs[[motif_names[[2]]]]  
  
diffLogoObj = createDiffLogoObject(pwm1 = pwm1, pwm2 = pwm2)  
diffLogo(diffLogoObj)
```

diffLogoFromPwm

Draw DiffLogo from PWM

Description

Draws the difference of two sequence logos.

Usage

```
diffLogoFromPwm(pwm1, pwm2, ymin = 0, ymax = 0,
  stackHeight = shannonDivergence,
  baseDistribution = normalizedDifferenceOfProbabilities,
  sparse = FALSE, alphabet = DNA, align_pwm = FALSE,
  unaligned_penalty = divergencePenaltyForUnaligned,
  try_reverse_complement = TRUE, base_distribution = NULL,
  length_normalization = FALSE)
```

Arguments

| | |
|------------------------|--|
| pwm1 | representation of the first position weight matrix (PWM) of type pwm, data.frame, or matrix |
| pwm2 | representation of the second position weight matrix (PWM) of type pwm, data.frame, or matrix |
| ymin | minimum value on the y-axis |
| ymax | maximum value on the y-axis |
| stackHeight | function for the height of a stack at position i |
| baseDistribution | function for the heights of the individual bases |
| sparse | if TRUE margins are reduced and tickmarks are removed from the logo |
| alphabet | of type Alphabet |
| align_pwm | if true, DiffLogo will align pwms before plotting |
| unaligned_penalty | is a function for localPwmAlignment. |
| try_reverse_complement | if True, alignment will try reverse complement pwms |
| base_distribution | is a vector of length nrow(pwm) that is added to unaligned columns of pwms for comparing. If NULL, uniform distribution is used |
| length_normalization | If true, will minimize the average divergence between PWMs. Otherwise will minimize the sum of divergences between positions. In both cases unaligned positions are compared to base_distribution and are counted when computing the alignment length. |

Value

none (draws difference logo)

Author(s)

Martin Nettling

Examples

```

motif_folder= "extdata/pwm"
motif_names = c("HepG2","MCF7","HUVEC","ProgFib")
motifs = list()
for (name in motif_names) {
  fileName = paste(motif_folder,"/",name,".pwm",sep="")
  file = system.file(fileName, package = "DiffLogo")
  motifs[[name]] = getPwmFromPwmFile(file)
}

pwm1 = motifs[[motif_names[[1]]]]
pwm2 = motifs[[motif_names[[2]]]]

diffLogoFromPwm(pwm1 = pwm1, pwm2 = pwm2)

```

diffLogoTable

Draw DiffLogo-table

Description

Draws a table of DiffLogos.

Usage

```
diffLogoTable(PWMs, sampleSizes = NULL, alphabet = DNA,
  configuration = list(), ...)
```

Arguments

| | |
|---------------|--|
| PWMs | a list/vector of position weight matrices (PWMs) each of type pwm, data.frame, or matrix |
| sampleSizes | the number of sequences behind each PWM |
| alphabet | the alphabet of the given PWMs |
| configuration | list of (probably part of) of configuration options. See diffLogoTableConfiguration. |
| ... | set of parameters passed to the function 'axis' for plotting |

Value

none (draws table of difference logos)

Author(s)

Martin Nettling

Examples

```

motif_folder= "extdata/pwm"
motif_names = c("HepG2","MCF7","HUVEC","ProgFib")
motifs = list()
for (name in motif_names) {
  fileName = paste(motif_folder,"/",name,".pwm",sep="")
  file = system.file(fileName, package = "DiffLogo")
  motifs[[name]] = getPwmFromPwmFile(file)
}

diffLogoTable(motifs)

```

diffLogoTableConfiguration

Configuration object for diffLogoTable

Description

Default configuration list for diffLogoTable

Usage

```

diffLogoTableConfiguration(alphabet, stackHeight = shannonDivergence,
  baseDistribution = normalizedDifferenceOfProbabilities,
  uniformYaxis = TRUE, sparse = TRUE, showSequenceLogosTop = TRUE,
  enableClustering = TRUE, treeHeight = 0.5, margin = 0.02,
  ratio = 1, align_pwm = FALSE, multiple_align_pwm = TRUE,
  unaligned_penalty = divergencePenaltyForUnaligned,
  try_reverse_complement = TRUE, length_normalization = FALSE,
  numberOfPermutations = 100)

```

Arguments

| | |
|----------------------|---|
| alphabet | used alphabet of type Alphabet |
| stackHeight | function for the height of a stack at position i |
| baseDistribution | function for the heights of the individual bases |
| uniformYaxis | if TRUE each DiffLogo is plotted with the same scaling of the y-axis |
| sparse | if TRUE margins are reduced and tickmarks are removed from the logo |
| showSequenceLogosTop | if TRUE the classical sequence logos are drawn above each column of the table |

| | |
|-------------------------------------|---|
| <code>enableClustering</code> | if TRUE the motifs are reordered, so that similar motifs have a small vertical and horizontal distance in the table |
| <code>treeHeight</code> | the height of the plotted cluster tree above the columns of the table; set equal to zero to omit the cluster tree |
| <code>margin</code> | the space reserved for labels |
| <code>ratio</code> | the ratio of the plot; this is needed to determine the margin sizes correctly |
| <code>align_pwm</code> | if True, will align and extend pwms in each cell of <code>diffLogoTable</code> independently. |
| <code>multiple_align_pwm</code> | if True, will align and extend pwms in the <code>diffLogoTable</code> jointly. |
| <code>unaligned_penalty</code> | is a function for <code>localPwmAlignment</code> . |
| <code>try_reverse_complement</code> | if True, alignment will try reverse complement pwms |
| <code>length_normalization</code> | if True, divergence between pwms is divided by length of pwms. |
| <code>numberOfPermutations</code> | number of permutations for the permutation test for the calculation of p-values |

Value

list of parameters

Author(s)

Lando Andrey

Examples

```
diffLogoTableConfiguration(DNA)
```

DNA

DNA alphabet

Description

the DNA alphabet, i.e. A, C, G, T

Usage

DNA

Format

An object of class `Alphabet` of length 4.

Author(s)

Martin Nettling

Examples

DNA

| | |
|-------------------|-----------------------------------|
| drawDiffLogoTable | <i>Draws a table of DiffLogos</i> |
|-------------------|-----------------------------------|

Description

Draws a table of DiffLogos.

Usage

```
drawDiffLogoTable(diffLogoTableObj, ...)
```

Arguments

```
diffLogoTableObj    the diffLogoTable-Object created by function prepareDiffLogoTable(...)
...                  optional parameters for function axis
```

Value

none (draws difference logo)

Examples

```
motif_folder= "extdata/pwm"
motif_names = c("HepG2", "MCF7", "HUVEC", "ProgFib")
motifs = list()
for (name in motif_names) {
  fileName = paste(motif_folder, "/", name, ".pwm", sep="")
  file = system.file(fileName, package = "DiffLogo")
  motifs[[name]] = getPwmFromPwmFile(file)
}

diffLogoTableObj = prepareDiffLogoTable(motifs)
drawDiffLogoTable(diffLogoTableObj)
```

`enrichDiffLogoObjectWithPvalues`*Enriches a difflogo object with p-values*

Description

Enriches a difflogo object with p-values which quantifies the probability that two PWM-positions are from the same distribution

Usage

```
enrichDiffLogoObjectWithPvalues(diffLogoObj, n1, n2,  
  stackHeight = shannonDivergence, numberOfPermutations = 100)
```

Arguments

| | |
|-----------------------------------|--|
| <code>diffLogoObj</code> | matrix of difflogo objects |
| <code>n1</code> | the number of sequences behind the first pwm behind the given difflogo object |
| <code>n2</code> | the number of sequences behind the second pwm behind the given difflogo object |
| <code>stackHeight</code> | function for the calculation of a divergence measure for two probability vectors |
| <code>numberOfPermutations</code> | the number of permutations to perform for the calculation of stackHeights |

Value

enriched difflogo object

Examples

```
motif_folder= "extdata/pwm"  
motif_names = c("HepG2", "MCF7", "HUVEC", "ProgFib")  
motifs = list()  
for (name in motif_names) {  
  fileName = paste(motif_folder, "/", name, ".pwm", sep="")  
  file = system.file(fileName, package = "DiffLogo")  
  motifs[[name]] = getPwmFromPwmFile(file)  
}  
  
pwm1 = motifs[[motif_names[[1]]]]  
pwm2 = motifs[[motif_names[[2]]]]  
n1 <- 100  
n2 <- 100  
diffLogoObj = createDiffLogoObject(pwm1 = pwm1, pwm2 = pwm2)  
diffLogoObj = enrichDiffLogoObjectWithPvalues(diffLogoObj, n1, n2)
```

enrichDiffLogoTableWithPvalues

Enriches a matrix of difflogo objects with p-values

Description

Enriches a matrix of difflogo objects with p-values which quantifies the probability that two PWM-positions are from the same distribution

Usage

```
enrichDiffLogoTableWithPvalues(diffLogoObjMatrix, sampleSizes,  
  stackHeight = shannonDivergence, numberOfPermutations = 100)
```

Arguments

| | |
|----------------------|--|
| diffLogoObjMatrix | matrix of difflogo objects |
| sampleSizes | number of sequences behind the pwms behind the given difflogo objects |
| stackHeight | function for the calculation of a divergence measure for two probability vectors |
| numberOfPermutations | the number of permutations to perform for the calculation of stackHeights |

Value

matrix of difflogo objects enriched with p-values

Author(s)

Martin Nettling

Examples

```
motif_folder= "extdata/pwm"  
motif_names = c("HepG2", "MCF7", "HUVEC", "ProgFib")  
motifs = list()  
for (name in motif_names) {  
  fileName = paste(motif_folder, "/", name, ".pwm", sep="")  
  file = system.file(fileName, package = "DiffLogo")  
  motifs[[name]] = getPwmFromPwmFile(file)  
}  
sampleSizes <- c(100, 150, 200, 250)  
names(sampleSizes) <- motif_names  
  
diffLogoTableObj = prepareDiffLogoTable(motifs);  
diffLogoTableObj$diffLogoObjMatrix = enrichDiffLogoTableWithPvalues(diffLogoTableObj$diffLogoObjMatrix, sampleS
```

`extendPwmsFromAlignmentVector`*Extend pwms with respect to alignment*

Description

Extends pwms by adding `base_distribution` to both sides, so that they keep aligned, but have equal length.

Usage

```
extendPwmsFromAlignmentVector(pwms, alignment_vector,  
  base_distribution = NULL)
```

Arguments

`pwms` is a list of matrixes
`alignment_vector` is a list of shifts (`$shift`) and orientations (`$direction`)
`base_distribution` is a vector of length `nrow(pwm)` that is added to unaligned columns of pwms for comparing. If `NULL`, uniform distribution is used

Value

extended pwms

Author(s)

Lando Andrey

Examples

```
file1 = system.file("extdata/homer/Max.motif", package = "DiffLogo")  
file2 = system.file("extdata/homer/c-Myc.motif", package = "DiffLogo")  
pwm1 = getPwmFromFile(file1)  
pwm2 = getPwmFromFile(file2)  
  
pwms <- list(pwm1, pwm2)  
multiple_pwms_alignment = multipleLocalPwmsAlignment(pwms)  
aligned_pwms = extendPwmsFromAlignmentVector(pwms, multiple_pwms_alignment$alignment$vector)
```

FULL_ALPHABET *Complete character alphabet*

Description

the alphabet of all 26 characters

Usage

FULL_ALPHABET

Format

An object of class Alphabet of length 4.

Author(s)

Hendrik Treutler

Examples

FULL_ALPHABET

getAlphabetFromCharacters
returns the alphabet which fits to the given characters

Description

returns the alphabet which fits to the given characters

Usage

getAlphabetFromCharacters(characters)

Arguments

characters a character vector of characters

Value

an alphabet of type Alphabet

Examples

```
alphabet = getAlphabetFromSequences(c("A", "A", "C", "C", "G", "G", "T", "T"))
```

`getAlphabetFromSequences`*returns the alphabet which fits to the given sequences*

Description

returns the alphabet which fits to the given sequences

Usage

```
getAlphabetFromSequences(sequences)
```

Arguments

sequences a character vector of sequences

Value

an alphabet of type Alphabet

Examples

```
alphabet = getAlphabetFromSequences("AACCGGTT")
```

`getPwmFromAlignment` *Create PWM from alignment*

Description

Creates a matrix-representation of a PWM from a set of sequences

Usage

```
getPwmFromAlignment(alignment, alphabet = NULL, pseudoCount = 0)
```

Arguments

alignment a vector or list of sequences each with equal length
alphabet of type Alphabet
pseudoCount the number of pseudo-observations for each character in the alphabet

Value

PWM as matrix

Author(s)

Hendrik Treutler

Examples

```
motif_folder= "extdata/alignments"  
motif_name = "calamodulin_1"  
fileName = paste(motif_folder,"/",motif_name,".txt",sep="")  
file = system.file(fileName, package = "DiffLogo")  
motif = getPwmFromAlignment(readLines(file), ASN, 1)  
seqLogo(pwm = motif, alphabet=ASN)
```

getPwmFromAlignmentFile

generates a pwm from an alignment file

Description

generates a pwm from an alignment file

Usage

```
getPwmFromAlignmentFile(filename, alphabet = NULL)
```

Arguments

| | |
|----------|---------------------------------------|
| filename | the alignment file |
| alphabet | the desired alphabet of type Alphabet |

Value

a pwm

Examples

```
fileName = "extdata/alignments/calamodulin_1.txt"  
file = system.file(fileName, package = "DiffLogo")  
pwm = getPwmFromAlignmentFile(file)
```

getPwmFromFastaFile *generates a pwm from a FASTA file*

Description

generates a pwm from a FASTA file

Usage

```
getPwmFromFastaFile(filename, alphabet = NULL)
```

Arguments

| | |
|----------|---------------------------------------|
| filename | the FASTA file |
| alphabet | the desired alphabet of type Alphabet |

Value

a pwm

Examples

```
fileName = "extdata/alignments/F-box_bacteria.seq.fa"  
file = system.file(fileName, package = "DiffLogo")  
pwm = getPwmFromFastaFile(file)
```

getPwmFromFile *generates a pwm from a file of different formats*

Description

Generates a pwm from a file of different formats. Supported formats are FASTA files (.fa, .fasta), alignment files (.txt, .text, .al, .alignment), PWM files (.pwm), JASPAR / Position Frequency Matrix files (.pfm), and homer files (.motif).

Usage

```
getPwmFromFile(filename)
```

Arguments

| | |
|----------|----------|
| filename | the file |
|----------|----------|

Value

a pwm

Examples

```
fileName = "extdata/pwm/H1-hESC.pwm"  
file = system.file(fileName, package = "DiffLogo")  
pwm = getPwmFromFile(file)
```

getPwmFromHomerFile *generates a pwm from a homer file*

Description

generates a pwm from a homer file

Usage

```
getPwmFromHomerFile(filename)
```

Arguments

filename the homer file

Value

a pwm

Examples

```
fileName = "extdata/homer/CTCF_Zf_CD4.motif"  
file = system.file(fileName, package = "DiffLogo")  
pwm = getPwmFromHomerFile(file)
```

getPwmFromPfmOrJasparFile
 generates a pwm from a jaspar file

Description

generates a pwm from a jaspar file

Usage

```
getPwmFromPfmOrJasparFile(filename)
```

Arguments

filename the jaspar file

Value

a pwm

Examples

```
fileName = "extdata/pfm/ctcf_jaspar.pfm"  
file = system.file(fileName, package = "DiffLogo")  
pwm = getPwmFromPfmOrJasparFile(file)
```

`getPwmFromPwmFile` *generates a pwm from a pwm file*

Description

generates a pwm from a pwm file

Usage

```
getPwmFromPwmFile(filename)
```

Arguments

filename the pwm file

Value

a pwm

Examples

```
fileName = "extdata/pwm/H1-hESC.pwm"  
file = system.file(fileName, package = "DiffLogo")  
pwm = getPwmFromPwmFile(file)
```

`getSequencesFromAlignmentFile`
extracts the sequences from an alignment file

Description

extracts the sequences from an alignment file

Usage

```
getSequencesFromAlignmentFile(filename)
```

Arguments

filename the alignment file

Value

a vector of sequences

Examples

```
fileName = "extdata/alignments/calamodulin_1.txt"
file = system.file(fileName, package = "DiffLogo")
sequences = getSequencesFromAlignmentFile(file)
```

getSequencesFromFastaFile

extracts the sequences from a FASTA file

Description

extracts the sequences from a FASTA file

Usage

```
getSequencesFromFastaFile(filename)
```

Arguments

filename the FASTA file

Value

a vector of sequences

Examples

```
fileName = "extdata/alignments/F-box_bacteria.seq.fa"
file = system.file(fileName, package = "DiffLogo")
sequences = getSequencesFromFastaFile(file)
```

| | |
|--------------------|----------------------------|
| informationContent | <i>information content</i> |
|--------------------|----------------------------|

Description

the information content for the given probability vector

Usage

```
informationContent(p)
```

Arguments

`p` probability vector representing the symbol distribution

Value

an object consisting of height a ylab

Author(s)

Martin Nettling

Examples

```
motif_folder= "extdata/pwm"  
motif_name = "HepG2"  
fileName = paste(motif_folder,"/",motif_name,".pwm",sep="")  
file = system.file(fileName, package = "DiffLogo")  
motif = getPwmFromPwmFile(file)  
seqLogo(pwm = motif, stackHeight = informationContent)
```

| | |
|-------------------|-------------------|
| localPwmAlignment | <i>Align pwms</i> |
|-------------------|-------------------|

Description

Finds best local alignment for two PWMs.

Usage

```
localPwmAlignment(pwm_left, pwm_right, divergence = shannonDivergence,  
  unaligned_penalty = divergencePenaltyForUnaligned,  
  try_reverse_complement = TRUE, base_distribution = NULL,  
  length_normalization = FALSE)
```

Arguments

| | |
|------------------------|--|
| pwm_left | first PWM, a matrix of type matrix |
| pwm_right | first PWM, a matrix of type matrix |
| divergence | is a measure of difference between two pwm columns. Smaller is more similar. If you want to use non-uniform background distribution, provide your own function. |
| unaligned_penalty | distance for unaligned columns at edges of matrixes. See divergencePenalty-ForUnaligned as an example for providing your own function |
| try_reverse_complement | If false the alignment will not be performed on reverse complements. If true, the input pwms should have column order of ACTG/ACGU. |
| base_distribution | is a vector of length nrow(pwm) that is added to unaligned columns of pwms for comparing. If NULL, uniform distribution is used |
| length_normalization | If true, will minimize the average divergence between PWMs. Otherwise will minimize the sum of divergences between positions. In both cases unaligned positions are compared to base_distribution and are counted when computing the alignment length. |

Value

list of length two containing the alignment and the divergence

Author(s)

Lando Andrey

lossOfAbsICDifferences

the change of information content

Description

the change of information content for the given probability vectors

Usage

```
lossOfAbsICDifferences(p1, p2)
```

Arguments

| | |
|----|--|
| p1 | probability vector representing the first symbol distribution |
| p2 | probability vector representing the second symbol distribution |

Value

an object consisting of height and ylab

Author(s)

Martin Nettling

Examples

```

motif_folder= "extdata/pwm"
motif_names = c("HepG2","MCF7","HUVEC","ProgFib")
motifs = list()
for (name in motif_names) {
  fileName = paste(motif_folder,"/",name,".pwm",sep="")
  file = system.file(fileName, package = "DiffLogo")
  motifs[[name]] = getPwmFromPwmFile(file)
}

pwm1 = motifs[[motif_names[[1]]]]
pwm2 = motifs[[motif_names[[2]]]]

diffLogoFromPwm(pwm1 = pwm1, pwm2 = pwm2, stackHeight = lossOfAbsICDifferences)

```

multipleLocalPwmsAlignment

Multiple PWMs alignment

Description

Creates a multiple alignment of pwms

Usage

```

multipleLocalPwmsAlignment(pwms, divergence = shannonDivergence,
  unaligned_penalty = divergencePenaltyForUnaligned,
  try_reverse_complement = TRUE, base_distribution = NULL,
  length_normalization = FALSE)

```

Arguments

| | |
|------------------------|---|
| pwms | list of pwms |
| divergence | Divergence measure. |
| unaligned_penalty | is a function for localPwmAlignment. |
| try_reverse_complement | if True, alignment will try reverse complement pwms |

base_distribution

is a vector of length `nrow(pwm)` that is added to unaligned columns of pwms for comparing. If `NULL`, uniform distribution is used

length_normalization

If true, will minimize the average divergence between PWMs. Otherwise will minimize the sum of divergences between positions. In both cases unaligned positions are compared to `base_distribution` and are counted when computing the alignment length.

Value

list

Author(s)

Lando Andrey

Examples

```
file1 = system.file("extdata/homer/Max.motif", package = "DiffLogo")
file2 = system.file("extdata/homer/c-Myc.motif", package = "DiffLogo")
pwm1 = getPwmFromFile(file1)
pwm2 = getPwmFromFile(file2)
```

```
multiple_pwms_alignment = multipleLocalPwmsAlignment(list(pwm1, pwm2))
```

normalizedDifferenceOfProbabilities

normalized probability differences

Description

probability differences normalized by the sum of absolute probability differences for the given pair of probability vectors

Usage

```
normalizedDifferenceOfProbabilities(p1, p2)
```

Arguments

p1 probability vector representing the first symbol distribution
p2 probability vector representing the second symbol distribution

Value

a vector with one result for each symbol

Author(s)

Martin Nettling

Examples

```
motif_folder= "extdata/pwm"
motif_names = c("HepG2","MCF7","HUVEC","ProgFib")
motifs = list()
for (name in motif_names) {
  fileName = paste(motif_folder,"/",name,".pwm",sep="")
  file = system.file(fileName, package = "DiffLogo")
  motifs[[name]] = getPwmFromPwmFile(file)
}

pwm1 = motifs[[motif_names[[1]]]]
pwm2 = motifs[[motif_names[[2]]]]

diffLogoFromPwm(pwm1 = pwm1, pwm2 = pwm2, baseDistribution = normalizedDifferenceOfProbabilities)
```

normalizePWM

normalizes the given pwm

Description

normalizes the given pwm to column-sums of 1.0

Usage

```
normalizePWM(pwm)
```

Arguments

pwm a pwm

Value

a normalized pwm

Examples

```
pwm = matrix(1:40, nrow = 4, dimnames = list(c("A","C","G","T"), 1:10))
pwm = normalizePWM(pwm)
```

prepareDiffLogoTable *Prepare a table of difflogo objects*

Description

Prepares a DiffLogoTable and generates an object that contains the hierarchical clustering and a matrix of prepared difference logos.

Usage

```
prepareDiffLogoTable(PWMs, alphabet = DNA, configuration = list())
```

Arguments

PWMs a list/vector of position weight matrices (PWMs) each of type pwm, data.frame, or matrix

alphabet the alphabet of the given PWMs

configuration list of (probably part of) of configuration options. See diffLogoTableConfiguration.

Value

matrix of difference logos

Author(s)

Martin Nettling

Examples

```
motif_folder= "extdata/pwm"
motif_names = c("HepG2", "MCF7", "HUVEC", "ProgFib")
motifs = list()
for (name in motif_names) {
  fileName = paste(motif_folder, "/", name, ".pwm", sep="")
  file = system.file(fileName, package = "DiffLogo")
  motifs[[name]] = getPwmFromPwmFile(file)
}
sampleSizes <- c(100, 150, 200, 250)

diffLogoTableObj = prepareDiffLogoTable(motifs);
```

probabilities *probabilities*

Description

the given probabilities

Usage

probabilities(p)

Arguments

p probability vector representing the symbol distribution

Value

the given vector

Author(s)

Martin Nettling

Examples

```
motif_folder= "extdata/pwm"
motif_name = "HepG2"
fileName = paste(motif_folder,"/",motif_name,".pwm",sep="")
file = system.file(fileName, package = "DiffLogo")
motif = getPwmFromPwmFile(file)
seqLogo(pwm = motif, baseDistribution = probabilities)
```

pwmDivergence *PWM divergence*

Description

Counts PWM divergence as sum of divergencies of their columns.

Usage

pwmDivergence(pwm_left, pwm_right, divergence = shannonDivergence)

Arguments

| | |
|------------|--|
| pwm_left | is a PWM representation in type of matrix |
| pwm_right | is a PWM representation in type of matrix. The result is symmetric on pwm_left and pwm_right |
| divergence | is a Divergence function on columns. |

Value

float - sum of divergences

pwmsDistanceMatrix *Multiple PWMs alignment*

Description

Creates a distance matrix for pwms

Usage

```
pwmsDistanceMatrix(pwms, diagonal_value = 0,
  bottom_default_value = NULL, divergence = shannonDivergence,
  unaligned_penalty = divergencePenaltyForUnaligned,
  try_reverse_complement = TRUE, base_distribution = NULL,
  length_normalization = FALSE)
```

Arguments

| | |
|------------------------|---|
| pwms | list of pwms |
| diagonal_value | value to put on diagonal. |
| bottom_default_value | value to put on bottom triangle. Set to NULL to get symmetric distance matrix. |
| divergence | divergence measure. |
| unaligned_penalty | is a function for localPwmAlignment. |
| try_reverse_complement | if True, alignment will try reverse complement pwms |
| base_distribution | is a vector of length nrow(pwm) that is added to unaligned columns of pwms for comparing. If NULL, uniform distribution is used |
| length_normalization | is a vector of length nrow(pwm) that is added to unaligned columns of pwms for comparing. If NULL, uniform distribution is used |

Value

list

Author(s)

Lando Andrey

reverseAlignmentVector
Reverse for alignment vector

Description

Returns alignment vector as if all pwm were reverted.

Usage

```
reverseAlignmentVector(alignment_vector, pwms)
```

Arguments

alignment_vector list of list which \$shift and \$orientation
pwms list of matrixes.

Value

list - reversed alignment vector

Author(s)

Lando Andrey

RNA *RNA alphabet*

Description

the RNA alphabet, i.e. A, C, G, U

Usage

```
RNA
```

Format

An object of class Alphabet of length 4.

Author(s)

Martin Nettling

Examples

RNA

seqLogo

Draw sequence logo

Description

Draws the classic sequence logo.

Usage

```
seqLogo(pwm, sparse = FALSE, drawLines = 0.5,
        stackHeight = informationContent, baseDistribution = probabilities,
        alphabet = DNA, main = NULL)
```

Arguments

| | |
|------------------|---|
| pwm | representation of a position weight matrix (PWM) of type pwm, data.frame, or matrix |
| sparse | if TRUE margins are reduced and tickmarks are removed from the logo |
| drawLines | distance between background lines |
| stackHeight | function for the height of a stack at position i |
| baseDistribution | function for the heights of the individual bases |
| alphabet | of type Alphabet |
| main | the main title for the plot |

Value

none (draws sequence logo)

Author(s)

Martin Nettling

Examples

```
motif_folder= "extdata/pwm"
motif_name = "HepG2"
fileName = paste(motif_folder,"/",motif_name,".pwm",sep="")
file = system.file(fileName, package = "DiffLogo")
motif = getPwmFromPwmFile(file)
seqLogo(pwm = motif)
```

| | |
|-------------------|---------------------------|
| shannonDivergence | <i>shannon divergence</i> |
|-------------------|---------------------------|

Description

the shannon divergence for the given pair of probability vectors

Usage

```
shannonDivergence(p1, p2)
```

Arguments

| | |
|----|--|
| p1 | probability vector representing the first symbol distribution |
| p2 | probability vector representing the second symbol distribution |

Value

an object consisting of height and ylab

Author(s)

Martin Nettling

Examples

```
motif_folder= "extdata/pwm"
motif_names = c("HepG2", "MCF7", "HUVEC", "ProgFib")
motifs = list()
for (name in motif_names) {
  fileName = paste(motif_folder, "/", name, ".pwm", sep="")
  file = system.file(fileName, package = "DiffLogo")
  motifs[[name]] = getPwmFromPwmFile(file)
}

pwm1 = motifs[[motif_names[[1]]]]
pwm2 = motifs[[motif_names[[2]]]]

diffLogoFromPwm(pwm1 = pwm1, pwm2 = pwm2, stackHeight = shannonDivergence)
```

sumOfAbsICDifferences *sum of absolute information content differences*

Description

the sum of absolute information content differences for the given pair of probability vectors

Usage

```
sumOfAbsICDifferences(p1, p2)
```

Arguments

p1 probability vector representing the first symbol distribution
p2 probability vector representing the second symbol distribution

Value

an object consisting of height and ylab

Author(s)

Martin Nettling

Examples

```
motif_folder= "extdata/pwm"
motif_names = c("HepG2", "MCF7", "HUVEC", "ProgFib")
motifs = list()
for (name in motif_names) {
  fileName = paste(motif_folder, "/", name, ".pwm", sep="")
  file = system.file(fileName, package = "DiffLogo")
  motifs[[name]] = getPwmFromPwmFile(file)
}

pwm1 = motifs[[motif_names[[1]]]]
pwm2 = motifs[[motif_names[[2]]]]

diffLogoFromPwm(pwm1 = pwm1, pwm2 = pwm2, stackHeight = sumOfAbsICDifferences)
```

sumOfAbsProbabilityDifferences
sum of absolute probability differences

Description

the sum of absolute probability differences for the given pair of probability vectors

Usage

```
sumOfAbsProbabilityDifferences(p1, p2)
```

Arguments

p1 probability vector representing the first symbol distribution
p2 probability vector representing the second symbol distribution

Value

an object consisting of height and ylab

Author(s)

Martin Nettling

Examples

```
motif_folder= "extdata/pwm"
motif_names = c("HepG2","MCF7","HUVEC","ProgFib")
motifs = list()
for (name in motif_names) {
  fileName = paste(motif_folder,"/",name,".pwm",sep="")
  file = system.file(fileName, package = "DiffLogo")
  motifs[[name]] = getPwmFromPwmFile(file)
}

pwm1 = motifs[[motif_names[[1]]]]
pwm2 = motifs[[motif_names[[2]]]]

diffLogoFromPwm(pwm1 = pwm1, pwm2 = pwm2, stackHeight = sumOfAbsProbabilityDifferences)
```

| | |
|------------------|---------------------------------------|
| sumProbabilities | <i>sum of probabilities, i.e. 1.0</i> |
|------------------|---------------------------------------|

Description

the sum of probabilities for the given probability vector, i.e. 1.0

Usage

```
sumProbabilities(p)
```

Arguments

p probability vector representing the symbol distribution

Value

an object consisting of height and ylab

Author(s)

Martin Nettling

Examples

```
motif_folder= "extdata/pwm"  
motif_name = "HepG2"  
fileName = paste(motif_folder, "/", motif_name, ".pwm", sep="")  
file = system.file(fileName, package = "DiffLogo")  
motif = getPwmFromPwmFile(file)  
seqLogo(pwm = motif, stackHeight = sumProbabilities)
```

| | |
|-----------------|---|
| switchDirection | <i>Switches between 'forward' and 'reverse'</i> |
|-----------------|---|

Description

Switches between 'forward' and 'reverse'

Usage

```
switchDirection(direction)
```

Arguments

direction either 'forward' or 'reverse'

Value

either 'reverse' or 'forward'

twoSetsAveragePwmDivergenceFromAlignmentVector

Average divergence between two sets.

Description

Computes average pwm divergence from alignment vector for two datasets. This equals to average divergence between all pairs where one pwm comes from left set, and other comes from right

Usage

```
twoSetsAveragePwmDivergenceFromAlignmentVector(left_pwms_list,  
left_pwms_alignment, right_pwms_list, right_pwms_alignment,  
divergence = shannonDivergence)
```

Arguments

left_pwms_list is a list of matrixes

left_pwms_alignment

is a list of shifts (\$shift) and orientations (\$direction)

right_pwms_list

is a list of matrixes

right_pwms_alignment

is a list of shifts (\$shift) and orientations (\$direction)

divergence divergence measure.

Value

float

Author(s)

Lando Andrey

Index

* datasets

- ASN, 4
- DNA, 13
- FULL_ALPHABET, 18
- RNA, 33

alignPwmSets, 3

Alphabet, 4

ASN, 4

baseDistributionPwm, 5

calculatePvalue, 5

createDiffLogoObject, 6

differenceOfICs, 8

diffLogo, 9

diffLogoFromPwm, 10

diffLogoTable, 11

diffLogoTableConfiguration, 12

DNA, 13

drawDiffLogoTable, 14

enrichDiffLogoObjectWithPvalues, 15

enrichDiffLogoTableWithPvalues, 16

extendPwmsFromAlignmentVector, 17

FULL_ALPHABET, 18

getAlphabetFromCharacters, 18

getAlphabetFromSequences, 19

getPwmFromAlignment, 19

getPwmFromAlignmentFile, 20

getPwmFromFastaFile, 21

getPwmFromFile, 21

getPwmFromHomerFile, 22

getPwmFromPfmOrJasparFile, 22

getPwmFromPwmFile, 23

getSequencesFromAlignmentFile, 23

getSequencesFromFastaFile, 24

informationContent, 25

localPwmAlignment, 25

lossOfAbsICDifferences, 26

multipleLocalPwmsAlignment, 27

normalizedDifferenceOfProbabilities,
28

normalizePWM, 29

prepareDiffLogoTable, 30

probabilities, 31

pwmDivergence, 31

pwmsDistanceMatrix, 32

reverseAlignmentVector, 33

RNA, 33

seqLogo, 34

shannonDivergence, 35

sumOfAbsICDifferences, 36

sumOfAbsProbabilityDifferences, 37

sumProbabilities, 38

switchDirection, 38

twoSetsAveragePwmDivergenceFromAlignmentVector,
39