

Package ‘hicVennDiagram’

May 16, 2024

Title Venn Diagram for genomic interaction data

Version 1.2.0

Description A package to generate high-resolution Venn and Upset plots for genomic interaction data from HiC, ChIA-PET, HiChIP, PLAC-Seq, Hi-TrAC, HiCAR and etc. The package generates plots specifically crafted to eliminate the deceptive visual representation caused by the counts method.

License GPL-3

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.1

VignetteBuilder knitr

biocViews DNA3DStructure, HiC, Visualization

Depends R (>= 4.3.0)

Imports GenomeInfoDb, GenomicRanges, IRanges, InteractionSet, rtracklayer, ggplot2, ComplexUpset, reshape2, eulerr, S4Vectors, methods, utils, htmlwidgets, svglite

Suggests BiocStyle, knitr, rmarkdown, testthat, ChIPpeakAnno, grid, TxDb.Hsapiens.UCSC.hg38.knownGene

URL <https://github.com/jianhong/hicVennDiagram>

BugReports <https://github.com/jianhong/hicVennDiagram/issues>

git_url <https://git.bioconductor.org/packages/hicVennDiagram>

git_branch RELEASE_3_19

git_last_commit cf5f1bc

git_last_commit_date 2024-04-30

Repository Bioconductor 3.19

Date/Publication 2024-05-16

Author Jianhong Ou [aut, cre] (<<https://orcid.org/0000-0002-8652-2488>>)

Maintainer Jianhong Ou <jianhong.ou@duke.edu>

Contents

browseVenn	2
browseVenn-shiny	3
createGIbackground	3
gleamTest	4
upsetPlot	4
vennCount	6
vennPlot	6
vennTable-class	7
Index	9

browseVenn	<i>Browse the venn plot</i>
------------	-----------------------------

Description

Brow the venn plot in a web browser to adjust the plot and export the result.

Usage

```
browseVenn(plot, width = NULL, height = NULL)
```

Arguments

- plot plots of [vennPlot](#) or [upsetPlot](#)
- width width of the figure
- height height of the figure

Value

An object of class `htmlwidget` that will intelligently print itself into HTML in a variety of contexts including the R console, within R Markdown documents, and within Shiny output bindings.

Examples

```
pd <- system.file("extdata", package = "hicVennDiagram", mustWork = TRUE)
fs <- dir(pd, pattern = ".bedpe", full.names = TRUE)
vc <- vennCount(fs)
p <- vennPlot(vc)
browseVenn(p)
```

browseVenn-shiny	<i>Shiny bindings for browseVenn</i>
------------------	--------------------------------------

Description

Output and render functions for using browseVenn within Shiny applications and interactive Rmd documents.

Usage

```
browseVennOutput(outputId, width = "100%", height = "400px")
```

```
renderbrowseVenn(expr, env = parent.frame(), quoted = FALSE)
```

Arguments

outputId	output variable to read from
width, height	Must be a valid CSS unit (like '100%', '400px', 'auto') or a number, which will be coerced to a string and have 'px' appended.
expr	An expression that generates a browseVenn
env	The environment in which to evaluate expr.
quoted	Is expr a quoted expression (with quote())? This is useful if you want to save an expression in a variable.

createGIbackground	<i>Create background by input GInteractions</i>
--------------------	---

Description

Create background based on the distance distribution of input GInteractions.

Usage

```
createGIbackground(gi, size = 2 * lengths(gi))
```

Arguments

gi	A vector of bedpe files or a list of genomic interaction data (Pairs or GInteractions).
size	The maximal size of the background

Examples

```
pd <- system.file("extdata", package = "hicVennDiagram", mustWork = TRUE)
fs <- dir(pd, pattern = ".bedpe", full.names = TRUE)[1]
set.seed(123)
# createGIbackground(fs)
```

gleamTest	<i>Perform GLEAM test</i>
-----------	---------------------------

Description

Run Genomic Loops Enrichment Analysis Method test

Usage

```
gleamTest(query, subject, background, method = c("binom", "hyper"), ...)
```

Arguments

query, subject	A vector of bedpe files or a list of genomic interaction data (Pairs or GInteractions) or a list of GRanges object. 'subject' is optional if length of query > 1.
background	The test will restricted within the region. The background is the background of subject if subject is available. Otherwise, the background is the the background of second element of comparison group.
method	Distribution type for p-value.
...	parameters used by findOverlaps .

Examples

```
# example code
pd <- system.file("extdata", package = "hicVennDiagram", mustWork = TRUE)
fs <- dir(pd, pattern = ".bedpe", full.names = TRUE)
library(TxDb.Hsapiens.UCSC.hg38.knownGene)
## set.seed(123)
## background <- createGIbackground(fs)
## gleamTest(fs, background = background)
## gleamTest(fs, background = background, method = 'hyper')
grl <- GRangesList(exons=reduce(exons(TxDb.Hsapiens.UCSC.hg38.knownGene)),
  genes=reduce(genes(TxDb.Hsapiens.UCSC.hg38.knownGene)))
gleamTest(fs[seq_along(grl)], grl, background = grl[['exons']])
gleamTest(grl[c(2, 1)], grl, background = grl[['exons']])
gleamTest(grl, background = grl[['genes']])
```

upsetPlot	<i>UpSet plot for the Venn count table</i>
-----------	--

Description

Plot the overlaps counts by ComplexUpset.

Usage

```
upsetPlot(
  vennTable,
  label_all = list(na.rm = TRUE, color = "gray30", alpha = 0.7, label.padding = unit(0.1,
    "lines")),
  coln_prefix = NULL,
  ...
)
```

Arguments

vennTable	An vennTable object, the first element in the output of vennCount .
label_all	A list of parameters used by geom_label for text labels of counts for each group. If it set to FALSE or length of the list is zero, the labels will be ignored.
coln_prefix	The prefix to be removed for colnumn names of vennTable.
...	Parameters could be passed to upset except data and intersect.

Value

A ggplot object.

Examples

```
pd <- system.file("extdata", package = "hicVennDiagram", mustWork = TRUE)
fs <- dir(pd, pattern = ".bedpe", full.names = TRUE)
vc <- vennCount(fs)
upset_themes_fix <- lapply(ComplexUpset::upset_themes, function(.ele){
  .ele[names(.ele) %in% names(formals(ggplot2::theme))]
})
upsetPlot(vc, theme = upset_themes_fix)
## change the font size of lables and numbers
themes <- ComplexUpset::upset_modify_themes(
  ## get help by vignette('Examples_R', package = 'ComplexUpset')
  list('intersections_matrix'=
    ggplot2::theme(axis.text.y=ggplot2::element_text(size=24)))
)
themes <- lapply(themes, function(.ele){
  .ele[names(.ele) %in% names(formals(ggplot2::theme))]
})
upsetPlot(vc, label_all=list(
  na.rm = TRUE,
  color = 'gray30',
  alpha = .7,
  label.padding = grid::unit(0.1, "lines"),
  size = 5
), themes = themes)
```

vennCount	<i>Construct intersections of sets</i>
-----------	--

Description

Given a collection of bedpe files or a list of genomic interaction data, `vennCount` will compute all possible combinations of interactions and return an object of class `vennTable`, storing the combinations as well as the number of elements in each intersection.

Usage

```
vennCount(gi, FUN = min, ...)
```

Arguments

<code>gi</code>	A vector of bedpe files or a list of genomic interaction data (Pairs or GInteractions)
<code>FUN</code>	Function to summarize the overlapping number.
<code>...</code>	parameters used by findOverlaps

Value

An object of `vennTable`

Examples

```
pd <- system.file("extdata", package = "hicVennDiagram", mustWork = TRUE)
fs <- dir(pd, pattern = ".bedpe", full.names = TRUE)
vc <- vennCount(fs)
```

vennPlot	<i>Venn diagram for the Venn count table</i>
----------	--

Description

Plot the overlaps counts by eulerr.

Usage

```
vennPlot(vennTable, shape = "circle", ...)
```

Arguments

vennTable	An vennTable object, the first element in the output of vennCount .
shape	Geometric shape used in the diagram used by euler .
...	parameters to update fills and edges with and thereby a shortcut to set these parameters plot.euler .

Value

A grid object.

Examples

```
pd <- system.file("extdata", package = "hicVennDiagram", mustWork = TRUE)
fs <- dir(pd, pattern = ".bedpe", full.names = TRUE)
vc <- vennCount(fs)
vennPlot(vc)
## change the font size of venn plot lables and numbers,
## both cex or fontsize should work
vennPlot(vc, quantities=list(fontsize=24), labels=list(cex=1.5))
```

vennTable-class	<i>Class "vennTable"</i>
-----------------	--------------------------

Description

An object of class "vennTable" represents Venn counts.

Usage

```
vennTable(...)

## S4 method for signature 'vennTable'
x$name

## S4 replacement method for signature 'vennTable'
x$name <- value

## S4 method for signature 'vennTable,ANY,ANY'
x[[i]]

## S4 replacement method for signature 'vennTable,ANY,ANY'
x[[i]] <- value

## S4 method for signature 'vennTable'
show(object)
```

Arguments

<code>...</code>	Each argument in <code>...</code> becomes an slot in the new <code>vennTable</code> .
<code>x</code>	an object of <code>vennTable</code>
<code>name</code>	slot name of <code>vennTable</code>
<code>value</code>	values to assign
<code>i</code>	slot name of <code>vennTable</code>
<code>object</code>	an object of <code>vennTable</code> .

Value

An object of `vennTable`.

Slots

`combinations` A logical "matrix", specify the combinations.
`counts` A "numeric" vector, the overall counts number for each combination.
`vennCounts` A "matrix" object, specify the counts number for each sample in the combination.
`overlapList` "list", overlapping list of the genomic interactions.

Examples

```
vt <- vennTable()
```


Index

`[[`, vennTable, ANY, ANY-method
 (vennTable-class), [7](#)
`[[<-`, vennTable, ANY, ANY-method
 (vennTable-class), [7](#)
`$`, vennTable-method (vennTable-class), [7](#)
`$<-`, vennTable-method (vennTable-class),
 [7](#)
`'[[<-'`, vennTable-method
 (vennTable-class), [7](#)
`'[['`, vennTable-method
 (vennTable-class), [7](#)

`browseVenn`, [2](#)
`browseVenn-shiny`, [3](#)
`browseVennOutput` (browseVenn-shiny), [3](#)

`createGIbackground`, [3](#)

`euler`, [7](#)

`findOverlaps`, [4](#), [6](#)

`geom_label`, [5](#)
`GInteractions`, [3](#), [4](#), [6](#)
`gleamTest`, [4](#)

`Pairs`, [3](#), [4](#), [6](#)
`plot.euler`, [7](#)

`renderbrowseVenn` (browseVenn-shiny), [3](#)

`show`, vennTable-method
 (vennTable-class), [7](#)

`upset`, [5](#)
`upsetPlot`, [2](#), [4](#)

`vennCount`, [5](#), [6](#), [7](#)
`vennPlot`, [2](#), [6](#)
`vennTable`, [6](#)
`vennTable` (vennTable-class), [7](#)
`vennTable-class`, [7](#)