

Package ‘iSEEhex’

March 24, 2023

Title iSEE extension for summarising data points in hexagonal bins

Version 1.0.0

Date 2022-06-16

Description This package provides panels summarising data points in hexagonal bins for `iSEE`. It is part of `iSEEu`, the iSEE universe of panels that extend the `iSEE` package.

License Artistic-2.0

URL <https://github.com/iSEE/iSEEhex>

BugReports <https://support.bioconductor.org/t/iSEEhex>

biocViews Software, Infrastructure

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.2.0

Depends SummarizedExperiment, iSEE

Imports ggplot2, hexbin, methods, shiny

Suggests BiocStyle, covr, knitr, RefManageR, rmarkdown, sessioninfo, testthat (>= 3.0.0), scRNAseq, scater

Config/testthat/edition 3

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/iSEEhex>

git_branch RELEASE_3_16

git_last_commit 1e2f7ce

git_last_commit_date 2022-11-01

Date/Publication 2023-03-24

Author Kevin Rue-Albrecht [aut, cre] (<<https://orcid.org/0000-0003-3899-3872>>),
Charlotte Soneson [aut] (<<https://orcid.org/0000-0003-3833-2169>>),
Federico Marini [aut] (<<https://orcid.org/0000-0003-3252-7758>>),
Aaron Lun [aut] (<<https://orcid.org/0000-0002-3564-4813>>)

Maintainer Kevin Rue-Albrecht <kevinrue67@gmail.com>

R topics documented:

ReducedDimensionHexPlot-class	2
Index	4

ReducedDimensionHexPlot-class

The ReducedDimensionHexPlot class

Description

The ReducedDimensionHexPlot is a [ReducedDimensionPlot](#) subclass that is dedicated to creating a reduced dimension plot summarising data points in hexagonal bins.

Slot overview

The following slots control the parameters used in the visualization:

- `BinResolution`, a numeric positive scalar specifying the number of hexagonal bins in both vertical and horizontal directions. Defaults to 100.

In addition, this class inherits all slots from its parent [ReducedDimensionPlot](#), [ColumnDotPlot](#), [DotPlot](#) and [Panel](#) classes.

Constructor

`ReducedDimensionHexPlot(...)` creates an instance of a `ReducedDimensionHexPlot` class, where any slot and its value can be passed to `...` as a named argument.

Supported methods

In the following code snippets, `x` is an instance of a `ReducedDimensionHexPlot` class. Refer to the documentation for each method for more details on the remaining arguments.

For defining the interface:

- `.panelColor(x)` will return the specified default color for this panel class.
- `.fullName(x)` will return "Hexagonal reduced dimension plot".
- `.hideInterface(x, field)` will return TRUE for `field="Downsample"` as downsampling is not applicable to this panel that summarizes all data points in each hexagonal bin; otherwise this function will call the [ReducedDimensionPlot](#) method.
- `.defineVisualShapeInterface(x)` will return NULL for this panel, as the shape aesthetic is not applicable to this panel that does not display individual data points.
- `.defineVisualSizeInterface(x)` overrides the equivalent method inherited from all parents classes and will return instead an HTML tag definition that contains a user input controlling the number of hexagonal bins in both vertical and horizontal directions.
- `.defineVisualOtherInterface(x)` will return NULL, as there are no additional visual parameters for this panel.

- `.allowableColorByDataChoices(x, se)` will return a character vector with the names of all continuous fields in `colData(se)`, where `se` is the input `SummarizedExperiment` object.

For monitoring reactive expressions:

- `.createObservers(x, se, input, session, pObjects, rObjects)` sets up observers for all new slots described above, as well as in the parent classes via the `ReducedDimensionPlot` method.

For creating the plot:

- `.generateDotPlot(x, envir)` will return a list with `plot`, a `ggplot2::ggplot()` object; and `commands`, a character vector of commands to produce that object when evaluated inside `envir`.

For documentation:

- `.definePanelTour(x)` returns an `data.frame` containing the steps of a panel-specific tour.
- `.getDotPlotColorHelp(x, color_choices)` returns a function that generates an `rintrojs` tour for the color choice UI.

Author(s)

Kevin Rue-Albrecht

See Also

[ReducedDimensionPlot](#), for the base class.

Examples

```
library(scRNAseq)

# Example data ----
sce <- ReprocessedAllenData(assays="tophat_counts")
class(sce)

library(scater)
sce <- logNormCounts(sce, exprs_values="tophat_counts")

sce <- runPCA(sce, ncomponents=4)
sce <- runTSNE(sce)
rowData(sce)$ave_count <- rowMeans(assay(sce, "tophat_counts"))
rowData(sce)$n_cells <- rowSums(assay(sce, "tophat_counts") > 0)

# launch the app itself ----

if (interactive()) {
  iSEE(sce, initial=list(
    ReducedDimensionHexPlot(BinResolution=50),
    ReducedDimensionPlot()
  ))
}
```

Index

.allowableColorByDataChoices, 3
.allowableColorByDataChoices, ReducedDimensionHexPlot-method
(ReducedDimensionHexPlot-class), 2
.createObservers, 3
.createObservers, ReducedDimensionHexPlot-method
(ReducedDimensionHexPlot-class), 2
.definePanelTour, 3
.definePanelTour, ReducedDimensionHexPlot-method
(ReducedDimensionHexPlot-class), 2
.defineVisualOtherInterface, 2
.defineVisualOtherInterface, ReducedDimensionHexPlot-method
(ReducedDimensionHexPlot-class), 2
.defineVisualShapeInterface, 2
.defineVisualShapeInterface, ReducedDimensionHexPlot-method
(ReducedDimensionHexPlot-class), 2
.defineVisualSizeInterface, 2
.defineVisualSizeInterface, ReducedDimensionHexPlot-method
(ReducedDimensionHexPlot-class), 2
.fullName, 2
.fullName, ReducedDimensionHexPlot-method
(ReducedDimensionHexPlot-class), 2
.generateDotPlot, 3
.generateDotPlot, ReducedDimensionHexPlot-method
(ReducedDimensionHexPlot-class), 2
.getDotPlotColorHelp, 3
.getDotPlotColorHelp, ReducedDimensionHexPlot-method
(ReducedDimensionHexPlot-class), 2
.hideInterface, 2
.hideInterface, ReducedDimensionHexPlot-method
(ReducedDimensionHexPlot-class), 2
HexPlot, 2
initialize, ReducedDimensionHexPlot-method
(ReducedDimensionHexPlot-class), 2
Panel, 2
ReducedDimensionHexPlot, 2
ReducedDimensionHexPlot
(ReducedDimensionHexPlot-class), 2
ReducedDimensionHexPlot-class, 2
ReducedDimensionPlot, 2, 3
SummarizedExperiment, 3
colData(se), 3
ColumnDotPlot, 2
DotPlot, 2
ggplot2::ggplot(), 3
panelColor, ReducedDimensionHexPlot-method
(ReducedDimensionHexPlot-class), 2