

Package ‘faers’

May 6, 2024

Title R interface for FDA Adverse Event Reporting System

Version 1.1.0

BugReports <https://github.com/Yunuuuu/faers>

Description

The FDA Adverse Event Reporting System (FAERS) is a database used for the spontaneous reporting of adverse events and medication errors related to human drugs and therapeutic biological products. faers package serves as the interface between the FAERS database and R. Furthermore, faers package offers a standardized approach for performing pharmacovigilance analysis.

License MIT + file LICENSE

Depends R (>= 4.4.0)

Imports BiocParallel, brio, cli, curl (>= 5.0.0), data.table, httr2 (>= 1.0.0), MCMCpack, methods, openEBGM, rlang (>= 1.1.0), rvest, tools, utils, vroom, xml2

Suggests BiocStyle, countrycode, knitr, rmarkdown, testthat (>= 3.0.0)

biocViews Software, DataImport, BiomedicalInformatics, Pharmacogenomics, Pharmacogenomics

Encoding UTF-8

ByteCompile true

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.0

Config/testthat/edition 3

Config/testthat/parallel true

VignetteBuilder knitr

Collate 'athena.R' 'available.R' 'meddra.R' 'class-FAERS.R' 'combine.R' 'counts.R' 'dedup.R' 'download.R' 'faers-package.R' 'faers.R' 'fda_drugs.R' 'import-standalone-assert.R' 'import-standalone-cli.R' 'import-standalone-obj-type.R' 'load.R' 'merge.R' 'meta.R' 'methods-FAERS.R' 'parse.R' 'period.R' 'phv_.R' 'phv_ebgm.R' 'rxnorm.R' 'sample.R' 'signal.R' 'standardize.R' 'unify.R' 'utils-file.R' 'utils-str.R' 'utils.R'

git_url `https://git.bioconductor.org/packages/faers`
git_branch `devel`
git_last_commit `a621c54`
git_last_commit_date `2024-04-30`
Repository `Bioconductor 3.20`
Date/Publication `2024-05-06`
Author Yun Peng [aut, cre] (<<https://orcid.org/0000-0003-2801-3332>>),
YuXuan Song [aut],
Caipeng Qin [aut],
JiaXing Lin [aut]
Maintainer Yun Peng <yunyunp96@163.com>

Contents

faers-package	3
athena	3
faers	4
FAERS-class	5
faers_available	7
faers_before_period	8
faers_clearcache	8
faers_combine	9
faers_counts	10
faers_dedup	11
faers_download	12
faers_get	13
faers_load	15
faers_merge	16
faers_meta	18
faers_parse	18
faers_phv_signal	20
faers_standardize	21
fda_drugs	22
MedDRA-class	23
phv_signal	24
Index	29

faers-package	<i>faers: R interface for FDA Adverse Event Reporting System</i>
---------------	--

Description

The FDA Adverse Event Reporting System (FAERS) is a database used for the spontaneous reporting of adverse events and medication errors related to human drugs and therapeutic biological products. faers pacakge serves as the interface between the FAERS database and R. Furthermore, faers pacakge offers a standardized approach for performing pharmacovigilance analysis.

Author(s)

Maintainer: Yun Peng <yunyunp96@gmail.com> ([ORCID](#))

Authors:

- YuXuan Song <yuxuan_song2021@163.com>
- Jiaxing Song <1570851599@qq.com>
- Caipeng Qin <qincaipeng@pkuph.edu.cn>

See Also

Useful links:

- Report bugs at <https://github.com/Yunuuuu/faers>

athena	<i>Read and Parse ATHENA VOCABULARIES data</i>
--------	--

Description

Read and Parse ATHENA VOCABULARIES data

Usage

```
athena(use = NULL, list = FALSE, force = FALSE, url = NULL)
```

Arguments

use	An atomic character specifying the files to use with values in "concept", "domain", "concept_class", "concept_relationship", "concept_ancestor", "concept_synonym", "drug_strength", "relationship", and "vocabulary".
list	A boolean value, should it only list files in the ATHENA VOCABULARIES data?
force	A boolean value. If set to TRUE, it indicates the retrieval of VOCABULARIES data in the url directly, bypassing the cache.
url	A string of url for ATHENA VOCABULARIES data. You must provide it to cache the file when you firstly run this function.

Value

- if `list = TRUE`, an atomic character.
- if `list = FALSE`, a [data.table](#) if use is a string or otherwise a list of [data.table](#).

faers

*Download and parse FAERS Quarterly Data files***Description**

Download and parse FAERS Quarterly Data files

Usage

```
faers(
  years,
  quarters,
  format = NULL,
  dir = getwd(),
  compress_dir = dir,
  handle_opts = list()
)
```

Arguments

<code>years</code>	An atomic integer indicates years for which data are required.
<code>quarters</code>	An atomic character, only "q1", "q2", "q3", and "q4" are allowed.
<code>format</code>	File format to used, only "ascii" and "xml" are availabe. Default: "ascii".
<code>dir</code>	The destination directory for any downloads. Defaults to current working dir.
<code>compress_dir</code>	A string specifies the directory to extract files to. It will be created if necessary.
<code>handle_opts</code>	Extra handle options passed to each request new_handle .

Value

A [FAERSxml](#) or [FAERSascii](#) object.

Examples

```
# you must change `dir`, as the file included in the package is sampled
data <- faers(2004, "q1",
  dir = system.file("extdata", package = "faers"),
  compress_dir = tempdir()
)
```

FAERS-class*FAERS class*

Description

Provide a container for FAERS Quarterly Data file

Usage

```
## S4 method for signature 'FAERS'
show(object)

## S4 method for signature 'FAERSascii'
show(object)

faers_data(object, ...)

## S4 method for signature 'FAERS'
faers_data(object)

faers_year(object)

## S4 method for signature 'FAERS'
faers_year(object)

faers_quarter(object)

## S4 method for signature 'FAERS'
faers_quarter(object)

faers_period(object)

## S4 method for signature 'FAERS'
faers_period(object)

faers_meddra(object, ...)

## S4 method for signature 'FAERS'
faers_meddra(object, use = NULL)

faers_deleted_cases(object, ...)

## S4 method for signature 'FAERSascii'
faers_deleted_cases(object)

faers_header(object)
```

```
## S4 method for signature 'FAERSxml'
faers_header(object)
```

Arguments

object	A FAERS object.
...	Other arguments passed to specific methods.
use	A string, what meddra data to use, "hierarchy" or "smq". If NULL, a MedDRA will be returned. Only used when object has been standardized

Details

- faers_data: Extract the data slot.
- faers_year: Extract the year slot.
- faers_quarter: Extract the quarter slot.
- faers_period: A [data.table](#) combine the year and quarter slot.
- faers_meddra: Extract the meddra slot. If object have never been standardized, always return NULL.
- faers_deleted_cases: Extract the deletedCases slot.

Value

See details.

Slots

year An integer specifies the year information.

quarter A string specifies the quarter information.

data For FAERSxml, a [data.table](#). For FAERSascii, a list of [data.table](#).

meddra A [MedDRA](#) or NULL representing the meddra data used for standardization.

format A string of "ascii" or "xml" indicates the file format used.

deletedCases An atomic character, as of 2019 Quarter one there are new files that lists deleted cases. [faers_dedup](#) will remove cases in this slot.

standardization A bool, indicates whether standardization has been performed.

deduplication A bool, indicates whether deduplication has been performed.

Examples

```
# usually we use faers() function to create a `FAERS` object
# you must change `dir`, as the file included in the package is sampled
data <- faers(2004, "q1",
  dir = system.file("extdata", package = "faers"),
  compress_dir = tempdir()
)
faers_data(data)
faers_year(data)
```

```
faers_quarter(data)
faers_period(data)
faers_meddra(data)
faers_deleted_cases(data)
```

faers_available	<i>Check if FAERS year</i>
-----------------	----------------------------

Description

This function check if data for the years and quarters selected are available at FAERS to be downloaded.

Usage

```
faers_available(years, quarters, force = FALSE, internal = FALSE)
```

Arguments

years	An atomic integer indicates years for which data are required.
quarters	An atomic character, only "q1", "q2", "q3", and "q4" are allowed.
force	A boolean value. If set to TRUE, it indicates the retrieval of information about all records' metadata in the FAERS Quarterly Data Extract Files Site, bypassing the cache.
internal	A boolean value. It determines whether to use the internal data associated with the package when no cached file is available.

Value

A logical indicates FAERS can have data for the years and quarters required?

Examples

```
faers_available(c(2011, 2023), c("q1", "q2"))
```

faers_before_period	<i>Test whether years and quarters are before specified period</i>
---------------------	--

Description

Test whether years and quarters are before specified period

Usage

```
faers_before_period(years, quarters, y, q, inclusive = TRUE)
```

Arguments

years	An atomic integer indicates years to test.
quarters	An atomic character indicates quarters to test, only "q1", "q2", "q3", and "q4" are allowed.
y	An integer, specifying the period year.
q	A string, specifying the period quarter.
inclusive	A bool, whether to include the period specifid.

Value

An atomic logical with the same length of the max length of years and quarters.

Examples

```
faers_before_period(c(2011, 2012), c("q1", "q3"), 2011, "q2")
```

faers_clearcache	<i>Remove caches</i>
------------------	----------------------

Description

Remove caches

Usage

```
faers_clearcache(caches = NULL, force = FALSE)
```

Arguments

caches	An atomic character, indicates what caches to remove? Only "metadata", "fdadrugs", and "athena" can be used. If NULL, all caches will be removed.
force	logical. Should permissions be changed (if possible) to allow the file or directory to be removed?

Value

Path of the deleted directory invisibly

Examples

```
faers_clearcache()
```

faers_combine	<i>Combine FAERS objects from different Quarterly files.</i>
---------------	--

Description

Packed all FAERSascii or FAERSxml objects into a single FAERSascii or FAERSxml object. It is important to note that all data passed to these functions via the `...` argument must belong to the different **FAERS** objects, indicating that they have the different period data (as defined by [faers_period](#)).

Usage

```
faers_combine(...)
```

Arguments

`...` Multiple FAERSxml or FAERSascii objects or a list containing FAERSxml or FAERSascii objects. Objects can be standardized by [faers_standardize](#) but cannot be de-duplicated by [faers_dedup](#). If we combine deduplicated objects from different quarterly data files, duplicate reports will be introduced again.

Value

A [FAERSxml](#) or [FAERSascii](#) object.

Examples

```
# the files included in the package are sampled
data1 <- faers_parse(
  system.file("extdata", "aers_ascii_2004q1.zip", package = "faers"),
  compress_dir = tempdir()
)
data2 <- faers_parse(
  system.file("extdata", "faers_ascii_2017q2.zip", package = "faers"),
  compress_dir = tempdir()
)
faers_combine(data1, data2)
```

faers_counts

*Counting the number of unique case for each event***Description**

Counting the number of unique case for each event

Usage

```
faers_counts(.object, ...)

## S4 method for signature 'FAERSascii'
faers_counts(
  .object,
  .events = "soc_name",
  .fn = NULL,
  ...,
  .field = "reac",
  .na.rm = FALSE
)
```

Arguments

.object	A FAERSascii object.
...	Other arguments passed to specific methods, for FAERSascii method, other arguments passed to .fn().
.events	A character specify the events column(s) in the .field data to count the unique primaryid. If multiple columns were selected, the combination for all columns will define the interested events.
.fn	<p>A function or formula defined the preprocessing function before creating contingency table, with the .field data as the input and return a data.table.</p> <p>Note: When using the set* or := function from data.table with the "demo", "drug", "ther", "rpsr", and "outc" data, exercise caution as these functions directly modify the internal data. In such cases, it is advisable to use the copy function first.</p> <p>If a function, it is used as is.</p> <p>If a formula, e.g. $\sim .x + 2$, it is converted to a function with up to two arguments: .x (single argument) or .x and .y (two arguments). The . placeholder can be used instead of .x. This allows you to create very compact anonymous functions (lambdas) with up to two inputs.</p> <p>If a string, the function is looked up in globalenv().</p>
.field	A string indicates the interested FAERS fields to use. Only values "demo", "drug", "indi", "ther", "reac", "rpsr", and "outc" can be used.
.na.rm	A bool, whether NA value in .events column(s) should be removed.

Value

A [data.table](#) object.

Examples

```
# you must change `dir`, as the files included in the package are sampled
data <- faers(c(2004, 2017), c("q1", "q2"),
  dir = system.file("extdata", package = "faers"),
  compress_dir = tempdir()
)
## Not run:
# you must standardize and deduplication before disproportionality analysis
# you should replace `meddra_path` with yours
data <- faers_standardize(data, meddra_path)
data <- faers_dedup(data)
faers_counts(data)

## End(Not run)
std_data <- readRDS(system.file("extdata", "standardized_data.rds",
  package = "faers"
))
faers_counts(std_data)
```

faers_dedup

*Tidy up FAERS Quarterly Data with duplicate records removed***Description**

Tidy up FAERS Quarterly Data with duplicate records removed

Usage

```
faers_dedup(object, ...)
```

S4 method for signature 'FAERSascii'

```
faers_dedup(object, remove_deleted_cases = TRUE)
```

S4 method for signature 'FAERSxml'

```
faers_dedup(object)
```

S4 method for signature 'ANY'

```
faers_dedup(object)
```

Arguments

object A [FAERSascii](#) object.

... Other arguments passed to specific methods.

remove_deleted_cases

 If TRUE, will remove all [deletedCases](#) from the final result.

Value

A [FAERSascii](#) object.

See Also

[faers_standardize](#)

Examples

```
# you must change `dir`, as the files included in the package are sampled
data <- faers(c(2004, 2017), c("q1", "q2"),
  dir = system.file("extdata", package = "faers"),
  compress_dir = tempdir()
)
## Not run:
# we must standardize firstly
# you should replace `meddra_path` with yours
data <- faers_standardize(data, meddra_path)
faers_dedup(data)

## End(Not run)
```

faers_download

Download FAERS data

Description

This function downloads the FAERS data for selected years and quarters.

Usage

```
faers_download(years, quarters, format = NULL, dir = getwd(), ...)
```

Arguments

years	An atomic integer indicates years for which data are required.
quarters	An atomic character, only "q1", "q2", "q3", and "q4" are allowed.
format	File format to used, only "ascii" and "xml" are available. Default: "ascii".
dir	The destination directory for any downloads. Defaults to current working dir.
...	Extra handle options passed to each request new_handle .

Value

An atomic character for the path of downloaded files.

Examples

```
# you must change `dir`, as the file included in the package is sampled
# in this way, the file will downloaded from FAERS
faers_download(
  year = 2004, quarter = "q1",
  dir = system.file("extdata", package = "faers")
)
```

faers_get

*Methods for FAERS class***Description**

Utils function for [FAERSascii](#) class.

Usage

```
faers_get(object, ...)

## S4 method for signature 'FAERSascii'
faers_get(object, field)

faers_mget(object, ...)

## S4 method for signature 'FAERSascii'
faers_mget(object, fields)

faers_primaryid(object, ...)

## S4 method for signature 'FAERSascii'
faers_primaryid(object)

## S4 method for signature 'FAERSascii,ANY,ANY,ANY'
x[i]

## S4 method for signature 'FAERSascii'
x[[i]]

## S4 method for signature 'FAERSascii'
x$name

faers_keep(object, ...)

## S4 method for signature 'FAERSascii'
faers_keep(object, primaryid = NULL, invert = FALSE)

faers_filter(.object, ...)
```

```
## S4 method for signature 'FAERSascii'
faers_filter(.object, .fn, ..., .field = NULL, .invert = FALSE)

faers_modify(.object, ...)

## S4 method for signature 'FAERSascii'
faers_modify(.object, .field, .fn, ...)
```

Arguments

<code>object, .object</code>	A FAERSascii object.
<code>...</code>	Other arguments passed to specific methods. For <code>faers_filter</code> : other arguments passed to <code>.fn</code> .
<code>field</code>	A string indicates the FAERS fields to use. Only values "demo", "drug", "indi", "reac", "ther", "rpsr", and "outc" can be used.
<code>fields</code>	A character vector specifying the fields to use. Only values "demo", "drug", "indi", "ther", "reac", "rpsr", and "outc" can be used.
<code>x</code>	A FAERSascii object.
<code>i, name</code>	Indices specifying elements to extract. For <code>i</code> , it will be okay to use integer indices.
<code>primaryid</code>	An atomic character or integer specifies the reports to keep. If <code>NULL</code> , will do nothing.
<code>invert</code>	A bool. If <code>TRUE</code> , will keep reports not in <code>primaryid</code> .
<code>.fn</code>	<p>A function or formula, accept the field data as the input and return an atomic integer or character of <code>primaryid</code> you want to keep or remove based on argument <code>.invert</code>.</p> <p>If a function, it is used as is.</p> <p>If a formula, e.g. <code>~ .x + 2</code>, it is converted to a function with up to two arguments: <code>.x</code> (single argument) or <code>.x</code> and <code>.y</code> (two arguments). The <code>.</code> placeholder can be used instead of <code>.x</code>. This allows you to create very compact anonymous functions (lambdas) with up to two inputs.</p> <p>If a string, the function is looked up in <code>globalenv()</code>.</p>
<code>.field</code>	<p>A string indicating the FAERS data to be used as input for the <code>.fn</code> function to extract the <code>primaryid</code> or modify data. Only the following values can be used: "demo", "drug", "indi", "ther", "reac", "rpsr", and "outc".</p> <ul style="list-style-type: none"> <code>faers_filter</code>: Use <code>.fn</code> to extract <code>primaryid</code>. If <code>NULL</code>, <code>.object</code> will be passed directly to <code>.fn</code>. <code>.fn</code> should return an atomic integer or character of <code>primaryid</code> that you want to keep or remove based on the <code>.invert</code> argument. <code>faers_modify</code>: Use <code>.fn</code> to modify the specified field data. You cannot use <code>NULL</code> here. <code>.fn</code> should always return a data.table.
<code>.invert</code>	A bool. If <code>TRUE</code> , will keep reports not returned by <code>.fn</code> .

Details

- `faers_get`: Extract a specific field [data.table](#). For `reac` and `indi` field, meddra data will be automatically added if available.
- `faers_mget`: Extract a list of field [data.table](#). For `reac` and `indi` field, meddra data will be automatically added if available.
- `[`, `$`, and `:`: Extract a specific field [data.table](#) or a list of field [data.table](#) from [FAERS](#) object. Note: this just extract field data from @data slot directly. For usual usage, just use `faers_get` or `faers_mget`.
- `faers_primaryid`: Extract the primaryid from demo field.
- `faers_keep`: only keep data from specified primaryid. Note: year, quarter, deletedCases will be kept as the original. So make sure you didn't filter a whole period FAERS quarterly data, in this way, it's much better to run [faers](#).
- `faers_filter`: apply a function to extract the wanted primaryid, then use `faers_keep` to keep data from these primaryids.

Value

See details.

Examples

```
# you must change `dir`, as the file included in the package is sampled
data <- faers(2004, "q1",
  dir = system.file("extdata", package = "faers"),
  compress_dir = tempdir()
)
faers_get(data, "indi")
data[["indi"]]
data$indi
faers_get(data, "demo")
data[["demo"]]
data$demo
faers_mget(data, c("indi", "drug"))
faers_mget(data, c("indi", "demo"))
faers_primaryid(data)
faers_keep(data, primaryid = sample(faers_primaryid(data), 20L))
faers_filter(data, .fn = function(x) {
  sample(x$primaryid, 100L)
}, .field = "demo")
```

faers_load

Load data attached in faers package

Description

Load data attached in faers package

Usage

```
faers_load(nm)
```

Arguments

nm A string of the data name. Available name: "irAEs".

Details

- irAEs: Immune-related adverse events examined in ICI-associated adverse events

Value

- irAEs: A [data.table](#)

References

- Chen Chen, Bin Wu, ChenYu Zhang, Ting Xu, Immune-related adverse events associated with immune checkpoint inhibitors: An updated comprehensive disproportionality analysis of the FDA adverse event reporting system, International Immunopharmacology

Examples

```
faers_load("irAEs")
```

faers_merge	<i>Merge all FAERS field data into one</i>
-------------	--

Description

Merge all FAERS field data into one

Usage

```
faers_merge(object, ...)  
  
## S4 method for signature 'FAERSascii'  
faers_merge(object, fields = NULL, all = TRUE, all.x = all, all.y = all)  
  
## S4 method for signature 'FAERSxml'  
faers_merge(object)  
  
## S4 method for signature 'ANY'  
faers_merge(object)
```


Arguments

<code>object</code>	A FAERSascii or FAERSxml object.
<code>...</code>	Other arguments passed to specific methods.
<code>fields</code>	A character vector specifying the fields to use. Only values "demo", "drug", "indi", "ther", "reac", "rpsr", and "outc" can be used.
<code>all</code>	logical; <code>all = TRUE</code> is shorthand to save setting both <code>all.x = TRUE</code> and <code>all.y = TRUE</code> .
<code>all.x</code>	logical; if <code>TRUE</code> , rows from <code>x</code> which have no matching row in <code>y</code> are included. These rows will have 'NA's in the columns that are usually filled with values from <code>y</code> . The default is <code>FALSE</code> so that only rows with data from both <code>x</code> and <code>y</code> are included in the output.
<code>all.y</code>	logical; analogous to <code>all.x</code> above.

Details

Each pair of field data are merged based on "year", "quarter" and "primaryid". In cases where any pair of data contains information related to "drug_seq" elements, such as "drug_seq", "indi_drug_seq", or "dsg_drug_seq", "drug_seq" will be aligned as well. `fields` shall be organized in the subsequent sequence: 'demo', 'drug', 'indi', 'reac', 'ther', 'rpsr', and 'outc' and the merging sequence will correspondingly adhere to this order. Only the initial instance, of the "caseid" column will be preserved.

Value

A [data.table](#) object.

Note

You'd better only merge necessary data, otherwise a lot of memory will be consumed to merge all fields data.

Examples

```
# you must change `dir`, as the file included in the package is sampled
data <- faers(2004, "q1",
  dir = system.file("extdata", package = "faers"),
  compress_dir = tempdir()
)
faers_merge(data, "indi") # only one field is just like faers_get()
faers_merge(data, c("demo", "indi"))
```

faers_meta	<i>List of FAERS data</i>
------------	---------------------------

Description

The function lists the metadata for the FAERS databases currently available to download.

Usage

```
faers_meta(force = FALSE, internal = !curl::has_internet())
```

Arguments

force	A boolean value. If set to TRUE, it indicates the retrieval of information about all records' metadata in the FAERS Quarterly Data Extract Files Site, bypassing the cache.
internal	A boolean value. It determines whether to use the internal data associated with the package when no cached file is available.

Value

A [data.table](#) reporting years, period, quarter, and file urls and file sizes.

See Also

<https://fis.fda.gov/extensions/FPD-QDE-FAERS/FPD-QDE-FAERS.html>

Examples

```
faers_meta()
```

faers_parse	<i>Parse FAERS Quarterly Data</i>
-------------	-----------------------------------

Description

Parse FAERS Quarterly Data

Usage

```
faers_parse(
  path,
  format = NULL,
  year = NULL,
  quarter = NULL,
  compress_dir = getwd()
)
```

Arguments

path	A string specifies the path of FAERS Quarterly Data. You can pass the FAERS zip file directly, In this way, all files in the zip file will be extracted in compress_dir. Or, you can also uncompressed yourself, and passed the directory contained the uncompressed files.
format	File format to used, only "ascii" and "xml" are availabe. Default: "ascii".
year	Year of the FAERS Quarterly Data. Coerced into integer, if NULL, this will be extracted from path.
quarter	String specifies quarter of the FAERS data, if NULL, this will be extracted from path.
compress_dir	A string specifies the directory to extract files to. It will be created if necessary.

Value

A [FAERSxml](#) or [FAERSascii](#) object.

Unification

For all fields data:

- All names have been converted to lowercase.
- Rename "isr" into "primaryid" for periods before 2012q3.

Field specific operations:

- demo:
 - Rename "gndr_cod" into "sex" for periods before 2014q2.
 - Rename "case" and "i_f_cod" into "caseid" and "i_f_code" for legacy aers, before 2012q3.
 - "age_in_years" was added, measured in years.
 - "country_code" was added (encoded according to the iso2c standards), it will be convenient to translate it into other code with [countrycode](#).
 - "gender" was added, which recoded "UNK", "NS", and "YR" in "sex" as NA.
- ther: Rename "drug_seq" into "dsg_drug_seq" for legacy aers, before 2012q3.
- indi: Rename "drug_seq" into "indi_drug_seq" for legacy aers, before 2012q3.
- outc: Rename "outc_code" into "outc_cod" for 2012q4 data

Examples

```
# the files included in the package are sampled
data <- faers_parse(
  system.file("extdata", "aers_ascii_2004q1.zip", package = "faers"),
  compress_dir = tempdir()
)
```

faers_phv_signal	Create contingency table and run disproportionality analysis
------------------	--

Description

Create contingency table and run disproportionality analysis

Usage

```
faers_phv_table(.object, ..., .full, .object2)

## S4 method for signature 'FAERSascii,FAERSascii,missing'
faers_phv_table(.object, .events = "soc_name", ..., .full, .object2)

## S4 method for signature 'FAERSascii,missing,FAERSascii'
faers_phv_table(.object, .events = "soc_name", ..., .full, .object2)

faers_phv_signal(.object, ...)

## S4 method for signature 'FAERSascii'
faers_phv_signal(
  .object,
  .methods = NULL,
  ...,
  .phv_signal_params = list(),
  BPPARAM = SerialParam()
)
```

Arguments

.object	A FAERSascii object. The value n11 or a will be calculated from .object. The unique number of primaryids will be regarded as n1..
...	Other arguments passed to specific methods. <ul style="list-style-type: none"> • faers_phv_table: other arguments passed to faers_counts. • faers_phv_signal: other arguments passed to faers_phv_table.
.full	A FAERSascii object with data from full data. In this way, .object must be a subset of .full. The unique number of primaryids will be regarded as n.
.object2	A FAERSascii object with data from another interested drug. In this way, .object and .object2 should be not overlapped. The unique number of primaryids will be regarded as n0..
.events	A character specify the events column(s) in the .field data to count the unique primaryid. If multiple columns were selected, the combination for all columns will define the interested events.
.methods	Just an alias of method in phv_signal .

`.phv_signal_params` Other arguments passed to [phv_signal](#).

`BPPARAM` An optional [BiocParallelParam](#) instance defining the parallel back-end to be used during evaluation.

Details

- `faers_phv_table`: build a contingency table for all events in `.events`.
- `faers_phv_signal`: Pharmacovigilance Analysis used contingency table constructed with `faers_phv_table`. You must pass `.full` or `.object2` into `faers_phv_table`.

Value

A [data.table](#) object.

See Also

[phv_signal](#)

Examples

```
# you must change `dir`, as the files included in the package are sampled
data <- faers(c(2004, 2017), c("q1", "q2"),
  dir = system.file("extdata", package = "faers"),
  compress_dir = tempdir()
)
## Not run:
# you must standardize and deduplication before disproportionality analysis
# you should replace `meddra_path` with yours
data <- faers_standardize(data, meddra_path)
data <- faers_dedup(data)
# we use faers_filter() to extract data we are interested
# here, we just sample 100 reports. You should do it based on your purpose.
faers_phv_signal(
  faers_filter(data, .fn = ~ sample(faers_primaryid(.x), 100L)),
  .full = data
)

## End(Not run)
```

<code>faers_standardize</code>	<i>Standardize FAERS Quarterly Data for Preferred Term and drug names</i>
--------------------------------	---

Description

Standardize FAERS Quarterly Data for Preferred Term and drug names

Usage

```
faers_standardize(object, ...)

## S4 method for signature 'FAERSascii'
faers_standardize(object, meddra_path, add_smq = FALSE)
```

Arguments

object	A FAERSascii object.
...	Other arguments passed to specific methods.
meddra_path	A string, define the path of MedDRA directory.
add_smq	A bool, indicates whether Standardised MedDRA Queries (SMQ) should be added. If TRUE, "smq_content.asc", and "smq_list.asc" must exist.

Value

A [FAERSascii](#) object.

See Also

[MedDRA](#)

Examples

```
## # you must change `dir`, as the files included in the package are sampled
data <- faers(c(2004, 2017), c("q1", "q2"),
  dir = system.file("extdata", package = "faers"),
  compress_dir = tempdir()
)
## Not run:
# you should replace `meddra_path` with yours
data <- faers_standardize(data, meddra_path)

## End(Not run)
```

fda_drugs

Read and Parse Drugs@FDA data

Description

Read and Parse Drugs@FDA data

Usage

```
fda_drugs(pattern = "Products", list = FALSE, force = FALSE)
```

Arguments

pattern	File pattern to use. Must define a file exactly, you can set <code>list = TRUE</code> to see what files can be used.
list	A boolean value, should it only list files in the <code>Drugs@FDA</code> dataset?
force	A boolean value. If set to <code>TRUE</code> , it indicates the retrieval of <code>Drugs@FDA</code> data in the FDA directly, bypassing the cache.

Value

- if `list = TRUE`, an atomic character.
- if `list = FALSE`, a [data.table](#).

See Also

<https://www.fda.gov/drugs/drug-approvals-and-databases/drugsfda-data-files>

Examples

```
fda_drugs(list = TRUE)
fda_drugs()
```

MedDRA-class

MedDRA class

Description

Provide a container for MedDRA Data file

Usage

```
meddra(path, add_smq = FALSE)

## S4 method for signature 'MedDRA'
show(object)

meddra_hierarchy(object, ...)

## S4 method for signature 'MedDRA'
meddra_hierarchy(object)

meddra_smq(object, ...)

## S4 method for signature 'MedDRA'
meddra_smq(object)

meddra_version(object, ...)
```

```
## S4 method for signature 'MedDRA'
meddra_version(object)
```

Arguments

path	A string, define the path of MedDRA directory.
add_smq	A bool, indicates whether Standardised MedDRA Queries (SMQ) should be added. If TRUE, "smq_content.asc", and "smq_list.asc" must exist.
object	A MedDRA object.
...	Other arguments passed to specific methods.

Value

- meddra: A MedDRA object.
- meddra_hierarchy: Extract the hierarchy slot.
- meddra_smq: Extract the smq slot.
- meddra_version: Extract the version slot.

Slots

hierarchy A [data.table](#) or NULL representing the meddra hierarchy data. There are five levels to the MedDRA hierarchy, arranged from very specific to very general.

smq A [data.table](#) or NULL representing the meddra smq data. Standardised MedDRA Queries (SMQs) are used to support signal detection and monitoring. SMQs are validated, standard sets of MedDRA terms. These sets of terms have undergone extensive review, testing, analysis and expert discussion. SMQs represent a variety of safety topics of regulatory interest (e.g., SMQ Severe cutaneous adverse reactions, SMQ Anaphylactic reaction).

version A string, the version of MedDRA.

See Also

- <https://www.meddra.org/>
- <https://www.meddra.org/how-to-use/basics/hierarchy>
- <https://www.meddra.org/how-to-use/tools/smq>

Description

Pharmacovigilance, also known as drug safety. In the context of pharmacovigilance studies, disproportionality analysis primarily served as a tool to evaluate possible association between a specific adverse event and a particular drug which can then be investigated through clinical assessment of individual case reports.

Usage

```
phv_signal(  
  a,  
  b,  
  c,  
  d,  
  methods = NULL,  
  alpha = 0.05,  
  correct = TRUE,  
  n_mcmc = 100000L,  
  alpha1 = 0.5,  
  alpha2 = 0.5,  
  theta_init = NULL,  
  squashing = TRUE,  
  BPPARAM = SerialParam()  
)  
  
phv_ror(a, b, c, d, alpha = 0.05)  
  
phv_prr(a, b, c, d, alpha = 0.05)  
  
phv_chisq(a, b, c, d, correct = TRUE, BPPARAM = SerialParam())  
  
phv_fisher(a, b, c, d, alpha = 0.05, BPPARAM = SerialParam())  
  
phv_bcpnn_norm(a, b, c, d, alpha = 0.05)  
  
phv_bcpnn_mcmc(  
  a,  
  b,  
  c,  
  d,  
  alpha = 0.05,  
  n_mcmc = 100000L,  
  BPPARAM = SerialParam()  
)  
  
phv_obsexp_shrink(  
  a,  
  b,  
  c,  
  d,  
  alpha = 0.05,  
  alpha1 = 0.5,  
  alpha2 = 0.5,  
  n_mcmc = 100000L,  
  BPPARAM = SerialParam()  
)
```

```
phv_ebgm(a, b, c, d, alpha = 0.05, theta_init = NULL, squashing = TRUE)
```

Arguments

a	also referred to as n11 as this is the count of event of interest under exposure of interest.
b	also referred to as n10 as this is the count of <i>not</i> event of interest under exposure of interest.
c	also referred to as n01 as this is the count of event of interest under <i>not</i> exposure of interest.
d	also referred to as n00 as this is the count of <i>not</i> event of interest under <i>not</i> exposure of interest.
methods	An atomic character, specifies the method used to signal mining. Currently, only "ror", "pr", "chisq", "bcpnn_norm", "bcpnn_mcmc", "obsexp_shrink", "fisher", and "ebgm" are supported. If NULL, all supported methods will be used.
alpha	Level of significance, for construction of the confidence intervals.
correct	A bool indicating whether to apply Yates's continuity correction when computing the chi-squared statistic.
n_mcmc	Number of MCMC simulations per (a,b,c,d)-tuple to calculate confidence intervals.
alpha1	Numerator shrinkage parameter ≥ 0 , default 0.5.
alpha2	Denominator shrinkage parameter ≥ 0 , default 0.5.
theta_init	A data frame of initial hyperparameter guesses with columns ordered as: alpha1, beta1, alpha2, beta2. See openEBGM::autoHyper
squashing	A bool, whether do automated data squashing. If any zeros found in a, will always be TRUE.
BPPARAM	An optional BiocParallelParam instance defining the parallel back-end to be used during evaluation.

Details

Note that the a, b, c, d inputs can be an atomic vectors of equal length, for which the function will perform the calculations for each individual (a,b,c,d)-tuple moving across the vectors.

It is assumed that the contingency table under consideration has drugs/exposures in the rows and outcomes/events in the columns. See contingency table section.

We use the distinct patient count method to obtain the frequency counts of patients exposed to each interested drug, those reporting interested event. As illustrated in the Contingency table, n equals the total number of patients in the database, n11 is the number of patients with exposure to the interested drug during the model period and reporting interested events, n10 is the number of patients that have used the interested drug but did not experience interested event during any of the model periods associated with the drug, n01 is the number of patients that did not use the interested drug but experienced interested event, and n00 is the number of patients that were not exposed to the interested drug and did not report interested condition.

Value

A [data.table](#) with columns of estimated value and it's confidence interval (ci_low and ci_high). Estimated column are as follows:

- phv_ror: reporting odds ratio (ror).
- phv_prr: proportional reporting ratio (pr). Signal defined as a prr of at least 2, chi-squared with Yates's correction of at least 4 and $a \geq 3$. An equivalent alternative to chi-squared is to calculate a confidence interval around the prr.
- phv_bcpnn_norm: information component (ic).
- phv_bcpnn_mcmc: information component (ic).
- phv_obsexp_shrink: observed to expected ratio (oe_ratio).
- phv_ebgm: Empirical Bayes Geometric Mean (ebgm).

Contingency table

	ADR of interest	Other ADRs	Total
Drug of interest	a=n11	b=n10	a+b=n1.
Other drugs	c=n01	d=n00	c+d=n0.
Total	a+c=n.1	b+d=n.0	a+b+c+d=n

phv_obsexp_shrink

The observed to expected (OE) ratio with approximate confidence intervals are constructed on the log2 scale as outlined in Norén et al. (2013).

Expected value was estimated by $(a + b) / (a + b + c + d) * (a + c)$.

The OE ratio with shrinkage estimates is calculated as $(0 + \alpha_1) / (E + \alpha_2)$.

If $(0 + \alpha_1) < 1$, then the exact uncertainty limits should be used. That is the confidence intervals as implemented in phv_bcpnn_mcmc (Norén et al., 2013).

$\log_2(OE)$ approximates the Bayesian confidence propagation neural network information component (IC) with reasonable accuracy when $\alpha_1 = \alpha_2 = 0.5$ (Norén et al., 2013).

phv_ebgm

An implementation of the Gamma-Poisson Shrinker (GPS) model for identifying unexpected counts in large contingency tables using an empirical Bayes approach. The Empirical Bayes Geometric Mean (EBGM) and quantile scores are obtained from the GPS model estimates. The GPS was proposed by DuMouchel as a signal detection tool for large frequency tables with both observed (O) and expected (E) counts for each drug-outcome pair. It assumes the observed count of any drug-outcome pair follows the Poisson distribution.

For each drug-outcome pair, the primary parameter of interest was the risk ratio. Rather than using the observed over expected (O/E), GPS uses the empirical Bayesian geometric mean (EBGM) posterior distribution of the risk ratio and the surrounding confidence interval for each drug-outcome

pair to identify statistical signals of excess risk. To prevent spurious false positives due to implausibly high risk ratios, GPS implements a Bayesian framework that “shrinks” O/E estimates towards a value which is close to the average O/E values for all drug-event pairs at each level of granularity.

References

- David Olaleye, SAS Institute Inc. (2019), Real-World Evidence and Population Health Analytics: Intersection and Application, <https://support.sas.com/resources/papers/proceedings19/3361-2019.pdf>
- Evans, S.J.W., Waller, P.C. and Davis, S. (2001), Use of proportional reporting ratios (PRRs) for signal generation from spontaneous adverse drug reaction reports. *Pharmacoepidem. Drug Safe.*, 10: 483-486. <https://doi.org/10.1002/pds.677>
- Norén GN, Hopstadius J, Bate A. Shrinkage observed-to-expected ratios for robust and transparent large-scale pattern discovery. *Statistical methods in medical research*. 2013 Feb;22(1):57-69.
- <https://journal.r-project.org/archive/2017/RJ-2017-063/RJ-2017-063.pdf>

Examples

```
phv_signal(122, 1320, 381, 31341)
phv_signal(122, 1320, 381, 31341, "ror")
phv_ror(122, 1320, 381, 31341)
phv_signal(122, 1320, 381, 31341, "prrr")
phv_prr(122, 1320, 381, 31341)
phv_signal(122, 1320, 381, 31341, "chisq")
phv_chisq(122, 1320, 381, 31341)
phv_signal(122, 1320, 381, 31341, "bcpnn_norm")
phv_bcpnn_norm(122, 1320, 381, 31341)
phv_signal(122, 1320, 381, 31341, "bcpnn_mcmc")
phv_bcpnn_mcmc(122, 1320, 381, 31341)
phv_signal(122, 1320, 381, 31341, "obsexp_shrink")
phv_obsexp_shrink(122, 1320, 381, 31341)
phv_signal(122, 1320, 381, 31341, "fisher")
phv_fisher(122, 1320, 381, 31341)
phv_signal(122, 1320, 381, 31341, "ebgm")
phv_ebgm(122, 1320, 381, 31341)
```

Index

* **internal**

- faers-package, [3](#)
- [,FAERSascii,ANY,ANY,ANY-method (faers_get), [13](#)
- [,FAERSascii-method (faers_get), [13](#)
- [[,FAERSascii-method (faers_get), [13](#)
- [,FAERSascii-method (faers_get), [13](#)
- athena, [3](#)
- BiocParallelParam, [21](#), [26](#)
- copy, [10](#)
- countrycode, [19](#)
- data.table, [4](#), [6](#), [10](#), [11](#), [14–18](#), [21](#), [23](#), [24](#), [27](#)
- deletedCases, [11](#)
- FAERS, [9](#), [15](#)
- FAERS (FAERS-class), [5](#)
- faers, [4](#), [15](#)
- FAERS-class, [5](#)
- faers-package, [3](#)
- faers_available, [7](#)
- faers_before_period, [8](#)
- faers_clearcache, [8](#)
- faers_combine, [9](#)
- faers_counts, [10](#), [20](#)
- faers_counts,FAERSascii-method (faers_counts), [10](#)
- faers_data (FAERS-class), [5](#)
- faers_data,FAERS-method (FAERS-class), [5](#)
- faers_dedup, [6](#), [9](#), [11](#)
- faers_dedup,ANY-method (faers_dedup), [11](#)
- faers_dedup,FAERSascii-method (faers_dedup), [11](#)
- faers_dedup,FAERSxml-method (faers_dedup), [11](#)
- faers_deleted_cases (FAERS-class), [5](#)
- faers_deleted_cases,FAERSascii-method (FAERS-class), [5](#)

- faers_download, [12](#)
- faers_field (FAERS-class), [5](#)
- faers_filter (faers_get), [13](#)
- faers_filter,FAERSascii-method (faers_get), [13](#)
- faers_get, [13](#)
- faers_get,FAERSascii-method (faers_get), [13](#)
- faers_header (FAERS-class), [5](#)
- faers_header,FAERSxml-method (FAERS-class), [5](#)
- faers_keep (faers_get), [13](#)
- faers_keep,FAERSascii-method (faers_get), [13](#)
- faers_load, [15](#)
- faers_meddra (FAERS-class), [5](#)
- faers_meddra,FAERS-method (FAERS-class), [5](#)
- faers_merge, [16](#)
- faers_merge,ANY-method (faers_merge), [16](#)
- faers_merge,FAERSascii-method (faers_merge), [16](#)
- faers_merge,FAERSxml-method (faers_merge), [16](#)
- faers_meta, [18](#)
- faers_mget (faers_get), [13](#)
- faers_mget,FAERSascii-method (faers_get), [13](#)
- faers_modify (faers_get), [13](#)
- faers_modify,FAERSascii-method (faers_get), [13](#)
- faers_parse, [18](#)
- faers_period, [9](#)
- faers_period (FAERS-class), [5](#)
- faers_period,FAERS-method (FAERS-class), [5](#)
- faers_phv_signal, [20](#)
- faers_phv_signal,FAERSascii-method (faers_phv_signal), [20](#)

[faers_phv_table \(faers_phv_signal\), 20](#)
[faers_phv_table, FAERSascii, FAERSascii-missing, \[phv_signal\]\(#\), 20, 21, 24](#)
[\(faers_phv_signal\), 20](#)
[faers_phv_table, FAERSascii, missing, FAERSascii-method](#)
[\(faers_phv_signal\), 20](#)
[faers_primaryid \(faers_get\), 13](#)
[faers_primaryid, FAERSascii-method](#)
[\(faers_get\), 13](#)
[faers_quarter \(FAERS-class\), 5](#)
[faers_quarter, FAERS-method](#)
[\(FAERS-class\), 5](#)
[faers_standardize, 9, 12, 21](#)
[faers_standardize, FAERSascii-method](#)
[\(faers_standardize\), 21](#)
[faers_year \(FAERS-class\), 5](#)
[faers_year, FAERS-method \(FAERS-class\), 5](#)
[FAERSascii, 4, 9–14, 17, 19, 20, 22](#)
[FAERSascii \(FAERS-class\), 5](#)
[FAERSascii-class \(FAERS-class\), 5](#)
[FAERSxml, 4, 9, 17, 19](#)
[FAERSxml \(FAERS-class\), 5](#)
[FAERSxml-class \(FAERS-class\), 5](#)
[fda_drugs, 22](#)

[MedDRA, 6, 22](#)
[MedDRA \(MedDRA-class\), 23](#)
[meddra \(MedDRA-class\), 23](#)
[MedDRA-class, 23](#)
[meddra_hierarchy \(MedDRA-class\), 23](#)
[meddra_hierarchy, MedDRA-method](#)
[\(MedDRA-class\), 23](#)
[meddra_smq \(MedDRA-class\), 23](#)
[meddra_smq, MedDRA-method](#)
[\(MedDRA-class\), 23](#)
[meddra_version \(MedDRA-class\), 23](#)
[meddra_version, MedDRA-method](#)
[\(MedDRA-class\), 23](#)

[new_handle, 4, 12](#)

[openEBGM: :autoHyper, 26](#)

[phv_bcpnn_mcmc \(phv_signal\), 24](#)
[phv_bcpnn_norm \(phv_signal\), 24](#)
[phv_chisq \(phv_signal\), 24](#)
[phv_ebgm \(phv_signal\), 24](#)
[phv_fisher \(phv_signal\), 24](#)
[phv_obsexp_shrink \(phv_signal\), 24](#)
[phv_prr \(phv_signal\), 24](#)