

Package ‘martini’

January 26, 2021

Type Package

Title GWAS Incorporating Networks

Version 1.11.0

Description martini deals with the low power inherent to GWAS studies by using prior knowledge represented as a network. SNPs are the vertices of the network, and the edges represent biological relationships between them (genomic adjacency, belonging to the same gene, physical interaction between protein products). The network is scanned using SConES, which looks for groups of SNPs maximally associated with the phenotype, that form a close subnetwork.

License MIT + file LICENSE

LazyData TRUE

Imports igraph (>= 1.0.1), Matrix, methods (>= 3.3.2), memoise (>= 1.1.0), Rcpp (>= 0.12.8), snpStats (>= 1.20.0), S4Vectors (>= 0.12.2), stats, utils

Suggests biomaRt (>= 2.34.1), STRINGdb, httr (>= 1.2.1), IRanges (>= 2.8.2), knitr, testthat, readr, rmarkdown

Depends R (>= 3.6)

LinkingTo Rgin, Rcpp, RcppEigen (>= 0.3.3.5.0)

RoxygenNote 7.1.1

Encoding UTF-8

biocViews Software, GenomeWideAssociation, SNP, GeneticVariability, Genetics, FeatureExtraction, GraphAndNetwork, Network

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/martini>

git_branch master

git_last_commit 4368b2f

git_last_commit_date 2020-12-03

Date/Publication 2021-01-25

Author Hector Climente-Gonzalez [aut, cre]
(<<https://orcid.org/0000-0002-3030-7471>>),
Chloe-Agathe Azencott [aut] (<<https://orcid.org/0000-0003-1003-301X>>)

Maintainer Hector Climente-Gonzalez <hector.climente@riken.jp>

R topics documented:

evo	2
get_GI_network	3
get_GM_network	4
get_GS_network	5
ldweight_edges	5
minigwas	6
minippi	6
minisnpMapping	7
run_scones	7
scones	8
scones.cv	9
search_cones	10
sigmod	11
sigmod.cv	12
simulate_causal_snps	13
simulate_phenotype	13
subvert	14
Index	16

evo

Run evo.

Description

Run evo.

Usage

evo(X, Y, W, opts)

Arguments

X	A matrix with the genotypes.
Y	A vector with the phenotypes.
W	A sparse matrix containing the adjacency matrix of the network.
opts	A named list with the settings.

Value

An object with the evo results.

get_GI_network *Get gene-interaction network.*

Description

Creates a network of SNPs where each SNP is connected as in the **GM** network and, in addition, to all the other SNPs pertaining to any interactor of the gene it is mapped to. Corresponds to the gene-interaction (GI) network described by Azencott et al.

Usage

```
get_GI_network(  
  gwas,  
  organism = 9606,  
  snpMapping = snp2gene(gwas, organism),  
  ppi = get_gxg_string(organism),  
  col_ppi = c("gene1", "gene2"),  
  col_genes = c("snp", "gene"),  
  flush = FALSE  
)
```

Arguments

gwas	A SnpMatrix object with the GWAS information.
organism	Tax ID of the studied organism. Required if snpMapping is not provided. The default is 9606 (human).
snpMapping	A data.frame informing how SNPs map to genes. It contains minimum two columns: SNP id and a gene it maps to. Each row corresponds to one gene-SNP mapping. Unless column names are specified using col_genes, involved columns must be named 'snp' and 'gene'.
ppi	A data.frame describing protein-protein interactions with at least two columns. Gene ids must be the contained in snpMapping. Unless column names are specified using col_ppi, involved columns must be named gene1 and gene2.
col_ppi	Optional, length-2 character vector with the names of the two columns involving the protein-protein interactions.
col_genes	Optional, length-2 character vector with the names of the two columns involving the SNP-gene mapping. The first element is the column of the SNP, and the second is the column of the gene.
flush	Remove cached results? Boolean value.

Value

An igraph network of the GI network of the SNPs.

References

Azencott, C. A., Grimm, D., Sugiyama, M., Kawahara, Y., & Borgwardt, K. M. (2013). Efficient network-guided multi-locus association mapping with graph cuts. *Bioinformatics*, 29(13), 171-179. <https://doi.org/10.1093/bioinformatics/btt238>

Examples

```
get_GI_network(minigwas, snpMapping = minisnpMapping, ppi = minippi)
```

get_GM_network	<i>Get gene membership network.</i>
----------------	-------------------------------------

Description

Creates a network of SNPs where each SNP is connected as in the [GS](#) network and, in addition, to all the other SNPs pertaining to the same gene. Corresponds to the gene membership (GM) network described by Azencott et al.

Usage

```
get_GM_network(  
  gwas,  
  organism = 9606,  
  snpMapping = snp2gene(gwas, organism),  
  col_genes = c("snp", "gene")  
)
```

Arguments

gwas	A SnpMatrix object with the GWAS information.
organism	Tax ID of the studied organism. Required if snpMapping is not provided. The default is 9606 (human).
snpMapping	A data.frame informing how SNPs map to genes. It contains minimum two columns: SNP id and a gene it maps to. Each row corresponds to one gene-SNP mapping. Unless column names are specified using col_genes, involved columns must be named 'snp' and 'gene'.
col_genes	Optional, length-2 character vector with the names of the two columns involving the SNP-gene mapping. The first element is the column of the SNP, and the second is the column of the gene.

Value

An igraph network of the GM network of the SNPs.

References

Azencott, C. A., Grimm, D., Sugiyama, M., Kawahara, Y., & Borgwardt, K. M. (2013). Efficient network-guided multi-locus association mapping with graph cuts. *Bioinformatics*, 29(13), 171-179. <https://doi.org/10.1093/bioinformatics/btt238>

Examples

```
get_GM_network(minigwas, snpMapping = minisnpMapping)
```

get_GS_network	<i>Get genomic sequence network.</i>
----------------	--------------------------------------

Description

Creates a network of SNPs where each SNP is connected to its adjacent SNPs in the genome sequence. Corresponds to the genomic sequence (GS) network described by Azencott et al.

Usage

```
get_GS_network(gwas)
```

Arguments

gwas	A SnpMatrix object with the GWAS information.
------	---

Value

An igraph network of the GS network of the SNPs.

References

Azencott, C. A., Grimm, D., Sugiyama, M., Kawahara, Y., & Borgwardt, K. M. (2013). Efficient network-guided multi-locus association mapping with graph cuts. *Bioinformatics*, 29(13), 171-179. <https://doi.org/10.1093/bioinformatics/btt238>

Examples

```
get_GS_network(minigwas)
```

ldweight_edges	<i>Include linkage disequilibrium information in the network.</i>
----------------	---

Description

Include linkage disequilibrium information in the SNP network. The weight of the edges will be lower the higher the linkage is.

Usage

```
ldweight_edges(net, ld, method = "inverse")
```

Arguments

net	A SNP network.
ld	A dsCMatrix or dgCMatrix containing linkage disequilibrium measures, like the output of <code>ld</code> .
method	How to incorporate linkage-disequilibrium values into the network.

Value

A copy of net where the edges weighted according to linkage disequilibrium.

Examples

```
ld <- snpStats::ld(minigwas[['genotypes']], depth = 2, stats = "R.squared")
# don't weight edges for which LD cannot be calculated
ld[is.na(ld)] <- 0
gi <- get_GI_network(minigwas, snpMapping = minisnpMapping, ppi = minippi)
ldGi <- ldweight_edges(gi, ld)
```

minigwas

Description of the minigwas dataset.

Description

Small GWAS example.

Format

A list with 3 items:

genotypes Genotype and phenotype information.

fam Simulated network.

map Result of running find_cones with gwas and net.

Examples

```
data(minigwas)

# access different elements
minigwas[["genotypes"]]
minigwas[["map"]]
minigwas[["fam"]]
```

minippi

PPIs for the minigwas dataset.

Description

data.frame describing pairs of proteins that interact for minigwas.

Examples

```
data(minippi)

head(minippi)
```

minisnpMapping	<i>Genes for the minigwas dataset.</i>
----------------	--

Description

data.frame that maps SNPs from minigwas to their gene.

Examples

```
data(minisnpMapping)
```

```
head(minisnpMapping)
```

run_scones	<i>Run shake.</i>
------------	-------------------

Description

Run scones.

Usage

```
run_scones(c, eta, lambda, W)
```

Arguments

c	A vector with the association of each SNP with the phenotype.
eta	A numeric with the value of the eta parameter.
lambda	A numeric with the value of the eta parameter.
W	A sparse matrix with the connectivity.

Value

A list with vector indicating if the feature was selected and the objective score.

scones	<i>Find connected explanatory SNPs.</i>
--------	---

Description

Finds the SNPs maximally associated with a phenotype while being connected in an underlying network.

Usage

```
scones(gwas, net, eta, lambda, covars = data.frame(), score = "chi2")
```

Arguments

gwas	A SnpMatrix object with the GWAS information.
net	An igraph network that connects the SNPs.
eta	Value of the eta parameter.
lambda	Value of the lambda parameter.
covars	A data frame with the covariates. It must contain a column 'sample' containing the sample IDs, and an additional columns for each covariate.
score	Association score to measure association between genotype and phenotype. Possible values: chi2 (default), glm.

Value

A copy of the SnpMatrix\$map data.frame, with the following additions:

- c: contains the univariate association score for every single SNP.
- selected: logical vector indicating if the SNP was selected by SConES or not.
- module: integer with the number of the module the SNP belongs to.

References

Azencott, C. A., Grimm, D., Sugiyama, M., Kawahara, Y., & Borgwardt, K. M. (2013). Efficient network-guided multi-locus association mapping with graph cuts. *Bioinformatics*, 29(13), 171-179. <https://doi.org/10.1093/bioinformatics/btt238>

Examples

```
gi <- get_GI_network(minigwas, snpMapping = minisnpMapping, ppi = minippi)
scones(minigwas, gi, 10, 1)
```


scones.cv

*Find connected explanatory SNPs.***Description**

Finds the SNPs maximally associated with a phenotype while being connected in an underlying network. Select the hyperparameters by cross-validation.

Usage

```
scones.cv(gwas, net, covars = data.frame(), ...)
```

Arguments

gwas	A SnpMatrix object with the GWAS information.
net	An igraph network that connects the SNPs.
covars	A data frame with the covariates. It must contain a column 'sample' containing the sample IDs, and an additional columns for each covariate.
score	Association score to measure association between genotype and phenotype. Possible values: chi2 (default), glm.
criterion	String with the function to measure the quality of a split. Possible values: consistency (default), bic, aic, aicc.
etas	Numeric vector with the etas to explore in the grid search. If omitted, it's automatically created based on the association scores.
lambdas	Numeric vector with the lambdas to explore in the grid search. If omitted, it's automatically created based on the association scores.
c	Numeric vector with the association scores of the SNPs. Specify it to automatically an appropriate range of etas and lambdas.

Value

A copy of the `SnpMatrix$map` data.frame, with the following additions:

- `c`: contains the univariate association score for every single SNP.
- `selected`: logical vector indicating if the SNP was selected by SConES or not.
- `module`: integer with the number of the module the SNP belongs to.

References

Azencott, C. A., Grimm, D., Sugiyama, M., Kawahara, Y., & Borgwardt, K. M. (2013). Efficient network-guided multi-locus association mapping with graph cuts. *Bioinformatics*, 29(13), 171-179. <https://doi.org/10.1093/bioinformatics/btt238>

Examples

```
gi <- get_GI_network(minigwas, snpMapping = minisnpMapping, ppi = minippi)
scones.cv(minigwas, gi)
scones.cv(minigwas, gi, score = "glm")
```

search_cones	<i>Find connected explanatory SNPs.</i>
--------------	---

Description

Finds the SNPs maximally associated with a phenotype while being connected in an underlying network (Azencott et al., 2013).

Usage

```
search_cones(gwas, net, encoding = "additive", sigmod = FALSE, ...)
```

Arguments

gwas	A SnpMatrix object with the GWAS information.
net	An igraph network that connects the SNPs.
encoding	SNP encoding. Possible values: additive (default), recessive, dominant, codominant.
sigmod	Boolean. If TRUE, use the Sigmod variant of SConES, meant to prioritize tightly connected clusters of SNPs.
...	Extra arguments for get_evo_settings .

Value

A copy of the SnpMatrix\$map data.frame, with the following additions:

- C: contains the univariate association score for every single SNP.
- selected: logical vector indicating if the SNP was selected by SConES or not.
- module: integer with the number of the module the SNP belongs to.

References

Azencott, C. A., Grimm, D., Sugiyama, M., Kawahara, Y., & Borgwardt, K. M. (2013). Efficient network-guided multi-locus association mapping with graph cuts. *Bioinformatics*, 29(13), 171-179. <https://doi.org/10.1093/bioinformatics/btt238>

Examples

```
gi <- get_GI_network(minigwas, snpMapping = minisnpMapping, ppi = minippi)
search_cones(minigwas, gi)
search_cones(minigwas, gi, encoding = "recessive")
search_cones(minigwas, gi, associationScore = "skat")
```

sigmod	<i>Find connected explanatory SNPs.</i>
--------	---

Description

Finds the SNPs maximally associated with a phenotype while being connected in an underlying network.

Usage

```
sigmod(gwas, net, eta, lambda, covars = data.frame(), score = "chi2")
```

Arguments

gwas	A SnpMatrix object with the GWAS information.
net	An igraph network that connects the SNPs.
eta	Value of the eta parameter.
lambda	Value of the lambda parameter.
covars	A data frame with the covariates. It must contain a column 'sample' containing the sample IDs, and an additional columns for each covariate.
score	Association score to measure association between genotype and phenotype. Possible values: chi2 (default), glm.

Value

A copy of the SnpMatrix\$map data.frame, with the following additions:

- c: contains the univariate association score for every single SNP.
- selected: logical vector indicating if the SNP was selected by SConES or not.
- module: integer with the number of the module the SNP belongs to.

References

Azencott, C. A., Grimm, D., Sugiyama, M., Kawahara, Y., & Borgwardt, K. M. (2013). Efficient network-guided multi-locus association mapping with graph cuts. *Bioinformatics*, 29(13), 171-179. <https://doi.org/10.1093/bioinformatics/btt238>

Examples

```
gi <- get_GI_network(minigwas, snpMapping = minisnpMapping, ppi = minippi)
scones(minigwas, gi, 10, 1)
```

sigmod.cv

*Find connected explanatory SNPs.***Description**

Finds the SNPs maximally associated with a phenotype while being connected in an underlying network. Select the hyperparameters by cross-validation.

Usage

```
sigmod.cv(gwas, net, covars = data.frame(), ...)
```

Arguments

gwas	A SnpMatrix object with the GWAS information.
net	An igraph network that connects the SNPs.
covars	A data frame with the covariates. It must contain a column 'sample' containing the sample IDs, and an additional columns for each covariate.
score	Association score to measure association between genotype and phenotype. Possible values: chi2 (default), glm.
criterion	String with the function to measure the quality of a split. Possible values: consistency (default), bic, aic, aicc.
etas	Numeric vector with the etas to explore in the grid search. If omitted, it's automatically created based on the association scores.
lambdas	Numeric vector with the lambdas to explore in the grid search. If omitted, it's automatically created based on the association scores.
c	Numeric vector with the association scores of the SNPs. Specify it to automatically an appropriate range of etas and lambdas.

Value

A copy of the SnpMatrix\$map data.frame, with the following additions:

- c: contains the univariate association score for every single SNP.
- selected: logical vector indicating if the SNP was selected by SConES or not.
- module: integer with the number of the module the SNP belongs to.

References

Liu, Y., Brossard, M., Roqueiro, D., Margaritte-Jeannin, P., Sarnowski, C., Bouzigon, E., Demenais, F. (2017). SigMod: an exact and efficient method to identify a strongly interconnected disease-associated module in a gene network. *Bioinformatics*, 33(10), 1536–1544. <https://doi.org/10.1093/bioinformatics/btx004>

Examples

```
gi <- get_GI_network(minigwas, snpMapping = minisnpMapping, ppi = minippi)
sigmod.cv(minigwas, gi)
sigmod.cv(minigwas, gi, score = "glm")
```

simulate_causal_snps *Simulate causal SNPs*

Description

Selects randomly interconnected genes as causal, then selects a proportion of them as causal.

Usage

```
simulate_causal_snps(net, ngenes = 20, pcausal = 1)
```

Arguments

net	An igraph gene-interaction (GI) network that connects the SNPs.
ngenes	Number of causal genes.
pcausal	Number between 0 and 1, proportion of the SNPs in causal genes that are causal themselves.

Value

A vector with the ids of the simulated causal SNPs.

Examples

```
gi <- get_GI_network(minigwas, snpMapping = minisnpMapping, ppi = minippi)
simulate_causal_snps(gi, ngenes=2)
```

simulate_phenotype *Simulate phenotype*

Description

Simulates a phenotype from a GWAS experiment and a specified set of causal SNPs. If the data is qualitative, only controls are used.

Usage

```
simulate_phenotype(  
  gwas,  
  snps,  
  h2,  
  model = "additive",  
  effectSize = rnorm(length(snps)),  
  qualitative = FALSE,  
  ncases,  
  ncontrols,  
  prevalence  
)
```

Arguments

gwas	A SnpMatrix object with the GWAS information.
snps	Character vector with the SNP ids of the causal SNPs. Must match SNPs in <code>gwas[["map"]][["snp.names"]]</code> .
h2	Heritability of the phenotype (between 0 and 1).
model	String specifying the genetic model under the phenotype. Accepted values: "additive".
effectSize	Numeric vector with the same length as the number of causal SNPs. It indicates the effect size of each of the SNPs; if absent, they are sampled from a normal distribution.
qualitative	Bool indicating if the phenotype is qualitative or not (quantitative).
ncases	Integer specifying the number of cases to simulate in a qualitative phenotype. Required if <code>qualitative = TRUE</code> .
ncontrols	Integer specifying the number of controls to simulate in a qualitative phenotype. Required if <code>qualitative = TRUE</code> .
prevalence	Value between 0 and 1 specifying the population prevalence of the disease. Note that <code>ncases</code> cannot be greater than <code>prevalence * number of samples</code> . Required if <code>qualitative = TRUE</code> .

Value

A copy of the GWAS experiment with the new phenotypes in `gwas[["fam"]][["affected"]]`.

References

Inspired from GCTA simulation tool: <http://cnsgenomics.com/software/gcta/Simu.html>.

Examples

```
gi <- get_GI_network(minigwas, snpMapping = minisnpMapping, ppi = minippi)
causal <- simulate_causal_snps(gi, ngenes = 2)
simulate_phenotype(minigwas, causal, h2 = 1)
```

subvert

Vertices with an attribute

Description

Returns the nodes matching some condition.

Usage

```
subvert(net, attr, values, affirmative = TRUE)
```

Arguments

net	An igraph network.
attr	An attribute of the vertices.
values	Possible values of attr
affirmative	Logical. States if a condition must be its affirmation (e.g. all nodes with gene name "X"), or its negation (all nodes not with gene name "X").

Value

The vertices with attribute equal to any of the values in values.

Examples

```
gi <- get_GI_network(minigwas, snpMapping = minisnpMapping, ppi = minippi)
martini::subvert(gi, "gene", "A")
martini::subvert(gi, "name", c("1A1", "1A3"))
```

Index

evo, [2](#)

get_evo_settings, [10](#)

get_GI_network, [3](#)

get_GM_network, [4](#)

get_GS_network, [5](#)

GM, [3](#)

GS, [4](#)

ld, [5](#)

ldweight_edges, [5](#)

minigwas, [6](#)

minippi, [6](#)

minisnpMapping, [7](#)

run_scones, [7](#)

scones, [8](#)

scones.cv, [9](#)

search_cones, [10](#)

sigmoid, [11](#)

sigmoid.cv, [12](#)

simulate_causal_snps, [13](#)

simulate_phenotype, [13](#)

subvert, [14](#)