# hgu133a2frmavecs

October 9, 2024

---

`hgu133a2barcodevecs` *Vectors used by barcode function for hgu133a2.*

---

## Description

Parameters of the background distribution for use with the barcode function. These correspond to version 3.0 of the Gene Expression Barcode website.

## Usage

```
data(hgu133a2barcodevecs)
```

## Format

A list with 3 elements.

| | |
|---|---|
| mu | background means |
| tau | background standard deviations |
| entropy | observed gene entropy |

## Examples

```
data(hgu133a2barcodevecs)
str(hgu133a2barcodevecs)
```

---

`hgu133a2frmavecs` *Vectors used by fRMA for hgu133a2.*

---

## Description

Frozen parameter vectors for use with the frma and GNUSE functions.

## Usage

```
data(hgu133a2frmavecs)
data(hgu133a2hsentrezgfrmavecs)
```

## Format

A list with 6 or 7 elements.

| | |
|---|---|
| normVec | normalization vector |
| probeVec | probe effect vector |
| probeVarWithin | within batch probe variance |
| probeVarBetween | between batch probe variance |
| probesetSD | within probeset standard deviation |
| medianSE | median standard error for gene expression estimates |
| version | the Entrez Gene alternative CDF version if applicable |

## Examples

```
data(hgu133a2frmavecs)
str(hgu133a2frmavecs)
```

# Index

∗ **datasets**
hgu133a2barcodevecs, 1
hgu133a2frmavecs, 1

hgu133a2barcodevecs, 1
hgu133a2frmavecs, 1
hgu133a2hsentrezgfrmavecs
(hgu133a2frmavecs), 1