

# Package ‘amplican’

December 1, 2023

**Type** Package

**Title** Automated analysis of CRISPR experiments

**Description** `amplican` performs alignment of the amplicon reads, normalizes gathered data, calculates multiple statistics (e.g. cut rates, frameshifts) and presents results in form of aggregated reports. Data and statistics can be broken down by experiments, barcodes, user defined groups, guides and amplicons allowing for quick identification of potential problems.

**Version** 1.24.0

**URL** <https://github.com/valenlab/amplican>

**BugReports** <https://github.com/valenlab/amplican/issues>

**biocViews** ImmunoOncology, Technology, Alignment, qPCR, CRISPR

**License** GPL-3

**LazyData** true

**LinkingTo** Rcpp

**Depends** R (>= 3.5.0), methods, BiocGenerics (>= 0.22.0), Biostrings (>= 2.44.2), data.table (>= 1.10.4-3)

**Imports** Rcpp, utils (>= 3.4.1), S4Vectors (>= 0.14.3), ShortRead (>= 1.34.0), IRanges (>= 2.10.2), GenomicRanges (>= 1.28.4), GenomeInfoDb (>= 1.12.2), BiocParallel (>= 1.10.1), gtable (>= 0.2.0), gridExtra (>= 2.2.1), ggplot2 (>= 3.3.4), ggthemes (>= 3.4.0), waffle (>= 0.7.0), stringr (>= 1.2.0), stats (>= 3.4.1), matrixStats (>= 0.52.2), Matrix (>= 1.2-10), dplyr (>= 0.7.2), rmarkdown (>= 1.6), knitr (>= 1.16), cluster (>= 2.1.4)

**RoxygenNote** 7.2.3

**Suggests** testthat, BiocStyle, GenomicAlignments

**Collate** 'helpers\_general.R' 'AlignmentsExperimentSet-class.R'  
'RcppExports.R' 'helpers\_rmd.R' 'amplicanReport.R'  
'helpers\_directory.R' 'helpers\_warnings.R' 'helpers\_filters.R'  
'helpers\_alignment.R' 'amplicanAlign.R' 'amplican.R'  
'amplicanFilter.R' 'amplicanNormalize.R' 'amplicanSummarize.R'  
'ggforce\_bezier.R' 'helpers\_plots.R'

**VignetteBuilder** knitr  
**Encoding** UTF-8  
**git\_url** <https://git.bioconductor.org/packages/amplican>  
**git\_branch** RELEASE\_3\_18  
**git\_last\_commit** 265b7ec  
**git\_last\_commit\_date** 2023-10-24  
**Repository** Bioconductor 3.18  
**Date/Publication** 2023-12-01  
**Author** Kornel Labun [aut],  
 Eivind Valen [cph, cre]  
**Maintainer** Eivind Valen <eivind.valen@gmail.com>

## R topics documented:

AlignmentsExperimentSet-class	4
alphabetQuality	7
amplican	8
amplicanAlign	8
amplicanConsensus	11
amplicanFilter	12
amplicanMap	13
amplicanNormalize	14
amplicanOverlap	15
amplicanPipeline	16
amplicanPipelineConservative	19
amplicanReport	23
amplicanSummarize	24
amplican_print_reads	25
assignedCount	26
barcodeData	26
barcodeData<-	27
checkConfigFile	28
checkFileWriteAccess	28
checkPrimers	29
checkTarget	29
cigarsToEvents	30
comb_along	31
cumsumw	31
decode	32
defGR	32
experimentData	33
experimentData<-	34
extractEvents	34
findEOP	35
findLQR	36

findPD . . . . .	37
flipRanges . . . . .	38
fwdReads . . . . .	38
fwdReads<- . . . . .	39
fwdReadsType . . . . .	39
fwdReadsType<- . . . . .	40
geom_bezier . . . . .	40
getEventInfo . . . . .	43
getEvents . . . . .	44
get_left_primer . . . . .	45
get_right_primer . . . . .	45
get_seq . . . . .	46
goodAvgQuality . . . . .	46
goodBaseQuality . . . . .	47
is_hdr_strict_by_id . . . . .	47
lookupAlignment . . . . .	48
makeAlignment . . . . .	49
metaplot_deletions . . . . .	50
metaplot_insertions . . . . .	51
metaplot_mismatches . . . . .	52
pairToEvents . . . . .	53
plot_amplicon . . . . .	54
plot_cuts . . . . .	54
plot_deletions . . . . .	55
plot_height . . . . .	57
plot_heterogeneity . . . . .	57
plot_insertions . . . . .	58
plot_mismatches . . . . .	59
plot_variants . . . . .	60
readCounts . . . . .	62
readCounts<- . . . . .	63
revComp . . . . .	64
rveReads . . . . .	64
rveReads<- . . . . .	65
rveReadsType . . . . .	65
rveReadsType<- . . . . .	66
unassignedCount . . . . .	66
unassignedData . . . . .	67
unassignedData<- . . . . .	68
upperGroups . . . . .	68
writeAlignments . . . . .	69

---

AlignmentsExperimentSet-class

*An S4 class to represent alignments from multiple experiments*

---

### Description

Class AlignmentsExperimentSet holds data from multiple alignments for many experiments. Allows to examine alignments in great detail.

### Usage

```
AlignmentsExperimentSet(...)  
  
## S4 method for signature 'AlignmentsExperimentSet'  
length(x)  
  
## S4 method for signature 'AlignmentsExperimentSet'  
fwdReads(x)  
  
## S4 replacement method for signature 'AlignmentsExperimentSet'  
fwdReads(x) <- value  
  
## S4 method for signature 'AlignmentsExperimentSet'  
rveReads(x)  
  
## S4 replacement method for signature 'AlignmentsExperimentSet'  
rveReads(x) <- value  
  
## S4 method for signature 'AlignmentsExperimentSet'  
fwdReadsType(x)  
  
## S4 replacement method for signature 'AlignmentsExperimentSet'  
fwdReadsType(x) <- value  
  
## S4 method for signature 'AlignmentsExperimentSet'  
rveReadsType(x)  
  
## S4 replacement method for signature 'AlignmentsExperimentSet'  
rveReadsType(x) <- value  
  
## S4 method for signature 'AlignmentsExperimentSet'  
unassignedData(x)  
  
## S4 replacement method for signature 'AlignmentsExperimentSet'  
unassignedData(x) <- value  
  
## S4 method for signature 'AlignmentsExperimentSet'
```

```
readCounts(x)

## S4 replacement method for signature 'AlignmentsExperimentSet'
readCounts(x) <- value

## S4 method for signature 'AlignmentsExperimentSet'
experimentData(x)

## S4 replacement method for signature 'AlignmentsExperimentSet'
experimentData(x) <- value

## S4 method for signature 'AlignmentsExperimentSet'
barcodeData(x)

## S4 replacement method for signature 'AlignmentsExperimentSet'
barcodeData(x) <- value

## S4 method for signature 'AlignmentsExperimentSet'
unassignedCount(x)

## S4 method for signature 'AlignmentsExperimentSet'
assignedCount(x)

## S4 method for signature 'AlignmentsExperimentSet'
names(x)

## S4 method for signature 'AlignmentsExperimentSet'
c(x, ...)

## S4 method for signature 'AlignmentsExperimentSet,numeric,missing,missing'
x[i, j, ..., drop = TRUE]

## S3 method for class 'AlignmentsExperimentSet'
as.list(x, ...)

## S4 method for signature 'AlignmentsExperimentSet'
x$name

## S4 method for signature 'AlignmentsExperimentSet'
writeAlignments(x, file = "", aln_format = "txt")

## S4 method for signature 'AlignmentsExperimentSet'
lookupAlignment(x, ID, read_id = 1)

## S4 method for signature 'AlignmentsExperimentSet'
extractEvents(object, use_parallel = FALSE)
```

**Arguments**

...	pass any number of AlignmentsExperimentSet objects, make sure experiment IDs can be unique after merging
x, object	(AlignmentsExperimentSet)
value	Represents assignment values for setter methods.
i, j, name, drop	(numeric, missing, character, missing) AlignmentsExperimentSet object can be subsetted using names of the experiments eg. x\$name or x[i], resulting in AlignmentsExperimentSet object that has only one experiment. During this subsetting, values of unassignedData and barcodeData are dropped.
file	(connection or string) Destination file. When empty, defaults to standard output.
aln_format	("txt" or "fasta") Specifies format of the file.
ID	(string) Experiment Identifier
read_id	(numeric) Read Identifier. Reads are sorted by frequency. Defaults to 1, most abundant read.
use_parallel	(boolean) When using extractEvents you can use multicore back-end through <a href="#">register</a> as this is very slow function (despite vectorization).

**Value**

depending on the function used

**Slots**

fwdReads, rveReads	(list) Named list where each element is of class <a href="#">PairwiseAlignmentsSingleSubject</a> . Names correspond to the experiment ID. Contains alignments of reads against amplicons.
fwdReadsType, rveReadsType	(list) Named list where each element is of logical vector, so far TRUE corresponds to HDR events. Names correspond to the experiment ID. Contains type of read - HDR/NHEJ.
readCounts	(list) Named list where each element is numeric vector that describes how many reads are compressed into unique representation before alignment in fwdReads and/or rveReads.
unassignedData	(data.frame) Contains reads that failed to be assigned to any of the experiments. Alignment of forward against reverse reads may give hint whether these reads are compromised in any way.
experimentData	(data.frame) Expands on configuration file and provides information about cut rates, frameshifts, PRIMER DIMER detection etc. Each row corresponds to experiment ID.
barcodeData	(data.frame) Information that is gathered on the barcode level is gathered in this data.frame, mainly quality filtering statistics.

**View alignments**

Write out all alignments in "fasta" or "txt" format.:

```
writeAlignments(x, file = "", aln_format = "txt")
```

Write out human readable alignments for given experiment and read\_id.:

```
lookupAlignment(x, ID, read_id = 1)
```

**Coercion based on events**

Coerce to data.frame compatible with [GRanges](#) .:  
 as.data.frame(x)

**Examples**

```
exampleAlignments <- Biostrings::pairwiseAlignment(
  Biostrings::DNASTringSet(c("ACTGACTG", "CGACGACG")), "ACGTACGTACGT")
new("AlignmentsExperimentSet",
  fwdReads = list(ID_1 = exampleAlignments, ID_2 = exampleAlignments),
  rveReads = list(ID_1 = exampleAlignments, ID_2 = exampleAlignments),
  fwdReadsType = list(ID_1 = c(FALSE, FALSE), ID_2 = c(FALSE, FALSE)),
  rveReadsType = list(ID_1 = c(FALSE, FALSE), ID_2 = c(FALSE, FALSE)),
  readCounts = list(ID_1 = c(2, 20), ID_2 = c(30, 100)),
  unassignedData = NULL,
  experimentData = data.frame(ID = c("ID_1", "ID_2"),
    Barcode = c("B1", "B1"),
    whatever = c(50, 100)),
  barcodeData = data.frame(Barcode = "B1", statistic1 = 100))
# Coercion
extractEvents(AlignmentsExperimentSet())
GenomicRanges::GRanges(extractEvents(AlignmentsExperimentSet()))
```

---

 alphabetQuality

*This filters out sequences which have nonstandard nucleotides.*


---

**Description**

This filters out sequences which have nonstandard nucleotides.

**Usage**

```
alphabetQuality(reads, batch_size = 1e+07)
```

**Arguments**

reads (ShortRead object) Loaded reads from fastq.  
 batch\_size (numeric) How many reads to process at a time.

**Value**

(boolean) Logical vector with the valid rows as TRUE.

---

amplican

*Automated analysis of CRISPR experiments.*

---

### Description

Main goals:

1. Flexible pipeline for analysis of the CRISPR Mi-Seq or Hi-Seq data.
2. Compatible with GRanges and data.table style.
3. Precise quantification of mutation rates.
4. Prepare automatic reports as .Rmd files that are flexible and open for manipulation.
5. Provide specialized plots for deletions, insertions, mismatches, variants, heterogeneity of the reads.

### Details

To learn more about amplican, start with the vignettes: `browseVignettes(package = "amplican")`

### Author(s)

**Maintainer:** Eivind Valen <eivind.valen@gmail.com> [copyright holder]

Authors:

- Kornel Labun <kornel.labun@gmail.com>

### See Also

Useful links:

- <https://github.com/valenlab/amplican>
- Report bugs at <https://github.com/valenlab/amplican/issues>

---

amplicanAlign

*Align reads to amplicons.*

---

### Description

amplicanAlign takes a configuration files, fastq reads and output directory to prepare alignments and summary. It uses global Needleman-Wunsch algorithm with parameters optimized for CRISPR experiment. After alignments, object of `AlignmentsExperimentSet` is returned that allows for coercion into GRanges (plus is for forward and minus for reverse reads). It is also possible to output alignments in other, additional formats.



**Usage**

```

amplicanAlign(
  config,
  fastq_folder,
  use_parallel = FALSE,
  average_quality = 30,
  min_quality = 20,
  filter_n = FALSE,
  batch_size = 1e+06,
  scoring_matrix = Biostrings::nucleotideSubstitutionMatrix(match = 5, mismatch = -4,
    baseOnly = FALSE, type = "DNA"),
  gap_opening = 25,
  gap_extension = 0,
  fastqfiles = 0.5,
  primer_mismatch = 0,
  donor_mismatch = 3,
  donor_strict = FALSE
)

```

**Arguments**

config	(string) The path to your configuration file. For example: <code>system.file("extdata", "config.txt", package = "amplican")</code> . Configuration file can contain additional columns, but first 11 columns have to follow the example config specification.
fastq_folder	(string) Path to FASTQ files. If not specified, FASTQ files should be in the same directory as config file.
use_parallel	(boolean) Set to TRUE, if you have registered multicore back-end.
average_quality	(numeric) The FASTQ file have a quality for each nucleotide, depending on sequencing technology there exist many formats. This package uses <a href="#">readFastq</a> to parse the reads. If the average quality of the reads fall below value of <code>average_quality</code> then sequence is filtered. Default is 0.
min_quality	(numeric) Similar as in <code>average_quality</code> , but depicts the minimum quality for ALL nucleotides in given read. If one of nucleotides has quality BELOW <code>min_quality</code> , then the sequence is filtered. Default is 20.
filter_n	(boolean) Whether to filter out reads containing N base.
batch_size	(numeric) How many reads to analyze at a time? Needed for filtering of large fastq files.
scoring_matrix	(matrix) Default is 'NUC44'. Pass desired matrix using <a href="#">nucleotideSubstitutionMatrix</a> .
gap_opening	(numeric) The opening gap score.
gap_extension	(numeric) The gap extension score.
fastqfiles	(numeric) Normally you want to use both FASTQ files. But in some special cases, you may want to use only the forward file, or only the reverse file. Possible options:

- 0 Use both FASTQ files.
- 0.5 Use both FASTQ files, but only for one of the reads (forward or reverse) is required to have primer perfectly matched to sequence - eg. use when reverse reads are trimmed of primers, but forward reads have forward primer in the sequence.
- 1 Use only the forward FASTQ file.
- 2 Use only the reverse FASTQ file.

#### primer\_mismatch

(numeric) Decide how many mismatches are allowed during primer matching of the reads, that groups reads by experiments. When `primer_mismatch = 0` no mismatches are allowed, which can increase number of unassigned read.

`donor_mismatch` (numeric) How many events of length 1 (mismatches, deletions and insertions of length 1) are allowed when aligning toward the donor template. This parameter is only used when donor template is specified. The higher the parameter the less strict will be algorithm accepting read as HDR. Set to 0 if only perfect alignments to the donor template marked as HDR, unadvised due to error rate of the sequencers.

`donor_strict` (logical) Applies more strict algorithm for HDR detection. Only these reads that have all of the donor events will count as HDR. Tolerates ‘`donor_mismatch`’ level of noise, but no indels are allowed. Use this when your reads should span over the whole window of the donor events. Might be more time consuming.

#### Value

(AlignmentsExperimentSet) Check [AlignmentsExperimentSet](#) class for details. You can use [lookupAlignment](#) to examine alignments visually.

#### See Also

Other analysis steps: [amplicanConsensus\(\)](#), [amplicanFilter\(\)](#), [amplicanMap\(\)](#), [amplicanNormalize\(\)](#), [amplicanOverlap\(\)](#), [amplicanPipelineConservative\(\)](#), [amplicanPipeline\(\)](#), [amplicanReport\(\)](#), [amplicanSummarize\(\)](#)

#### Examples

```
# path to example config file
config <- system.file("extdata", "config.csv", package = "amplican")
# path to example fastq files
fastq_folder <- system.file("extdata", package = "amplican")
aln <- amplicanAlign(config, fastq_folder)
aln
```

---

amplicanConsensus      *Extract consensus out of forward and reverse events.*

---

## Description

When forward and reverse reads are in agreement on the events (eg. deletion) amplicanConsensus will mark forward event as TRUE indicating that he represents consensus. In cases where forward and reverse read agree only partially, for example, they share the same start of the deletion, but they have different end amplicanConsensus will pick the version of read with higher alignment score, in situation where both of the reads overlap expected cut site, otherwise both events will be rejected and marked FALSE. When there are events only on one of the strands they will be rejected.

## Usage

```
amplicanConsensus(aln, cfgT, overlaps = "overlaps", promiscuous = TRUE)
```

## Arguments

aln	(data.frame) Contains relevant events in GRanges style.
cfgT	(data.frame) Should be table containing at least positions of primers in the amplicons and their identifiers
overlaps	(character) Specifies which metadata column of aln indicates which events are overlapping expected cut site.
promiscuous	(boolean) Allows to relax consensus rules. When TRUE will allow Indels that are not confirmed by the other strand (when both are used).

## Details

In situation where you have only forward or only reverse reads don't use this function and assign all TRUE to all of your events.

Consensus out of the forward + reverse reads is required for amplicanSummary, and amplicanConsensus requires amplicanOverlap.

## Value

(boolean vector) Where TRUE means that given event represents consensus out of forward and reverse reads.

## See Also

Other analysis steps: [amplicanAlign\(\)](#), [amplicanFilter\(\)](#), [amplicanMap\(\)](#), [amplicanNormalize\(\)](#), [amplicanOverlap\(\)](#), [amplicanPipelineConservative\(\)](#), [amplicanPipeline\(\)](#), [amplicanReport\(\)](#), [amplicanSummarize\(\)](#)

**Examples**

```
file_path <- system.file("test_data", "test_aln.csv", package = "amplican")
aln <- data.table::fread(file_path)
cfgT <- data.table::fread(
  system.file("test_data", "test_cfg.csv", package = "amplican"))
all(aln$consensus == amplicanConsensus(aln, cfgT))
```

---

amplicanFilter	<i>Filter Events Overlapping Primers, PRIMER DIMERS and Low Alignment Score Events.</i>
----------------	---

---

**Description**

Very often alignments return deletions that are not real deletions, but rather artifact of incomplete reads eg.:

```
ACTGAAAA----- <- this "deletion" should be filtered
ACTG----ACTGACTG
```

We call them Events Overlapping Primers and filter them together with reads that are potentially PRIMER DIMERS. This filter will also remove all events coming from reads with low alignment score - potential Off-targets.

**Usage**

```
amplicanFilter(aln, cfgT, PRIMER_DIMER)
```

**Arguments**

aln	(data.frame) Should contain events from alignments in GRanges style with columns eg. seqnames, width, start, end.
cfgT	(data.frame) Needs columns Forward_Primer, ReversePrimer and Amplicon.
PRIMER_DIMER	(numeric) Value specifying buffer for PRIMER DIMER detection. For a given read it will be recognized as PRIMER DIMER when alignment will introduce gap of size bigger than: length of amplicon - (lengths of PRIMERS + PRIMER_DIMER value)

**Value**

(aln) Reduced by events classified as PRIMER DIMER or overlapping primers.

**See Also**

[findPD](#) and [findEOP](#)

Other analysis steps: [amplicanAlign\(\)](#), [amplicanConsensus\(\)](#), [amplicanMap\(\)](#), [amplicanNormalize\(\)](#), [amplicanOverlap\(\)](#), [amplicanPipelineConservative\(\)](#), [amplicanPipeline\(\)](#), [amplicanReport\(\)](#), [amplicanSummarize\(\)](#)

**Examples**

```
file_path <- system.file("extdata", "results", "alignments",
                        "raw_events.csv", package = "amplican")
aln <- data.table::fread(file_path)
cfgT <- data.table::fread(
  system.file("extdata", "results", "config_summary.csv",
             package = "amplican"))
amplicanFilter(aln, cfgT, 30)
```

---

amplicanMap	<i>Map events to their respective relative coordinates specified with UPPER case.</i>
-------------	---

---

**Description**

Translate coordinates of [GRanges](#) events so that they can be relative to the amplicon. As point zero we assume first left sided UPPER case letter in the amplicon. Be weary that events for amplicons without expected cut sites are filtered. Don't use this function, if you don't have expected cut sites specified and don't use any of the metaplots.

**Usage**

```
amplicanMap(aln, cfgT)
```

**Arguments**

aln (data.frame) List of events to map to the relative coordinates.  
 cfgT (data.frame) config table

**Value**

([GRanges](#)) Same as events, but the coordinates are relative to the expected cut sites.

**See Also**

Other analysis steps: [amplicanAlign\(\)](#), [amplicanConsensus\(\)](#), [amplicanFilter\(\)](#), [amplicanNormalize\(\)](#), [amplicanOverlap\(\)](#), [amplicanPipelineConservative\(\)](#), [amplicanPipeline\(\)](#), [amplicanReport\(\)](#), [amplicanSummarize\(\)](#)

**Examples**

```
# example config
config <- read.csv(system.file("extdata", "config.csv",
                             package = "amplican"))

# example events
events <- read.csv(system.file("extdata", "results", "alignments",
                              "raw_events.csv", package = "amplican"))
```

```
# make events relative to the UPPER case
amplicanMap(events, config)
```

---

amplicanNormalize      *Remove events that can be found in Controls.*

---

## Description

This function can adjust events for small differences between known annotations (amplicon sequences) and real DNA of the strain that was sequenced. Events from the control are grouped by add and their frequencies are calculated in respect to number of total reads in that groups. In next step events from the control are filtered according to min\_freq, all events below are treated as sequencing errors and rejected. Finally, all events that can be found in treatment group that find their exact match (by non skipped columns) in control group are removed. All events from control group are returned back.

## Usage

```
amplicanNormalize(
  aln,
  cfgT,
  add = c("guideRNA", "Group"),
  skip = c("counts", "score", "seqnames", "read_id", "strand", "overlaps", "consensus"),
  min_freq = 0.01
)
```

## Arguments

aln	(data.frame) Contains events from alignments.
cfgT	(data.frame) Config table with information about experiments.
add	(character vector) Columns from cfgT that should be included in event table for normalization matching. Defaults to c("guideRNA", "Group") , which means that only those events created by the same guideRNA in the same Group will be removed if found in Control.
skip	(character vector) Specifies which columns of aln to skip.
min_freq	(numeric) All events from control group below this frequency will be not included in filtering. Use this to filter out background noise and sequencing errors.

## Value

(data.frame) Same as aln, but events are normalized. Events from Control are not changed. Additionally columns from add are added to the data.frame.

**See Also**

Other analysis steps: [amplicanAlign\(\)](#), [amplicanConsensus\(\)](#), [amplicanFilter\(\)](#), [amplicanMap\(\)](#), [amplicanOverlap\(\)](#), [amplicanPipelineConservative\(\)](#), [amplicanPipeline\(\)](#), [amplicanReport\(\)](#), [amplicanSummarize\(\)](#)

**Examples**

```
aln <- data.frame(seqnames = 1:5, start = 1, end = 2, width = 2,
                 counts = 101:105)
cfgT <- data.frame(ID = 1:5, guideRNA = rep("ACTG", 5),
                  Reads_Filtered = c(2, 2, 3, 3, 4),
                  Group = c("A", "A", "B", "B", "B"),
                  Control = c(TRUE, FALSE, TRUE, FALSE, FALSE))
# all events are same as in the control group, therefore are filtered out
# events from control groups stay
amplicanNormalize(aln, cfgT)
# events that are different from control group are preserved
aln[2, "start"] <- 3
amplicanNormalize(aln, cfgT)
```

---

<code>amplicanOverlap</code>	<i>Check which events overlap expected cut sites.</i>
------------------------------	---

---

**Description**

To determine which deletions, insertions and mismatches (events) are probably created by CRISPR we check whether they overlap expected cut sites. Expected cut sites should be specified in UPPER CASE letters in the amplicon sequences.

**Usage**

```
amplicanOverlap(aln, cfgT, cut_buffer = 5, relative = FALSE)
```

**Arguments**

<code>aln</code>	(data.frame) Contains relevant events in GRanges style.
<code>cfgT</code>	(data.frame) Contains amplicon sequences.
<code>cut_buffer</code>	(numeric) Number of bases that should expand 5' and 3' of the specified expected cut sites.
<code>relative</code>	(boolean) Sets whether events are relative to the position of the target site.

**Value**

(boolean vector) Where TRUE means that given event overlaps cut site.

**See Also**

Other analysis steps: [amplicanAlign\(\)](#), [amplicanConsensus\(\)](#), [amplicanFilter\(\)](#), [amplicanMap\(\)](#), [amplicanNormalize\(\)](#), [amplicanPipelineConservative\(\)](#), [amplicanPipeline\(\)](#), [amplicanReport\(\)](#), [amplicanSummarize\(\)](#)

**Examples**

```
file_path <- system.file("test_data", "test_aln.csv", package = "amplican")
aln <- data.table::fread(file_path)
cfgT <- data.table::fread(
  system.file("test_data", "test_cfg.csv", package = "amplican"))
all(aln$overlaps == amplicanOverlap(aln, cfgT))
```

---

amplicanPipeline

*Wraps main package functionality into one function.*


---

**Description**

amplicanPipeline is convenient wrapper around all functionality of the package with the most robust settings. It will generate all results in the result\_folder and also knit prepared reports into 'reports' folder.

**Usage**

```
amplicanPipeline(
  config,
  fastq_folder,
  results_folder,
  knit_reports = TRUE,
  write_alignments_format = "None",
  average_quality = 30,
  min_quality = 0,
  filter_n = FALSE,
  batch_size = 1e+07,
  use_parallel = FALSE,
  scoring_matrix = Biostrings::nucleotideSubstitutionMatrix(match = 5, mismatch = -4,
    baseOnly = FALSE, type = "DNA"),
  gap_opening = 25,
  gap_extension = 0,
  fastqfiles = 0.5,
  primer_mismatch = 2,
  donor_mismatch = 3,
  donor_strict = FALSE,
  PRIMER_DIMER = 30,
  event_filter = TRUE,
  cut_buffer = 5,
```



```

promiscuous_consensus = TRUE,
normalize = c("guideRNA", "Group"),
min_freq = min_freq_default,
continue = TRUE
)

```

## Arguments

- config** (string) The path to your configuration file. For example: `system.file("extdata", "config.txt", package = "amplican")`. Configuration file can contain additional columns, but first 11 columns have to follow the example config specification.
- fastq\_folder** (string) Path to FASTQ files. If not specified, FASTQ files should be in the same directory as config file.
- results\_folder** (string) Where do you want to store results? The package will create files in that folder so make sure you have writing permissions.
- knit\_reports** (boolean) whether function should "knit" all reports automatically for you (it is time consuming, be patient), when false reports will be prepared, but not knitted
- write\_alignments\_format** (character vector) Whether amplicanPipeline should write alignments results to separate files. Alignments are also always saved as .rds object of [AlignmentsExperimentSet](#) class. Possible options are:
- "fasta" outputs alignments in fasta format where header indicates experiment ID, read id and number of reads
  - "txt" simple format, read information followed by forward read and amplicon sequence followed by reverse read with its amplicon sequence eg.:
- ```

ID: ID_1 Count: 7
ACTGAAAAA-----
ACTG-----ACTGACTG

-----G-ACTG
ACTGACTGACTG

```
- "None" Don't write any alignments to files.
  - c("fasta", "txt") There are also possible combinations of above formats, pass a vector to get alignments in multiple formats.
- average\_quality** (numeric) The FASTQ file have a quality for each nucleotide, depending on sequencing technology there exist many formats. This package uses [readFastq](#) to parse the reads. If the average quality of the reads fall below value of `average_quality` then sequence is filtered. Default is 0.
- min\_quality** (numeric) Similar as in `average_quality`, but depicts the minimum quality for ALL nucleotides in given read. If one of nucleotides has quality BELOW `min_quality`, then the sequence is filtered. Default is 20.
- filter\_n** (boolean) Whether to filter out reads containing N base.

|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| batch_size            | (numeric) How many reads to analyze at a time? Needed for filtering of large fastq files.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| use_parallel          | (boolean) Set to TRUE, if you have registered multicore back-end.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| scoring_matrix        | (matrix) Default is 'NUC44'. Pass desired matrix using <a href="#">nucleotideSubstitutionMatrix</a> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| gap_opening           | (numeric) The opening gap score.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| gap_extension         | (numeric) The gap extension score.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| fastqfiles            | (numeric) Normally you want to use both FASTQ files. But in some special cases, you may want to use only the forward file, or only the reverse file. Possible options: <ul style="list-style-type: none"> <li>• 0 Use both FASTQ files.</li> <li>• 0.5 Use both FASTQ files, but only for one of the reads (forward or reverse) is required to have primer perfectly matched to sequence - eg. use when reverse reads are trimmed of primers, but forward reads have forward primer in the sequence.</li> <li>• 1 Use only the forward FASTQ file.</li> <li>• 2 Use only the reverse FASTQ file.</li> </ul> |
| primer_mismatch       | (numeric) Decide how many mismatches are allowed during primer matching of the reads, that groups reads by experiments. When primer_mismatch = 0 no mismatches are allowed, which can increase number of unassigned read.                                                                                                                                                                                                                                                                                                                                                                                   |
| donor_mismatch        | (numeric) How many events of length 1 (mismatches, deletions and insertions of length 1) are allowed when aligning toward the donor template. This parameter is only used when donor template is specified. The higher the parameter the less strict will be algorithm accepting read as HDR. Set to 0 if only perfect alignments to the donor template marked as HDR, unadvised due to error rate of the sequencers.                                                                                                                                                                                       |
| donor_strict          | (logical) Applies more strict algorithm for HDR detection. Only these reads that have all of the donor events will count as HDR. Tolerates 'donor_mismatch' level of noise, but no indels are allowed. Use this when your reads should span over the whole window of the donor events. Might be more time consuming.                                                                                                                                                                                                                                                                                        |
| PRIMER_DIMER          | (numeric) Value specifying buffer for PRIMER DIMER detection. For a given read it will be recognized as PRIMER DIMER when alignment will introduce gap of size bigger than:<br>length of amplicon - (lengths of PRIMERS + PRIMER_DIMER value)                                                                                                                                                                                                                                                                                                                                                               |
| event_filter          | (logical) Whether detection of offtarget reads, should be enabled.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| cut_buffer            | The number of bases by which extend expected cut sites (specified as UPPER case letters in the amplicon) in 5' and 3' directions.                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| promiscuous_consensus | (boolean) Whether rules of <a href="#">amplicanConsensus</a> should be promiscuous. When promiscuous, we allow indels that have no confirmation on the other strand.                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| normalize             | (character vector) If column 'Control' in config table has all FALSE/0 values then normalization is skipped. Otherwise, normalization is strict, which means events that are found in 'Control' TRUE group will be removed in 'Control' FALSE group. This parameter by default uses columns 'guideRNA' and 'Group'                                                                                                                                                                                                                                                                                          |

|          |                                                                                                                                                                                  |
|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|          | to impose additional restrictions on normalized events eg. only events created by the same 'guideRNA' in the same 'Group' will be normalized.                                    |
| min_freq | (numeric) All events below this frequency are treated as sequencing errors and rejected. This parameter is used during normalization through <a href="#">amplicanNormalize</a> . |
| continue | (boolean) Default TRUE, decides whether to continue failed ampliCan runs. In case of FALSE, all contents in 'results' folder will be removed.                                    |

**Value**

(invisible) results\_folder path

**See Also**

Other analysis steps: [amplicanAlign\(\)](#), [amplicanConsensus\(\)](#), [amplicanFilter\(\)](#), [amplicanMap\(\)](#), [amplicanNormalize\(\)](#), [amplicanOverlap\(\)](#), [amplicanPipelineConservative\(\)](#), [amplicanReport\(\)](#), [amplicanSummarize\(\)](#)

**Examples**

```
# path to example config file
config <- system.file("extdata", "config.csv", package = "amplican")
# path to example fastq files
fastq_folder <- system.file("extdata", package = "amplican")
# output folder
results_folder <- tempdir()

#full analysis, not knitting files automatically
amplicanPipeline(config, fastq_folder, results_folder, knit_reports = FALSE)
```

---

amplicanPipelineConservative

*Wraps main package functionality into one function.*

---

**Description**

amplicanPipelineIndexHopping is identical as amplicanPipeline except that default min\_freq threshold is set to 0.15. Setting this threshold higher will decrease risks of inadequate normalization in cases of potential Index Hopping, potentially decreasing precision of true editing rate calling. Index Hopping can be mitigated with use of unique dual indexing pooling combinations. However, in cases when you might expect Index Hopping to occur you should use this function instead of amplicanPipeline.

**Usage**

```
amplicanPipelineConservative(
  config,
  fastq_folder,
  results_folder,
  knit_reports = TRUE,
  write_alignments_format = "None",
  average_quality = 30,
  min_quality = 0,
  filter_n = FALSE,
  batch_size = 1e+07,
  use_parallel = FALSE,
  scoring_matrix = Biostrings::nucleotideSubstitutionMatrix(match = 5, mismatch = -4,
    baseOnly = FALSE, type = "DNA"),
  gap_opening = 25,
  gap_extension = 0,
  fastqfiles = 0.5,
  primer_mismatch = 2,
  donor_mismatch = 3,
  donor_strict = FALSE,
  PRIMER_DIMER = 30,
  event_filter = TRUE,
  cut_buffer = 5,
  promiscuous_consensus = TRUE,
  normalize = c("guideRNA", "Group"),
  min_freq = min_freq_default,
  continue = TRUE
)
```

**Arguments**

- |                         |                                                                                                                                                                                                                                                                                                                                                                                         |
|-------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| config                  | (string) The path to your configuration file. For example: <code>system.file("extdata", "config.txt", package = "amplican")</code> . Configuration file can contain additional columns, but first 11 columns have to follow the example config specification.                                                                                                                           |
| fastq_folder            | (string) Path to FASTQ files. If not specified, FASTQ files should be in the same directory as config file.                                                                                                                                                                                                                                                                             |
| results_folder          | (string) Where do you want to store results? The package will create files in that folder so make sure you have writing permissions.                                                                                                                                                                                                                                                    |
| knit_reports            | (boolean) whether function should "knit" all reports automatically for you (it is time consuming, be patient), when false reports will be prepared, but not knitted                                                                                                                                                                                                                     |
| write_alignments_format | (character vector) Whether amplicanPipeline should write alignments results to separate files. Alignments are also always saved as .rds object of <a href="#">AlignmentsExperimentSet</a> class. Possible options are: <ul style="list-style-type: none"> <li>• "fasta" outputs alignments in fasta format where header indicates experiment ID, read id and number of reads</li> </ul> |

- "txt" simple format, read information followed by forward read and amplicon sequence followed by reverse read with its amplicon sequence eg.:

```
ID: ID_1 Count: 7
ACTGAAAAA-----
ACTG-----ACTGACTG
```

```
-----G-ACTG
ACTGACTGACTG
```

- "None" Don't write any alignments to files.
- c("fasta", "txt") There are also possible combinations of above formats, pass a vector to get alignments in multiple formats.

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| average_quality | (numeric) The FASTQ file have a quality for each nucleotide, depending on sequencing technology there exist many formats. This package uses <a href="#">readFastq</a> to parse the reads. If the average quality of the reads fall below value of average_quality then sequence is filtered. Default is 0.                                                                                                                                                                                                                                                                                                  |
| min_quality     | (numeric) Similar as in average_quality, but depicts the minimum quality for ALL nucleotides in given read. If one of nucleotides has quality BELOW min_quality, then the sequence is filtered. Default is 20.                                                                                                                                                                                                                                                                                                                                                                                              |
| filter_n        | (boolean) Whether to filter out reads containing N base.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| batch_size      | (numeric) How many reads to analyze at a time? Needed for filtering of large fastq files.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| use_parallel    | (boolean) Set to TRUE, if you have registered multicore back-end.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| scoring_matrix  | (matrix) Default is 'NUC44'. Pass desired matrix using <a href="#">nucleotideSubstitutionMatrix</a> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| gap_opening     | (numeric) The opening gap score.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| gap_extension   | (numeric) The gap extension score.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| fastqfiles      | (numeric) Normally you want to use both FASTQ files. But in some special cases, you may want to use only the forward file, or only the reverse file. Possible options: <ul style="list-style-type: none"> <li>• 0 Use both FASTQ files.</li> <li>• 0.5 Use both FASTQ files, but only for one of the reads (forward or reverse) is required to have primer perfectly matched to sequence - eg. use when reverse reads are trimmed of primers, but forward reads have forward primer in the sequence.</li> <li>• 1 Use only the forward FASTQ file.</li> <li>• 2 Use only the reverse FASTQ file.</li> </ul> |
| primer_mismatch | (numeric) Decide how many mismatches are allowed during primer matching of the reads, that groups reads by experiments. When primer_mismatch = 0 no mismatches are allowed, which can increase number of unassigned read.                                                                                                                                                                                                                                                                                                                                                                                   |
| donor_mismatch  | (numeric) How many events of length 1 (mismatches, deletions and insertions of length 1) are allowed when aligning toward the donor template. This parameter is only used when donor template is specified. The higher the parameter the                                                                                                                                                                                                                                                                                                                                                                    |

|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                       | less strict will be algorithm accepting read as HDR. Set to 0 if only perfect alignments to the donor template marked as HDR, unadvised due to error rate of the sequencers.                                                                                                                                                                                                                                                                                     |
| donor_strict          | (logical) Applies more strict algorithm for HDR detection. Only these reads that have all of the donor events will count as HDR. Tolerates 'donor_mismatch' level of noise, but no indels are allowed. Use this when your reads should span over the whole window of the donor events. Might be more time consuming.                                                                                                                                             |
| PRIMER_DIMER          | (numeric) Value specifying buffer for PRIMER DIMER detection. For a given read it will be recognized as PRIMER DIMER when alignment will introduce gap of size bigger than:<br>length of amplicon - (lengths of PRIMERS + PRIMER_DIMER value)                                                                                                                                                                                                                    |
| event_filter          | (logical) Whether detection of offtarget reads, should be enabled.                                                                                                                                                                                                                                                                                                                                                                                               |
| cut_buffer            | The number of bases by which extend expected cut sites (specified as UPPER case letters in the amplicon) in 5' and 3' directions.                                                                                                                                                                                                                                                                                                                                |
| promiscuous_consensus | (boolean) Whether rules of <a href="#">amplicanConsensus</a> should be promiscuous. When promiscuous, we allow indels that have no confirmation on the other strand.                                                                                                                                                                                                                                                                                             |
| normalize             | (character vector) If column 'Control' in config table has all FALSE/0 values then normalization is skipped. Otherwise, normalization is strict, which means events that are found in 'Control' TRUE group will be removed in 'Control' FALSE group. This parameter by default uses columns 'guideRNA' and 'Group' to impose additional restrictions on normalized events eg. only events created by the same 'guideRNA' in the same 'Group' will be normalized. |
| min_freq              | (numeric) All events below this frequency are treated as sequencing errors and rejected. This parameter is used during normalization through <a href="#">amplicanNormalize</a> .                                                                                                                                                                                                                                                                                 |
| continue              | (boolean) Default TRUE, decides whether to continue failed amplican runs. In case of FALSE, all contents in 'results' folder will be removed.                                                                                                                                                                                                                                                                                                                    |

### Details

result\_folder and also knit prepared reports into 'reports' folder.

### Value

(invisible) results\_folder path

### See Also

Other analysis steps: [amplicanAlign\(\)](#), [amplicanConsensus\(\)](#), [amplicanFilter\(\)](#), [amplicanMap\(\)](#), [amplicanNormalize\(\)](#), [amplicanOverlap\(\)](#), [amplicanPipeline\(\)](#), [amplicanReport\(\)](#), [amplicanSummarize\(\)](#)

---

|                |                                       |
|----------------|---------------------------------------|
| amplicanReport | <i>Prepare reports as .Rmd files.</i> |
|----------------|---------------------------------------|

---

## Description

amplicanReport takes a configuration file, fastq reads and output directory to prepare summaries as an editable .Rmd file. You can specify whether you want to make summaries based on ID, Barcode, Group or even guideRNA and Amplicon. This function automatically knits all reports after creation. If you want to postpone knitting and edit reports, use .Rmd templates to create your own version of reports instead of this function.

## Usage

```
amplicanReport(  
  results_folder,  
  levels = c("id", "barcode", "group", "guide", "amplicon", "summary"),  
  report_files = c("id_report", "barcode_report", "group_report", "guide_report",  
    "amplicon_report", "index"),  
  cut_buffer = 5,  
  xlab_spacing = 4,  
  top = 5,  
  knit_reports = TRUE  
)
```

## Arguments

|                |                                                                                                                                                                                                                          |
|----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| results_folder | (string) Folder containing results from the <a href="#">amplicanAlign</a> function, do not change names of the files.                                                                                                    |
| levels         | (vector) Possible values are: "id", "barcode", "group", "guide", "amplicon", "summary". You can also input more than one value eg. c("id", "barcode") will create two separate reports for each level.                   |
| report_files   | (vector) You can supply your own names of the files. For each of the levels there has to be one file name. Files are created in current working directory by default.                                                    |
| cut_buffer     | (numeric) Default 5. A number of bases that is used around the specified cut site.                                                                                                                                       |
| xlab_spacing   | (numeric) Default is 4. Spacing of the ticks on the x axis of plots.                                                                                                                                                     |
| top            | (numeric) Default is 5. How many of the top most frequent unassigned reads to report? It is only relevant when you used forward and reverse reads. We align them to each other as we could not specify correct amplicon. |
| knit_reports   | (boolean) Whether to knit reports automatically.                                                                                                                                                                         |

## Value

(string) Path to the folder with results.

**See Also**

Other analysis steps: `amplicanAlign()`, `amplicanConsensus()`, `amplicanFilter()`, `amplicanMap()`, `amplicanNormalize()`, `amplicanOverlap()`, `amplicanPipelineConservative()`, `amplicanPipeline()`, `amplicanSummarize()`

**Examples**

```
results_folder <- tempdir()
amplicanReport(results_folder, report_files = file.path(results_folder,
   c("id_report",
   "barcode_report",
   "group_report",
   "guide_report",
   "amplicon_report",
   "index")),
              knit_reports = FALSE)
```

---

|                                |                                                                                    |
|--------------------------------|------------------------------------------------------------------------------------|
| <code>amplicanSummarize</code> | <i>Summarize how many reads have frameshift and how many reads have deletions.</i> |
|--------------------------------|------------------------------------------------------------------------------------|

---

**Description**

Before using this function make sure events are filtered to represent consensus with `amplicanConsensus`, if you use both forward and reverse reads. If you want to calculate metrics over expected cut site, filter events using `amplicanOverlap`.

**Usage**

```
amplicanSummarize(aln, cfgT)
```

**Arguments**

`aln` (data.frame) Contains events from the alignments.  
`cfgT` (data.frame) Config file with the experiments details.

**Details**

Adds columns to `cfgT`:

- `ReadsCut` Count of reads with deletions overlapping expected cut site.
- `Reads_Frameshifted` Count of reads with frameshift overlapping expected cut site.

**Value**

(data.frame) As `cfgT`, but with extra columns.



**See Also**

Other analysis steps: `amplicanAlign()`, `amplicanConsensus()`, `amplicanFilter()`, `amplicanMap()`, `amplicanNormalize()`, `amplicanOverlap()`, `amplicanPipelineConservative()`, `amplicanPipeline()`, `amplicanReport()`

**Examples**

```
file_path <- system.file("extdata", "results", "alignments",
                        "events_filtered_shifted_normalized.csv",
                        package = "amplican")
aln <- data.table::fread(file_path)
cfgT <- data.table::fread(
  system.file("extdata", "results", "config_summary.csv",
             package = "amplican"))
amplicanSummarize(aln, cfgT)
```

---

`amplican_print_reads` *Pretty print forward and reverse reads aligned to each other.*

---

**Description**

Usefull and needed for barcode reports.

**Usage**

```
amplican_print_reads(forward, reverse)
```

**Arguments**

|                      |                                                                                    |
|----------------------|------------------------------------------------------------------------------------|
| <code>forward</code> | (character or vector of characters) Forward reads.                                 |
| <code>reverse</code> | (character or vector of characters) Will be reverse complemented before alignment. |

**Value**

Vector with alignments ready to be printed.

**Examples**

```
# load example data
unassigned_file <- system.file('extdata', 'results', 'alignments',
                              'unassigned_reads.csv', package = 'amplican')
unassigned <- data.table::setDF(data.table::fread(unassigned_file))
# sort by frequency
unassigned <- unassigned[order(unassigned$BarcodeFrequency,
                              decreasing = TRUE), ]
# print alignment of most frequent unassigned reads
```

```
cat(amplican_print_reads(unassigned[1, 'Forward'],
                        unassigned[1, 'Reverse']),
    sep = "\n")
```

---

|               |                                     |
|---------------|-------------------------------------|
| assignedCount | <i>Get count of assigned reads.</i> |
|---------------|-------------------------------------|

---

### Description

Get count of assigned reads.

### Usage

```
assignedCount(x)
```

### Arguments

x (AlignmentsExperimentSet)

### Value

(numeric)

### Examples

```
file_path <- system.file("extdata", "results", "alignments",
                        "AlignmentsExperimentSet.rds", package = "amplican")
aln <- readRDS(file_path)
writeAlignments(aln, file.path(tempdir(), "aln.txt"))
```

---

|             |                      |
|-------------|----------------------|
| barcodeData | <i>Barcode data.</i> |
|-------------|----------------------|

---

### Description

Get barcode data.frame with information on the barcode level.

### Usage

```
barcodeData(x)
```

### Arguments

x (AlignmentsExperimentSet)

**Value**

(data.tableOrNULL)

**Examples**

```
file_path <- system.file("extdata", "results", "alignments",
                        "AlignmentsExperimentSet.rds", package = "amplican")
aln <- readRDS(file_path)
barcodeData(aln)
```

---

`barcodeData<-`                    *Barcode data.*

---

**Description**

Set barcode data.frame with information on the barcode level.

**Usage**

```
barcodeData(x) <- value
```

**Arguments**

|                    |                           |
|--------------------|---------------------------|
| <code>x</code>     | (AlignmentsExperimentSet) |
| <code>value</code> | (data.frame)              |

**Value**

(AlignmentsExperimentSet)

**Examples**

```
file_path <- system.file("extdata", "results", "alignments",
                        "AlignmentsExperimentSet.rds", package = "amplican")
aln <- readRDS(file_path)
barcodeData(aln) <- barcodeData(aln) #replace with the same values as before
```

---

|                 |                                                                          |
|-----------------|--------------------------------------------------------------------------|
| checkConfigFile | <i>Pre-process a config file and checks that everything is in order.</i> |
|-----------------|--------------------------------------------------------------------------|

---

**Description**

Its takes care of the following: No IDs are duplicated. Every combination of barcode, forward primer and reverse primer is unique. Each barcode has unique forward reads file and reverse read files. Checks that the read files exist with read access.

**Usage**

```
checkConfigFile(configTable, fastq_folder)
```

**Arguments**

|              |                                |
|--------------|--------------------------------|
| configTable  | (data.frame) Config file.      |
| fastq_folder | (string) Path to fastq folder. |

**Value**

(boolean) TRUE, If anything goes wrong stops and prints error.

---

|                      |                                                                   |
|----------------------|-------------------------------------------------------------------|
| checkFileWriteAccess | <i>Checks if the given directory exist and can be written to.</i> |
|----------------------|-------------------------------------------------------------------|

---

**Description**

Checks if the given directory exist and can be written to.

**Usage**

```
checkFileWriteAccess(filePath)
```

**Arguments**

|          |                                         |
|----------|-----------------------------------------|
| filePath | (string) A string the path to the file. |
|----------|-----------------------------------------|

**Value**

(invisible) TRUE, Stop if no access.

---

|              |                                                                                                 |
|--------------|-------------------------------------------------------------------------------------------------|
| checkPrimers | <i>Checks if the forward and reverse primer are in the amplicon and where they are located.</i> |
|--------------|-------------------------------------------------------------------------------------------------|

---

**Description**

Checks if the forward and reverse primer are in the amplicon and where they are located.

**Usage**

```
checkPrimers(configTable, fastqfiles)
```

**Arguments**

|             |                                           |
|-------------|-------------------------------------------|
| configTable | (data.frame) A data frame of config file. |
| fastqfiles  | (numeric) Which primers are important.    |

**Value**

configTable (data.frame) A data frame of config file with additional fields for start locations of the primers

---

|             |                                                   |
|-------------|---------------------------------------------------|
| checkTarget | <i>Checks if the guideRNA is in the amplicon.</i> |
|-------------|---------------------------------------------------|

---

**Description**

Checks if the guideRNA is in the amplicon.

**Usage**

```
checkTarget(configTable)
```

**Arguments**

|             |                                        |
|-------------|----------------------------------------|
| configTable | (data.frame) data frame of config file |
|-------------|----------------------------------------|

**Value**

(boolean vector) Prints warning when some guides can't be found.

---

|                |                                                       |
|----------------|-------------------------------------------------------|
| cigarsToEvents | <i>Transform extended CIGAR strings into GRanges.</i> |
|----------------|-------------------------------------------------------|

---

### Description

Transform extended CIGAR strings into [GRanges](#) representation with events of deletions, insertions and mismatches.

### Usage

```
cigarsToEvents(  
  cigars,  
  aln_pos_start,  
  query_seq,  
  ref,  
  read_id,  
  mapq,  
  seqnames,  
  strands,  
  counts  
)
```

### Arguments

|               |                                                                                 |
|---------------|---------------------------------------------------------------------------------|
| cigars        | (character) Extended CIGARS.                                                    |
| aln_pos_start | (integer) Pos of CIGARS.                                                        |
| query_seq     | (character) Aligned query sequences.                                            |
| ref           | (character) Reference sequences used for alignment.                             |
| read_id       | (numeric) Read id for assignment for each of the CIGARS.                        |
| mapq          | (numeric) Mapping scores.                                                       |
| seqnames      | (character) Names of the sequences, potentially ids of the reference sequences. |
| strands       | (character) Strands to assign.                                                  |
| counts        | (integer) Vector of cigar counts, if data collapsed.                            |

### Value

([GRanges](#)) Same as events.

---

|            |                                                                                                          |
|------------|----------------------------------------------------------------------------------------------------------|
| comb_along | <i>Generate all combinations along string exchanging m characters at a time with dictionary letters.</i> |
|------------|----------------------------------------------------------------------------------------------------------|

---

**Description**

Generate all combinations along string seq swapping m characters at a time with letters defined in dictionary letters. Allows, for instance, to create a list of possible primers with two mismatches.

**Usage**

```
comb_along(seq, m = 2, letters = c("A", "C", "T", "G"))
```

**Arguments**

|         |                                                                   |
|---------|-------------------------------------------------------------------|
| seq     | (character) input character to permutate                          |
| m       | (integer) number of elements to permutate at each step            |
| letters | (character vector) dictionary source for combinations of elements |

**Value**

(character vector) all unique combinations of permuted string

**Examples**

```
comb_along("AC")
comb_along("AAA", 1)
comb_along("AAA")
comb_along("AAA", 3)
comb_along("AAAAAAAA")
```

---

|         |                                          |
|---------|------------------------------------------|
| cumsumw | <i>Cumulative sum to calculate shift</i> |
|---------|------------------------------------------|

---

**Description**

Cumulative sum to calculate shift

**Usage**

```
cumsumw(x)
```

**Arguments**

|   |           |
|---|-----------|
| x | (IRanges) |
|---|-----------|

**Value**

(numeric vector)

---

|        |                                                |
|--------|------------------------------------------------|
| decode | <i>Get codons for given string - translate</i> |
|--------|------------------------------------------------|

---

**Description**

Get codons for given string - translate

**Usage**

decode(x)

**Arguments**

x (string)

**Value**

(string) codons

---

|       |                                                                      |
|-------|----------------------------------------------------------------------|
| defGR | <i>Helper to construct GRanges with additional metadata columns.</i> |
|-------|----------------------------------------------------------------------|

---

**Description**

Helper to construct GRanges with additional metadata columns.

**Usage**

```
defGR(
  x,
  ID,
  score,
  strand_info = "+",
  type = "deletion",
  originally = "",
  replacement = ""
)
```



**Arguments**

|             |                                       |
|-------------|---------------------------------------|
| x           | (IRanges) names(x) indicating read_id |
| ID          | (string)                              |
| score       | (numeric) scores from the alignments  |
| strand_info | (string) Either '+', '-'              |
| type        | (string)                              |
| originally  | (string) Base pairs on the amplicon.  |
| replacement | (string) Base pairs on the read.      |

**Value**

(GRanges) Object with meta-data

---

|                |                         |
|----------------|-------------------------|
| experimentData | <i>Experiment data.</i> |
|----------------|-------------------------|

---

**Description**

Get experiment data.frame with information on the experiment level.

**Usage**

```
experimentData(x)
```

**Arguments**

|   |                           |
|---|---------------------------|
| x | (AlignmentsExperimentSet) |
|---|---------------------------|

**Value**

(data.frameOrNULL)

**Examples**

```
file_path <- system.file("extdata", "results", "alignments",
                        "AlignmentsExperimentSet.rds", package = "amplican")
aln <- readRDS(file_path)
experimentData(aln)
```

---

```
experimentData<-      Experiment data.
```

---

### Description

Set experiment data.frame with information on the experiment level.

### Usage

```
experimentData(x) <- value
```

### Arguments

```
x          (AlignmentsExperimentSet)
value      (data.frame)
```

### Value

(AlignmentsExperimentSet)

### Examples

```
file_path <- system.file("extdata", "results", "alignments",
                          "AlignmentsExperimentSet.rds", package = "amplican")
aln <- readRDS(file_path)
experimentData(aln) <- experimentData(aln) # replace with the same values
```

---

```
extractEvents      Extract AlignmentsExperimentSet events into data.frame.
```

---

### Description

Extracts events (insertions, deletions, mismatches) from alignments into data.frame. Can use multiple cores as process is quite slow. All events are relative towards forward strand. "-" in strand column indicates which events were from reverse reads.

### Usage

```
extractEvents(object, use_parallel = FALSE)
```

### Arguments

```
object      (AlignmentsExperimentSet)
use_parallel (boolean) Set to TRUE, if you have registered multicore back-end with register.
```

**Value**

(data.frame) Compatible with [GRanges](#) style.

**Examples**

```
file_path <- system.file("extdata", "results", "alignments",  
                          "AlignmentsExperimentSet.rds", package = "amplican")  
aln <- readRDS(file_path)  
extractEvents(aln)
```

---

findEOP

*Find Events Overlapping Primers.*

---

**Description**

Very often alignments return deletions that are not real deletions, but rather artifact of incomplete reads eg.:

```
ACTGAAAAA----- <- this "deletion" should be filtered  
ACTG----ACTGACTG
```

**Usage**

```
findEOP(aln, cfgT)
```

**Arguments**

aln (data.frame) Should contain events from alignments in [GRanges](#) style with columns eg. seqnames, width, start, end.

cfgT (data.frame) Needs columns Forward\_Primer, ReversePrimer and Amplicon.

**Value**

(logical vector) where TRUE indicates events that are overlapping primers

**See Also**

[findPD](#) [findLQR](#)

Other filters: [findLQR\(\)](#), [findPD\(\)](#)

## Examples

```
file_path <- system.file("extdata", "results", "alignments",
                        "raw_events.csv", package = "amplican")
aln <- data.table::fread(file_path)
cfgT <- data.table::fread(
  system.file("extdata", "results", "config_summary.csv",
             package = "amplican"))
findEOP(aln, cfgT)
```

---

findLQR

*Find Off-targets and Fragmented alignments from reads.*

---

## Description

Will try to detect off-targets and low quality alignments (outliers). It tries k-means clustering on normalized number of events per read and read alignment score. If there are 3 clusters (decided based on silhouette criterion) cluster with high event count and low alignment score will be marked for filtering. When there is less than 1000 scores in `aln` it will filter nothing.

## Usage

```
findLQR(aln)
```

## Arguments

`aln` (data.frame) Should contain events from alignments in GRanges style with columns eg. `seqnames`, `width`, `start`, `end`, `score`.

## Value

(logical vector) where TRUE indicates events that are potential off-targets or low quality alignments.

## See Also

[findPD](#) [findEOP](#)

Other filters: [findEOP\(\)](#), [findPD\(\)](#)

## Examples

```
file_path <- system.file("extdata", "results", "alignments",
                        "raw_events.csv", package = "amplican")
aln <- data.table::fread(file_path)
aln <- aln[seqnames == "ID_1"] # for first experiment
findLQR(aln)
```

---

|        |                                 |
|--------|---------------------------------|
| findPD | <i>Find PRIMER DIMER reads.</i> |
|--------|---------------------------------|

---

## Description

Use to filter reads that are most likely PRIMER DIMERS.

## Usage

```
findPD(aln, cfgT, PRIMER_DIMER = 30)
```

## Arguments

|              |                                                                                                                                                                                                                                               |
|--------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| aln          | (data.frame) Should contain events from alignments in <a href="#">GRanges</a> style with columns eg. seqnames, width, start, end.                                                                                                             |
| cfgT         | (data.frame) Needs columns Forward_Primer, ReversePrimer and Amplicon.                                                                                                                                                                        |
| PRIMER_DIMER | (numeric) Value specifying buffer for PRIMER DIMER detection. For a given read it will be recognized as PRIMER DIMER when alignment will introduce gap of size bigger than:<br>length of amplicon - (lengths of PRIMERS + PRIMER_DIMER value) |

## Value

(logical) Where TRUE indicates event classified as PRIMER DIMER

## See Also

[findEOP](#) [findLQR](#)

Other filters: [findEOP\(\)](#), [findLQR\(\)](#)

## Examples

```
file_path <- system.file("extdata", "results", "alignments",  
                        "raw_events.csv", package = "amplican")  
aln <- data.table::fread(file_path)  
cfgT <- data.table::fread(  
  system.file("extdata", "results", "config_summary.csv",  
             package = "amplican"))  
findPD(aln, cfgT)
```

---

|            |                                                                        |
|------------|------------------------------------------------------------------------|
| flipRanges | <i>Reverse complement events that have amplicons with direction 1.</i> |
|------------|------------------------------------------------------------------------|

---

**Description**

Reverse complement events that have amplicons with direction 1.

**Usage**

```
flipRanges(idR, cfgT)
```

**Arguments**

|      |                                         |
|------|-----------------------------------------|
| idR  | (data.frame) Loaded events.             |
| cfgT | (data.frame) Loaded configuration file. |

**Value**

(data.frame) Returns input idR, but events for amplicons with direction 1 reverse complemented, "+" and "-" swapped.

---

|          |                                      |
|----------|--------------------------------------|
| fwdReads | <i>Alignments for forward reads.</i> |
|----------|--------------------------------------|

---

**Description**

Get alignments for forward reads.

**Usage**

```
fwdReads(x)
```

**Arguments**

|   |                           |
|---|---------------------------|
| x | (AlignmentsExperimentSet) |
|---|---------------------------|

**Value**

(listOrNULL) list with objects of PairwiseAlignmentsSingleSubject

**Examples**

```
file_path <- system.file("extdata", "results", "alignments",
                        "AlignmentsExperimentSet.rds", package = "amplican")
aln <- readRDS(file_path)
fwdReads(aln)
```

---

fwdReads<-                    *Alignments for forward reads.*

---

### Description

Set alignments for forward reads.

### Usage

```
fwdReads(x) <- value
```

### Arguments

x                    (AlignmentsExperimentSet)  
value                (list) Named (experiment IDs) list with elements of

### Value

(AlignmentsExperimentSet) [PairwiseAlignmentsSingleSubject](#) class.

### Examples

```
file_path <- system.file("extdata", "results", "alignments",
                        "AlignmentsExperimentSet.rds", package = "amplican")
aln <- readRDS(file_path)
fwdReads(aln) <- fwdReads(aln) # replace with the same values
```

---

fwdReadsType                *Type of forward reads.*

---

### Description

Get type of forward reads.

### Usage

```
fwdReadsType(x)
```

### Arguments

x                    (AlignmentsExperimentSet)

### Value

(listOrNULL) list with objects of [PairwiseAlignmentsSingleSubject](#)

**Examples**

```
file_path <- system.file("extdata", "results", "alignments",
                        "AlignmentsExperimentSet.rds", package = "amplican")
aln <- readRDS(file_path)
fwdReadsType(aln)
```

---

fwdReadsType<-            *Read type for forward reads.*

---

**Description**

Set read type for forward reads.

**Usage**

```
fwdReadsType(x) <- value
```

**Arguments**

x                    (AlignmentsExperimentSet)  
value                (list) Named (experiment IDs) list with elements of

**Value**

(AlignmentsExperimentSet) [PairwiseAlignmentsSingleSubject](#) class.

**Examples**

```
file_path <- system.file("extdata", "results", "alignments",
                        "AlignmentsExperimentSet.rds", package = "amplican")
aln <- readRDS(file_path)
fwdReadsType(aln) <- fwdReadsType(aln) # replace with the same values
```

---

geom\_bezier            *Create quadratic or cubic bezier curves [copied from ggforce]*

---

**Description**

This set of functionality is copied from ggforce package due to dependency issues on Bioconductor and is used internally (not exported) only. This set of geoms makes it possible to connect points creating either quadratic or cubic beziers. bezier works by calculating points along the bezier and connecting these to draw the curve.



**Usage**

```
stat_bezier(
  mapping = NULL,
  data = NULL,
  geom = "path",
  position = "identity",
  na.rm = FALSE,
  show.legend = NA,
  n = 100,
  inherit.aes = TRUE,
  ...
)
```

```
geom_bezier(
  mapping = NULL,
  data = NULL,
  stat = "bezier",
  position = "identity",
  arrow = NULL,
  lineend = "butt",
  na.rm = FALSE,
  show.legend = NA,
  inherit.aes = TRUE,
  n = 100,
  ...
)
```

**Arguments**

|          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| mapping  | Set of aesthetic mappings created by <code>aes()</code> . If specified and <code>inherit.aes = TRUE</code> (the default), it is combined with the default mapping at the top level of the plot. You must supply mapping if there is no plot mapping.                                                                                                                                                                                                                                                                                                                                                                                                              |
| data     | <p>The data to be displayed in this layer. There are three options:</p> <p>If <code>NULL</code>, the default, the data is inherited from the plot data as specified in the call to <code>ggplot()</code>.</p> <p>A <code>data.frame</code>, or other object, will override the plot data. All objects will be fortified to produce a data frame. See <code>fortify()</code> for which variables will be created.</p> <p>A function will be called with a single argument, the plot data. The return value must be a <code>data.frame</code>, and will be used as the layer data. A function can be created from a formula (e.g. <code>~ head(.x, 10)</code>).</p> |
| geom     | The geometric object to use to display the data, either as a ggproto Geom subclass or as a string naming the geom stripped of the <code>geom_</code> prefix (e.g. "point" rather than "geom_point")                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| position | Position adjustment, either as a string naming the adjustment (e.g. "jitter" to use <code>position_jitter</code> ), or the result of a call to a position adjustment function. Use the latter if you need to change the settings of the adjustment.                                                                                                                                                                                                                                                                                                                                                                                                               |

|             |                                                                                                                                                                                                                                                               |
|-------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| na.rm       | If FALSE, the default, missing values are removed with a warning. If TRUE, missing values are silently removed.                                                                                                                                               |
| show.legend | logical. Should this layer be included in the legends? NA, the default, includes if any aesthetics are mapped. FALSE never includes, and TRUE always includes. It can also be a named logical vector to finely select the aesthetics to display.              |
| n           | The number of points to create for each segment                                                                                                                                                                                                               |
| inherit.aes | If FALSE, overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behaviour from the default plot specification, e.g. <code>borders()</code> . |
| ...         | Other arguments passed on to <code>layer()</code> . These are often aesthetics, used to set an aesthetic to a fixed value, like <code>colour = "red"</code> or <code>size = 3</code> . They may also be parameters to the paired geom/stat.                   |
| stat        | The statistical transformation to use on the data for this layer, either as a ggproto Geom subclass or as a string naming the stat stripped of the <code>stat_</code> prefix (e.g. "count" rather than "stat_count")                                          |
| arrow       | Arrow specification, as created by <code>grid::arrow()</code> .                                                                                                                                                                                               |
| lineend     | Line end style (round, butt, square).                                                                                                                                                                                                                         |

### Details

Input data is understood as a sequence of data points the first being the start point, then followed by one or two control points and then the end point. More than 4 and less than 3 points per group will throw an error.

### Aesthetics

`geom_link`, `geom_link2` and `geom_lin0` understand the following aesthetics (required aesthetics are in bold):

- **`x`** - **`y`** - `color` - `linewidth` - `linetype` - `alpha` - `lineend`

### Computed variables

**`x`**, **`y`** The interpolated point coordinates

**`index`** The progression along the interpolation mapped between 0 and 1

### Author(s)

Thomas Lin Pedersen

### Examples

```
beziers <- data.frame(
  x = c(1, 2, 3, 4, 4, 6, 6),
  y = c(0, 2, 0, 0, 2, 2, 0),
  type = rep(c('cubic', 'quadratic'), c(3, 4)),
  point = c('end', 'control', 'end', 'end', 'control', 'control', 'end')
)
```

```

help_lines <- data.frame(
  x = c(1, 3, 4, 6),
  xend = c(2, 2, 4, 6),
  y = 0,
  yend = 2
)
ggplot2::ggplot() + ggplot2::geom_segment(
  ggplot2::aes(x = x, xend = xend, y = y, yend = yend),
  data = help_lines,
  arrow = ggplot2::arrow(length = ggplot2::unit(c(0, 0, 0.5, 0.5), 'cm')),
  colour = 'grey') +
  amplican::geom_bezier(ggplot2::aes(x= x, y = y, group = type, linetype = type),
    data = beziers) +
  ggplot2::geom_point(ggplot2::aes(x = x, y = y, colour = point), data = beziers)

```

---

getEventInfo

*This function takes alignments and gives back the events coordinates.*


---

## Description

This function takes alignments and gives back the events coordinates.

## Usage

```
getEventInfo(aligned, ID, amplicon_shift, strand_info = "+")
```

## Arguments

|                |                                                                                                                         |
|----------------|-------------------------------------------------------------------------------------------------------------------------|
| aligned        | (PairwiseAlignmentsSingleSubject)                                                                                       |
| ID             | (string)                                                                                                                |
| amplicon_shift | (numeric vector) Shift events additionally by this value. PairwiseAlignmentsSingleSubject returns truncated alignments. |
| strand_info    | (string) Either '+', '-' or default '*'                                                                                 |
| amplicon_len   | (numeric) Length of the amplicon (subject)                                                                              |

## Value

(GRanges) Object with meta-data for insertion, deletion, mismatch

---

|           |                                                                         |
|-----------|-------------------------------------------------------------------------|
| getEvents | <i>Transform aligned strings into GRanges representation of events.</i> |
|-----------|-------------------------------------------------------------------------|

---

### Description

Transforms aligned strings into GRanges representation with events of deletions, insertions and mismatches. Subject should come from one amplicon sequence, after alignment to many sequences (patterns).

### Usage

```
getEvents(  
  pattern,  
  subject,  
  scores,  
  ID = "NA",  
  ampl_shift = 1L,  
  ampl_start = 1L,  
  strand_info = "+"  
)
```

### Arguments

|             |                                                                                                                                                                                        |
|-------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| pattern     | (character) Aligned pattern.                                                                                                                                                           |
| subject     | (character) Aligned subject.                                                                                                                                                           |
| scores      | (integer) Alignment scores of the pattern and subject.                                                                                                                                 |
| ID          | (character) Will be used as seqnames of output GRanges.                                                                                                                                |
| ampl_shift  | (numeric) Possible shift of the amplicons.                                                                                                                                             |
| ampl_start  | (numeric) Real amplicon starts. <a href="#">pairwiseAlignment</a> clips alignments, therefore to output GRanges relative to the amplicon sequence (subject) ranges have to be shifted. |
| strand_info | (character) Strands to assign.                                                                                                                                                         |

### Value

(GRanges) Same as events.

---

|                 |                             |
|-----------------|-----------------------------|
| get_left_primer | <i>left primer sequence</i> |
|-----------------|-----------------------------|

---

**Description**

left primer sequence

**Usage**

```
get_left_primer(config, id)
```

**Arguments**

|        |                           |
|--------|---------------------------|
| config | (data.frame) config table |
| id     | (vector) a vector of id's |

**Value**

(character) left primer sequence

---

|                  |                              |
|------------------|------------------------------|
| get_right_primer | <i>right primer sequence</i> |
|------------------|------------------------------|

---

**Description**

right primer sequence

**Usage**

```
get_right_primer(config, id)
```

**Arguments**

|        |                           |
|--------|---------------------------|
| config | (data.frame) config table |
| id     | (vector) a vector of id's |

**Value**

(character) right primer sequence

---

|         |                                                            |
|---------|------------------------------------------------------------|
| get_seq | <i>amplicon sequence, reverse complemented when needed</i> |
|---------|------------------------------------------------------------|

---

**Description**

amplicon sequence, reverse complemented when needed

**Usage**

```
get_seq(config, id, column = "Amplicon")
```

**Arguments**

|        |                           |
|--------|---------------------------|
| config | (data.frame) config table |
| id     | (vector) a vector of id's |

**Value**

(character) amplicon sequence, reverse complemented if Direction 1

---

|                |                                                                            |
|----------------|----------------------------------------------------------------------------|
| goodAvgQuality | <i>This filters out sequences which have bad average quality readings.</i> |
|----------------|----------------------------------------------------------------------------|

---

**Description**

This filters out sequences which have bad average quality readings.

**Usage**

```
goodAvgQuality(reads, avg = 30, batch_size = 1e+07)
```

**Arguments**

|            |                                                                                                                                                                                                                                                                                                           |
|------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| reads      | (ShortRead object) Loaded reads from fastq.                                                                                                                                                                                                                                                               |
| avg        | (numeric) This is what the average score of the quality of sequence should be. For example, if we have a sequence with nucleotides which have quality 70-70-70, the average would be 70. If set the average to 70 or less the sequence will pass. If we set the average to 71 the sequence will not pass. |
| batch_size | (numeric) How many reads to process at a time.                                                                                                                                                                                                                                                            |

**Value**

(boolean) Logical vector with the valid rows as TRUE.

---

goodBaseQuality      *Filters out sequences which have bad base quality readings.*

---

### Description

Filters out sequences which have bad base quality readings.

### Usage

```
goodBaseQuality(reads, min = 20, batch_size = 1e+07)
```

### Arguments

reads            (ShortRead object) Loaded reads from fastq.

min              (numeric) This is the minimum quality that we accept for every nucleotide. For example, if we have a sequence with nucleotides which have quality 50-50-50-50-10, and we set the minimum to 30, the whole sequence will be a bad sequence.

batch\_size      (numeric) How many reads to process at a time.

### Value

(boolean) Logical vector with the valid rows as TRUE.

---

is\_hdr\_strict\_by\_id      *Figure out which reads conform to the HDR using the donor.*

---

### Description

This is strict detection as compared to 'is\_hdr' which was designed to be less specific and allow for all kinds of donors. This method requires that you have exactly the same events (mismatches, insertions, deletions) as the difference between amplicon and donor sequences. Additional mismatches are also allowed, but restricted to only 'donor\_mismatch' number. This method assumes you have only consensus events and specific ID only.

### Usage

```
is_hdr_strict_by_id(
  aln_id,
  amplicon,
  donor,
  scoring_matrix,
  gap_opening = 25,
  gap_extension = 0,
  donor_mismatch = 3
)
```

**Arguments**

|                |                                                                                                                                   |
|----------------|-----------------------------------------------------------------------------------------------------------------------------------|
| aln_id         | (data.table) This are events that contain already consensus column, they are not shifted yet. These are only for one specific ID. |
| amplicon       | (string) amplicon sequence of this ID                                                                                             |
| donor          | (string) donor sequence of this ID                                                                                                |
| scoring_matrix | (scoring matrix)                                                                                                                  |
| gap_opening    | (integer)                                                                                                                         |
| gap_extension  | (integer)                                                                                                                         |
| donor_mismatch | (integer) How many mismatches are allowed in addition to the HDR events?                                                          |

**Value**

(boolean vector) of TRUE where HDR was detected

---

|                 |                                                 |
|-----------------|-------------------------------------------------|
| lookupAlignment | <i>Show alignment in human readable format.</i> |
|-----------------|-------------------------------------------------|

---

**Description**

Prints alignments in blast-like style for human examination.

**Usage**

```
lookupAlignment(x, ID, read_id = 1)
```

**Arguments**

|         |                                                                                              |
|---------|----------------------------------------------------------------------------------------------|
| x       | (AlignmentsExperimentSet)                                                                    |
| ID      | (string) Experiment Identifier                                                               |
| read_id | (numeric) Read Identifier. Reads are sorted by frequency. Defaults to 1, most abundant read. |

**Value**

(print to view)

**Examples**

```
# load example object
file_path <- system.file("extdata", "results", "alignments",
                          "AlignmentsExperimentSet.rds", package = "amplican")
aln <- readRDS(file_path)
# look at most frequent reads aligned from experiment ID_1
lookupAlignment(aln, "ID_1")
```



---

|               |                                |
|---------------|--------------------------------|
| makeAlignment | <i>Make alignments helper.</i> |
|---------------|--------------------------------|

---

### Description

Aligning reads to the amplicons for each ID in this barcode, constructing amplicanAlignment. Assume that all IDs here belong to the same barcode.

### Usage

```
makeAlignment(
  cfgT,
  average_quality,
  min_quality,
  filter_n,
  batch_size,
  scoring_matrix,
  gap_opening,
  gap_extension,
  fastqfiles,
  primer_mismatch,
  donor_mismatch,
  donor_strict
)
```

### Arguments

|                 |                                                                                                                                                                                                                                                                                                            |
|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| cfgT            | config file as data table                                                                                                                                                                                                                                                                                  |
| average_quality | (numeric) The FASTQ file have a quality for each nucleotide, depending on sequencing technology there exist many formats. This package uses <a href="#">readFastq</a> to parse the reads. If the average quality of the reads fall below value of average_quality then sequence is filtered. Default is 0. |
| min_quality     | (numeric) Similar as in average_quality, but depicts the minimum quality for ALL nucleotides in given read. If one of nucleotides has quality BELOW min_quality, then the sequence is filtered. Default is 20.                                                                                             |
| filter_n        | (boolean) Whether to filter out reads containing N base.                                                                                                                                                                                                                                                   |
| batch_size      | (numeric) How many reads to analyze at a time? Needed for filtering of large fastq files.                                                                                                                                                                                                                  |
| scoring_matrix  | (matrix) Default is 'NUC44'. Pass desired matrix using <a href="#">nucleotideSubstitutionMatrix</a> .                                                                                                                                                                                                      |
| gap_opening     | (numeric) The opening gap score.                                                                                                                                                                                                                                                                           |
| gap_extension   | (numeric) The gap extension score.                                                                                                                                                                                                                                                                         |
| fastqfiles      | (numeric) Normally you want to use both FASTQ files. But in some special cases, you may want to use only the forward file, or only the reverse file. Possible options:                                                                                                                                     |

- 0 Use both FASTQ files.
- 0.5 Use both FASTQ files, but only for one of the reads (forward or reverse) is required to have primer perfectly matched to sequence - eg. use when reverse reads are trimmed of primers, but forward reads have forward primer in the sequence.
- 1 Use only the forward FASTQ file.
- 2 Use only the reverse FASTQ file.

primer\_mismatch

(numeric) Decide how many mismatches are allowed during primer matching of the reads, that groups reads by experiments. When `primer_mismatch = 0` no mismatches are allowed, which can increase number of unassigned read.

donor\_mismatch

(numeric) How many events of length 1 (mismatches, deletions and insertions of length 1) are allowed when aligning toward the donor template. This parameter is only used when donor template is specified. The higher the parameter the less strict will be algorithm accepting read as HDR. Set to 0 if only perfect alignments to the donor template marked as HDR, unadvised due to error rate of the sequencers.

donor\_strict

(logical) Applies more strict algorithm for HDR detection. Only these reads that have all of the donor events will count as HDR. Tolerates ‘donor\_mismatch’ level of noise, but no indels are allowed. Use this when your reads should span over the whole window of the donor events. Might be more time consuming.

## Value

amplicanAlignment object for this barcode experiments

---

metaplot\_deletions      *MetaPlots deletions using ggplot2.*

---

## Description

This function plots deletions in relation to the amplicons for given selection vector that groups values by given config group. All reads should already be converted to their relative position to their respective amplicon using [amplicanMap](#). Top plot is for the forward reads and bottom plot is for reverse reads.

## Usage

```
metaplot_deletions(alnmt, config, group, selection, over = "overlaps")
```

## Arguments

`alnmt` (data.frame) Loaded alignment information from `events_filtered_shifted_normalized.csv` file.

`config` (data.frame) Loaded table from `config_summary.csv` file.

|           |                                                                                                                                              |
|-----------|----------------------------------------------------------------------------------------------------------------------------------------------|
| group     | (string) Name of the column from the config file to use for grouping. Events are subselected based on this column and values from selection. |
| selection | (string or vector of strings) Values from config column specified in group argument.                                                         |
| over      | (string) Specify which column contains overlaps with expected cut sites generated by <a href="#">amplicanOverlap</a>                         |

### Value

(deletions metaplot) ggplot2 object of deletions metaplot

### See Also

Other specialized plots: [metaplot\\_insertions\(\)](#), [metaplot\\_mismatches\(\)](#), [plot\\_cuts\(\)](#), [plot\\_deletions\(\)](#), [plot\\_heterogeneity\(\)](#), [plot\\_insertions\(\)](#), [plot\\_mismatches\(\)](#), [plot\\_variants\(\)](#)

### Examples

```
#example config
config <- read.csv(system.file("extdata", "results", "config_summary.csv",
                             package = "amplican"))

#example alignments results
alignments_file <- system.file("extdata", "results", "alignments",
                              "events_filtered_shifted_normalized.csv",
                              package = "amplican")

alignments <- read.csv(alignments_file)
metaplot_deletions(alignments[alignments$consensus, ],
                  config, "Group", "Betty")
```

---

metaplot\_insertions     *MetaPlots insertions using ggplot2.*

---

### Description

This function plots insertions in relation to the amplicons for given selection vector that groups values by given config group. All reads should already be converted to their relative position to their respective amplicon using [amplicanMap](#). Top plot is for the forward reads and bottom plot is for reverse reads.

### Usage

```
metaplot_insertions(alnmt, config, group, selection)
```

**Arguments**

|           |                                                                                                                                              |
|-----------|----------------------------------------------------------------------------------------------------------------------------------------------|
| alnmt     | (data.frame) Loaded alignment information from alignments_events.csv file.                                                                   |
| config    | (data.frame) Loaded table from config_summary.csv file.                                                                                      |
| group     | (string) Name of the column from the config file to use for grouping. Events are subselected based on this column and values from selection. |
| selection | (string or vector of strings) Values from config column specified in group argument.                                                         |

**Value**

(insertions metaplot) ggplot2 object of insertions metaplot

**See Also**

Other specialized plots: [metaplot\\_deletions\(\)](#), [metaplot\\_mismatches\(\)](#), [plot\\_cuts\(\)](#), [plot\\_deletions\(\)](#), [plot\\_heterogeneity\(\)](#), [plot\\_insertions\(\)](#), [plot\\_mismatches\(\)](#), [plot\\_variants\(\)](#)

**Examples**

```
#example config
config <- read.csv(system.file("extdata", "results", "config_summary.csv",
                             package = "amplican"))

#example alignments results
alignments_file <- system.file("extdata", "results", "alignments",
                              "events_filtered_shifted_normalized.csv",
                              package = "amplican")

alignments <- read.csv(alignments_file)
metaplot_insertions(alignments[alignments$consensus, ], config,
                  "Group", "Betty")
```

---

metaplot\_mismatches     *MetaPlots mismatches using ggplot2.*

---

**Description**

Plots mismatches in relation to the amplicons for given selection vector that groups values by given config group. All reads should already be converted to their relative position to their respective amplicon using [amplicanMap](#). Zero position on new coordinates is the most left UPPER case letter of the respective amplicon. This function filters out all alignment events that have amplicons without UPPER case defined. Top plot is for the forward reads and bottom plot is for reverse reads.

**Usage**

```
metaplot_mismatches(alnmt, config, group, selection)
```

**Arguments**

|           |                                                                                                                                              |
|-----------|----------------------------------------------------------------------------------------------------------------------------------------------|
| alnmt     | (data.frame) Loaded alignment information from alignments_events.csv file.                                                                   |
| config    | (data.frame) Loaded table from config_summary.csv file.                                                                                      |
| group     | (string) Name of the column from the config file to use for grouping. Events are subselected based on this column and values from selection. |
| selection | (string or vector of strings) Values from config column specified in group argument.                                                         |

**Value**

(mismatches metaplot) ggplot2 object of mismatches metaplot

**See Also**

Other specialized plots: [metaplot\\_deletions\(\)](#), [metaplot\\_insertions\(\)](#), [plot\\_cuts\(\)](#), [plot\\_deletions\(\)](#), [plot\\_heterogeneity\(\)](#), [plot\\_insertions\(\)](#), [plot\\_mismatches\(\)](#), [plot\\_variants\(\)](#)

**Examples**

```
#example config
config <- read.csv(system.file("extdata", "results", "config_summary.csv",
                             package = "amplican"))

#example alignments results
alignments_file <- system.file("extdata", "results", "alignments",
                              "events_filtered_shifted_normalized.csv",
                              package = "amplican")

alignments <- read.csv(alignments_file)
metaplot_mismatches(alignments,
                   config, "Group", "Betty")
```

---

pairToEvents

*Read "pair" format of EMBOSS needle into GRanges as events.*

---

**Description**

Parse EMBOSS needle (or needleall) "pair" format into GRanges representation with events of deletions, insertions and mismatches. Make sure that each file corresponds to single subject (single amplicon). Assumes that bottom sequence "-bsequence" corresponds to the "subject" and full sequence alignment is returned.

**Usage**

```
pairToEvents(file, ID = "NA", strand_info = "+")
```

**Arguments**

file (character) File path.  
 ID (character) ID of the experiment, will be used as seqnames of the reutner ranges.  
 strand\_info (character) Strand to assign.

**Value**

(GRanges) Same as events.

---

plot\_amplicon *Plots amplicon sequence using ggplot2.*

---

**Description**

Plots amplicon sequence using ggplot2.

**Usage**

```
plot_amplicon(amplicon, from, to)
```

**Arguments**

amplicon (character) Sequence of the amplicon to plot.  
 from (number) Minimum on x axis - start of the amplicon  
 to (number) Maximum on x axis - not necessarily end of the amplicon

**Value**

(amplicon plot) ggplot2 object of amplicon plot

---

plot\_cuts *Plots cuts using ggplot2.*

---

**Description**

This function plots cuts in relation to the amplicon with distinction for each ID.

**Usage**

```
plot_cuts(alignments, config, id, cut_buffer = 5, xlab_spacing = 4)
```

### Arguments

|              |                                                                                                                                                                                  |
|--------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| alignments   | (data.frame) Loaded alignment information from alignments_events.csv file.                                                                                                       |
| config       | (data.frame) Loaded table from config_summary.csv file.                                                                                                                          |
| id           | (string or vector of strings) Name of the ID column from config file or name of multiple IDs if it is possible to group them. First amplicon will be used as the basis for plot. |
| cut_buffer   | (numeric) Default is 5, you should specify the same as used in the analysis.                                                                                                     |
| xlab_spacing | (numeric) Spacing of the x axis labels. Default is 4.                                                                                                                            |

### Value

(cuts plot) gtable object of cuts plot

### See Also

Other specialized plots: [metaplot\\_deletions\(\)](#), [metaplot\\_insertions\(\)](#), [metaplot\\_mismatches\(\)](#), [plot\\_deletions\(\)](#), [plot\\_heterogeneity\(\)](#), [plot\\_insertions\(\)](#), [plot\\_mismatches\(\)](#), [plot\\_variants\(\)](#)

### Examples

```
#example config
config <- read.csv(system.file("extdata", "results", "config_summary.csv",
                             package = "amplican"))

#example alignments results
alignments_file <- system.file("extdata", "results", "alignments",
                              "events_filtered_shifted_normalized.csv",
                              package = "amplican")

alignments <- read.csv(alignments_file)
plot_cuts(alignments[alignments$consensus & alignments$overlaps, ],
          config, c('ID_1', 'ID_3'))
```

---

plot\_deletions

*Plots deletions using ggplot2.*

---

### Description

This function plots deletions in relation to the amplicon, assumes events are relative to the expected cut site. Top plot is for the forward reads, middle one shows amplicon sequence, and bottom plot is for reverse reads.

**Usage**

```
plot_deletions(
  alignments,
  config,
  id,
  cut_buffer = 5,
  xlab_spacing = 4,
  over = "overlaps"
)
```

**Arguments**

|              |                                                                                                                                                                                  |
|--------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| alignments   | (data.frame) Loaded alignment information from alignments.csv file.                                                                                                              |
| config       | (data.frame) Loaded table from config_summary.csv file.                                                                                                                          |
| id           | (string or vector of strings) Name of the ID column from config file or name of multiple IDs if it is possible to group them. First amplicon will be used as the basis for plot. |
| cut_buffer   | (numeric) Default is 5, you should specify the same as used in the analysis.                                                                                                     |
| xlab_spacing | (numeric) Spacing of the x axis labels. Default is 4.                                                                                                                            |
| over         | (string) Specify which columns contains overlaps with expected cut sites generated by <a href="#">amplicanOverlap</a>                                                            |

**Value**

(deletions plot) gtable object of deletions plot

**See Also**

Other specialized plots: [metaplot\\_deletions\(\)](#), [metaplot\\_insertions\(\)](#), [metaplot\\_mismatches\(\)](#), [plot\\_cuts\(\)](#), [plot\\_heterogeneity\(\)](#), [plot\\_insertions\(\)](#), [plot\\_mismatches\(\)](#), [plot\\_variants\(\)](#)

**Examples**

```
#example config
config <- read.csv(system.file("extdata", "results", "config_summary.csv",
                             package = "amplican"))

#example alignments results
alignments_file <- system.file("extdata", "results", "alignments",
                              "events_filtered_shifted_normalized.csv",
                              package = "amplican")

alignments <- read.csv(alignments_file)
p <- plot_deletions(alignments[alignments$consensus, ],
                   config, c('ID_1', 'ID_3'))
```



---

|             |                                                                      |
|-------------|----------------------------------------------------------------------|
| plot_height | <i>Get figure height in inches for number of elements on y axis.</i> |
|-------------|----------------------------------------------------------------------|

---

**Description**

Helper function to calculate figure height based on number of elements to plot for automating sizes of figures in knited reports.

**Usage**

```
plot_height(x)
```

**Arguments**

x (numeric) number of elements to fit onto height axis

**Value**

(numeric) In inches

**Examples**

```
plot_height(20)
```

---

|                    |                                                        |
|--------------------|--------------------------------------------------------|
| plot_heterogeneity | <i>Plots heterogeneity of the reads using ggplot2.</i> |
|--------------------|--------------------------------------------------------|

---

**Description**

This function creates stacked barplot explaining reads heterogeneity. It groups reads by user defined levels and measures how unique are reads in this level. Uniqueness of reads is simplified to the bins and colored according to the color gradient. Default color black indicates very high heterogeneity of the reads. The more yellow (default) the more similar are reads and less heterogeneous.

**Usage**

```
plot_heterogeneity(  
  alignments,  
  config,  
  level = "ID",  
  colors = c("#000000", "#F0E442"),  
  bins = c(0, 5, seq(10, 100, 10))  
)
```

**Arguments**

|            |                                                                                              |
|------------|----------------------------------------------------------------------------------------------|
| alignments | (data.frame) Loaded alignment information from alignments_events.csv file.                   |
| config     | (data.frame) Loaded table from config_summary.csv file.                                      |
| level      | (string) Name of the column from config file specifying levels to group by.                  |
| colors     | (html colors vector) Two colours for gradient, eg. c('#000000', '#F0E442').                  |
| bins       | (numeric vector) Numeric vector from 0 to 100 specifying bins eg. c(0, 5, seq(10, 100, 10)). |

**Value**

(heterogeneity plot) ggplot2 object of heterogeneity plot

**See Also**

Other specialized plots: [metaplot\\_deletions\(\)](#), [metaplot\\_insertions\(\)](#), [metaplot\\_mismatches\(\)](#), [plot\\_cuts\(\)](#), [plot\\_deletions\(\)](#), [plot\\_insertions\(\)](#), [plot\\_mismatches\(\)](#), [plot\\_variants\(\)](#)

**Examples**

```
#example config
config <- read.csv(system.file("extdata", "results", "config_summary.csv",
                             package = "amplican"))

#example alignments results
alignments_file <- system.file("extdata", "results", "alignments",
                              "events_filtered_shifted_normalized.csv",
                              package = "amplican")

alignments <- read.csv(alignments_file)
plot_heterogeneity(alignments[alignments$consensus, ], config)
```

---

plot\_insertions      *Plots insertions using ggplot2.*

---

**Description**

This function plots insertions in relation to the amplicon. Top plot is for the forward reads, middle one shows amplicon sequence, and bottom plot is for reverse reads.

**Usage**

```
plot_insertions(alignments, config, id, cut_buffer = 5, xlab_spacing = 4)
```

**Arguments**

|              |                                                                                                                                                                                  |
|--------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| alignments   | (data.frame) Loaded alignment information from alignments_events.csv file.                                                                                                       |
| config       | (data.frame) Loaded table from config_summary.csv file.                                                                                                                          |
| id           | (string or vector of strings) Name of the ID column from config file or name of multiple IDs if it is possible to group them. First amplicon will be used as the basis for plot. |
| cut_buffer   | (numeric) Default is 5, you should specify the same as used in the analysis.                                                                                                     |
| xlab_spacing | (numeric) Spacing of the x axis labels. Default is 4.                                                                                                                            |

**Value**

(insertions plot) gtable object of insertions plot

**See Also**

Other specialized plots: [metaplot\\_deletions\(\)](#), [metaplot\\_insertions\(\)](#), [metaplot\\_mismatches\(\)](#), [plot\\_cuts\(\)](#), [plot\\_deletions\(\)](#), [plot\\_heterogeneity\(\)](#), [plot\\_mismatches\(\)](#), [plot\\_variants\(\)](#)

**Examples**

```
#example config
config <- read.csv(system.file("extdata", "results", "config_summary.csv",
                             package = "amplican"))

#example alignments results
alignments_file <- system.file("extdata", "results", "alignments",
                              "events_filtered_shifted_normalized.csv",
                              package = "amplican")

alignments <- read.csv(alignments_file)
p <- plot_insertions(alignments, config, c('ID_1','ID_3'))
```

---

plot\_mismatches      *Plots mismatches using ggplot2.*

---

**Description**

Plots mismatches in relation to the amplicon, assumes your reads are relative to the respective amplicon sequences predicted cut sites. Top plot is for the forward reads, middle one shows amplicon sequence, and bottom plot is for reverse reads.

**Usage**

```
plot_mismatches(alignments, config, id, cut_buffer = 5, xlab_spacing = 4)
```

**Arguments**

|              |                                                                                                                                                                                                                                                                     |
|--------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| alignments   | (data.frame) Loaded alignment information from alignments_events.csv file.                                                                                                                                                                                          |
| config       | (data.frame) Loaded table from config_summary.csv file.                                                                                                                                                                                                             |
| id           | (string or vector of strings) Name of the ID column from config file or name of multiple IDs, if it is possible to group them. They have to have the same amplicon, amplicons on the reverse strand will be reverse complemented to match forward strand amplicons. |
| cut_buffer   | (numeric) Default is 5, you should specify the same as used in the analysis.                                                                                                                                                                                        |
| xlab_spacing | (numeric) Spacing of the x axis labels. Default is 4.                                                                                                                                                                                                               |

**Value**

(mismatches plot) gtable object of mismatches plot

**See Also**

Other specialized plots: [metaplot\\_deletions\(\)](#), [metaplot\\_insertions\(\)](#), [metaplot\\_mismatches\(\)](#), [plot\\_cuts\(\)](#), [plot\\_deletions\(\)](#), [plot\\_heterogeneity\(\)](#), [plot\\_insertions\(\)](#), [plot\\_variants\(\)](#)

**Examples**

```
#example config
config <- read.csv(system.file("extdata", "results", "config_summary.csv",
                             package = "amplican"))

#example alignments results
alignments_file <- system.file("extdata", "results", "alignments",
                              "events_filtered_shifted_normalized.csv",
                              package = "amplican")

alignments <- read.csv(alignments_file)
id <- c('ID_1', 'ID_3'); cut_buffer = 5; xlab_spacing = 4;
p <- plot_mismatches(alignments, config, c('ID_1', 'ID_3'))
ggplot2::ggsave("~/test.png", p, width = 25, units = "in")
```

---

plot\_variants

*Plots most frequent variants using ggplot2.*

---

**Description**

This function plots variants in relation to the amplicon. Shows sequences of top mutants without aggregating on deletions, insertions and mismatches.

**Usage**

```
plot_variants(
  alignments,
  config,
  id,
  cut_buffer = 5,
  top = 10,
  annot = "cov",
  summary_plot = TRUE
)
```

**Arguments**

|              |                                                                                                                                                                                                                                                                               |       |     |  |     |
|--------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-----|--|-----|
| alignments   | (data.frame) Loaded alignment information from alignments_events.csv file.                                                                                                                                                                                                    |       |     |  |     |
| config       | (data.frame) Loaded table from config_summary.csv file.                                                                                                                                                                                                                       |       |     |  |     |
| id           | (string or vector of strings) Name of the ID column from config file or name of multiple IDs if it is possible to group them. First amplicon will be used as the basis for plot.                                                                                              |       |     |  |     |
| cut_buffer   | (numeric) Default is 5, you should specify the same as used in the analysis.                                                                                                                                                                                                  |       |     |  |     |
| top          | (numeric) Specify number of most frequent reads to plot. By default it is 10. Check <a href="#">plot_heterogeneity</a> to see how many reads will be enough to give good overview of your variants.                                                                           |       |     |  |     |
| annot        | ("codon" or "cov" or NA) What to display for annotation top plot. When NA will not display anything, also not display total summary. Codon plot is all reading frames for a given window, and the default "cov" is coverage of all indels and mismatches over a given window. |       |     |  |     |
| summary_plot | (boolean) Whether small summary plot in the upper right corner should be displayed. Top bar summarizes total reads with frameshift (F), reads with Edits without Frameshift (Edits) and reads without Edits (Match).                                                          |       |     |  |     |
|              | <table> <tr> <td>annot</td> <td>on</td> <td> </td> <td>off</td> </tr> </table>                                                                                                                                                                                                | annot | on  |  | off |
| annot        | on                                                                                                                                                                                                                                                                            |       | off |  |     |

**Details**

Top plot shows all six possible frames for given amplicon. Amino acids are colored as follows:

|                    |                           |         |
|--------------------|---------------------------|---------|
| Small nonpolar     | G, A, S, T                | Orange  |
| Hydrophobic        | C, V, I, L, P, F, Y, M, W | Green   |
| Polar              | N, Q, H                   | Magenta |
| Negatively charged | D, E                      | Red     |
| Positively charged | K, R                      | Blue    |
| Other              | eg. *, U, +               | Grey    |

Variant plot shows amplicon reference, UPPER letters which were the basis for window selection are highlighted with dashed white box (guideRNA). Black triangles are reflecting insertion points. Dashed letters indicate deletions. Table associated with variant plot represents:

- Freq - Frequency of given read in experiment. Variants are ordered by frequency value.
- Count - Represents raw count of this variant reads in experiment.
- F - Sum of deletion and insertion widths of events overlapping presented window. Green background indicates frameshift.

### Value

(variant plot) gtable object of variants plot

### Note

This function is inspired by [plotAlignments](#).

### See Also

Other specialized plots: [metaplot\\_deletions\(\)](#), [metaplot\\_insertions\(\)](#), [metaplot\\_mismatches\(\)](#), [plot\\_cuts\(\)](#), [plot\\_deletions\(\)](#), [plot\\_heterogeneity\(\)](#), [plot\\_insertions\(\)](#), [plot\\_mismatches\(\)](#)

### Examples

```
#example config
config <- read.csv(system.file("extdata", "results", "config_summary.csv",
                             package = "amplican"))

#example alignments results
alignments_file <- system.file("extdata", "results", "alignments",
                              "events_filtered_shifted_normalized.csv",
                              package = "amplican")
alignments <- read.csv(alignments_file)

alignments <- alignments[alignments$consensus & alignments$overlaps, ]
p <- plot_variants(alignments[alignments$consensus & alignments$overlaps, ],
                  config, c('ID_1','ID_3'))
```

---

readCounts

*Alignments for forward reads.*

---

### Description

Set alignments for forward reads.

### Usage

```
readCounts(x)
```

### Arguments

x (AlignmentsExperimentSet)

**Value**

(listOrNULL)

**Examples**

```
file_path <- system.file("extdata", "results", "alignments",
                        "AlignmentsExperimentSet.rds", package = "amplican")
aln <- readRDS(file_path)
readCounts(aln)
```

---

readCounts<- *Alignments for forward reads.*

---

**Description**

Set alignments for forward reads.

**Usage**

```
readCounts(x) <- value
```

**Arguments**

|       |                                                     |
|-------|-----------------------------------------------------|
| x     | (AlignmentsExperimentSet)                           |
| value | (list) Named (experiment IDs) list with elements of |

**Value**

(AlignmentsExperimentSet) [PairwiseAlignmentsSingleSubject](#) class.

**Examples**

```
file_path <- system.file("extdata", "results", "alignments",
                        "AlignmentsExperimentSet.rds", package = "amplican")
aln <- readRDS(file_path)
readCounts(aln) <- readCounts(aln) # replace with the same values
```

---

|         |                                                               |
|---------|---------------------------------------------------------------|
| revComp | <i>Reverse and complement given string or list of strings</i> |
|---------|---------------------------------------------------------------|

---

**Description**

Reverse and complement given string or list of strings

**Usage**

```
revComp(x)
```

**Arguments**

x (string or vector of strings)

**Value**

(string or vector of strings) reverse complemented input

---

|          |                                      |
|----------|--------------------------------------|
| rveReads | <i>Alignments for reverse reads.</i> |
|----------|--------------------------------------|

---

**Description**

Get alignments for reverse reads.

**Usage**

```
rveReads(x)
```

**Arguments**

x (AlignmentsExperimentSet)

**Value**

(listOrNULL) list with objects of PairwiseAlignmentsSingleSubject

**Examples**

```
file_path <- system.file("extdata", "results", "alignments",  
                        "AlignmentsExperimentSet.rds", package = "amplican")  
aln <- readRDS(file_path)  
rveReads(aln)
```



---

rveReads<-                    *Alignments for forward reads.*

---

**Description**

Set alignments for forward reads.

**Usage**

```
rveReads(x) <- value
```

**Arguments**

x                    (AlignmentsExperimentSet)  
value                (list) Named (experiment IDs) list with elements of

**Value**

(AlignmentsExperimentSet) [PairwiseAlignmentsSingleSubject](#) class.

**Examples**

```
file_path <- system.file("extdata", "results", "alignments",
                        "AlignmentsExperimentSet.rds", package = "amplican")
aln <- readRDS(file_path)
rveReads(aln) <- rveReads(aln) # replace with the same values
```

---

rveReadsType                *Type of reverse reads.*

---

**Description**

Get type of reverse reads.

**Usage**

```
rveReadsType(x)
```

**Arguments**

x                    (AlignmentsExperimentSet)

**Value**

(listOrNULL) list with objects of [PairwiseAlignmentsSingleSubject](#)

**Examples**

```
file_path <- system.file("extdata", "results", "alignments",
                        "AlignmentsExperimentSet.rds", package = "amplican")
aln <- readRDS(file_path)
rveReadsType(aln)
```

---

rveReadsType<-            *Read type for reverse reads.*

---

**Description**

Set read type for reverse reads.

**Usage**

```
rveReadsType(x) <- value
```

**Arguments**

x                    (AlignmentsExperimentSet)  
value                (list) Named (experiment IDs) list with elements of

**Value**

(AlignmentsExperimentSet) [PairwiseAlignmentsSingleSubject](#) class.

**Examples**

```
file_path <- system.file("extdata", "results", "alignments",
                        "AlignmentsExperimentSet.rds", package = "amplican")
aln <- readRDS(file_path)
rveReadsType(aln) <- rveReadsType(aln) # replace with the same values
```

---

unassignedCount            *Get count of unassigned reads.*

---

**Description**

Get count of unassigned reads.

**Usage**

```
unassignedCount(x)
```

**Arguments**

x                    (AlignmentsExperimentSet)

**Value**

(numeric)

**Examples**

```
file_path <- system.file("extdata", "results", "alignments",  
                        "AlignmentsExperimentSet.rds", package = "amplican")  
aln <- readRDS(file_path)  
unassignedCount(aln)
```

---

|                |                                     |
|----------------|-------------------------------------|
| unassignedData | <i>Unassigned read information.</i> |
|----------------|-------------------------------------|

---

**Description**

Get unassigned reads and their characteristics.

**Usage**

```
unassignedData(x)
```

**Arguments**

x (AlignmentsExperimentSet)

**Value**

(data.frameOrNULL)

**Examples**

```
file_path <- system.file("extdata", "results", "alignments",  
                        "AlignmentsExperimentSet.rds", package = "amplican")  
aln <- readRDS(file_path)  
unassignedData(aln)
```

---

```
unassignedData<-      Alignments for forward reads.
```

---

**Description**

Set alignments for forward reads.

**Usage**

```
unassignedData(x) <- value
```

**Arguments**

x (AlignmentsExperimentSet)  
 value (list) Named (experiment IDs) list with elements of

**Value**

(AlignmentsExperimentSet) [PairwiseAlignmentsSingleSubject](#) class.

**Examples**

```
file_path <- system.file("extdata", "results", "alignments",
                        "AlignmentsExperimentSet.rds", package = "amplican")
aln <- readRDS(file_path)
unassignedData(aln) <- unassignedData(aln) #replace with the same values
```

---

```
upperGroups      Detect uppercases as ranges object.
```

---

**Description**

For a given string, detect how many groups of uppercases is inside, where are they, and how long they are.

**Usage**

```
upperGroups(candidate)
```

**Arguments**

candidate (string) A string with the nucleotide sequence.

**Details**

For example: asdkfaAGASDGA<sup>s</sup>jaeuradAFDS<sup>f</sup>asfj<sup>aeior</sup>Aua<sup>oeurasj</sup>fasdh<sup>fash</sup>TTS<sup>faj</sup>eias<sup>jsf</sup>  
 Has 4 groups of uppercases of length 7, 4, 1 and 3.

**Value**

(IRanges) A IRanges object with uppercases groups for given candidate string

---

|                 |                                  |
|-----------------|----------------------------------|
| writeAlignments | <i>Write alignments to file.</i> |
|-----------------|----------------------------------|

---

**Description**

Saves alignments into txt or fasta file.

**Usage**

```
writeAlignments(x, file = "", aln_format = "txt")
```

**Arguments**

|            |                                                                                   |
|------------|-----------------------------------------------------------------------------------|
| x          | (AlignmentsExperimentSet)                                                         |
| file       | (connection or string) Destination file. When empty, defaults to standard output. |
| aln_format | ("txt" or "fasta") Specifies format of the file.                                  |

**Value**

(invisible)

**Examples**

```
file_path <- system.file("extdata", "results", "alignments",  
                        "AlignmentsExperimentSet.rds", package = "amplican")  
aln <- readRDS(file_path)  
writeAlignments(aln, file.path(tempdir(), "aln.txt"))
```

# Index

## \* analysis steps

- amplicanAlign, 8
- amplicanConsensus, 11
- amplicanFilter, 12
- amplicanMap, 13
- amplicanNormalize, 14
- amplicanOverlap, 15
- amplicanPipeline, 16
- amplicanPipelineConservative, 19
- amplicanReport, 23
- amplicanSummarize, 24

## \* filters

- findEOP, 35
- findLQR, 36
- findPD, 37

## \* internal

- AlignmentsExperimentSet-class, 4
- alphabetQuality, 7
- assignedCount, 26
- barcodeData, 26
- barcodeData<-, 27
- checkConfigFile, 28
- checkFileWriteAccess, 28
- checkPrimers, 29
- checkTarget, 29
- cumsumw, 31
- decode, 32
- defGR, 32
- experimentData, 33
- experimentData<-, 34
- extractEvents, 34
- flipRanges, 38
- fwdReads, 38
- fwdReads<-, 39
- fwdReadsType, 39
- fwdReadsType<-, 40
- get\_left\_primer, 45
- get\_right\_primer, 45
- get\_seq, 46

- getEventInfo, 43
- goodAvgQuality, 46
- goodBaseQuality, 47
- lookupAlignment, 48
- makeAlignment, 49
- plot\_amplicon, 54
- readCounts, 62
- readCounts<-, 63
- revComp, 64
- rveReads, 64
- rveReads<-, 65
- rveReadsType, 65
- rveReadsType<-, 66
- unassignedCount, 66
- unassignedData, 67
- unassignedData<-, 68
- upperGroups, 68
- writeAlignments, 69

## \* specialized plots

- metaplot\_deletions, 50
- metaplot\_insertions, 51
- metaplot\_mismatches, 52
- plot\_cuts, 54
- plot\_deletions, 55
- plot\_heterogeneity, 57
- plot\_insertions, 58
- plot\_mismatches, 59
- plot\_variants, 60

[,AlignmentsExperimentSet,numeric,missing,missing-method  
(AlignmentsExperimentSet-class),  
4

\$,AlignmentsExperimentSet-method  
(AlignmentsExperimentSet-class),  
4

aes(), 41

AlignmentsExperimentSet, 8, 10, 17, 20

AlignmentsExperimentSet  
(AlignmentsExperimentSet-class),  
4

- AlignmentsExperimentSet-class, 4
- alphabetQuality, 7
- amplican, 8
- amplican-package (amplican), 8
- amplican\_print\_reads, 25
- amplicanAlign, 8, 11–13, 15, 16, 19, 22–25
- amplicanConsensus, 10, 11, 12, 13, 15, 16, 18, 19, 22, 24, 25
- amplicanFilter, 10, 11, 12, 13, 15, 16, 19, 22, 24, 25
- amplicanMap, 10–12, 13, 15, 16, 19, 22, 24, 25, 50–52
- amplicanNormalize, 10–13, 14, 16, 19, 22, 24, 25
- amplicanOverlap, 10–13, 15, 15, 19, 22, 24, 25, 51, 56
- amplicanPipeline, 10–13, 15, 16, 16, 22, 24, 25
- amplicanPipelineConservative, 10–13, 15, 16, 19, 19, 24, 25
- amplicanReport, 10–13, 15, 16, 19, 22, 23, 25
- amplicanSummarize, 10–13, 15, 16, 19, 22, 24, 24
- as.list.AlignmentsExperimentSet (AlignmentsExperimentSet-class), 4
- assignedCount, 26
- assignedCount, AlignmentsExperimentSet-method (AlignmentsExperimentSet-class), 4
- barcodeData, 26
- barcodeData, AlignmentsExperimentSet-method (AlignmentsExperimentSet-class), 4
- barcodeData<-, 27
- barcodeData<-, AlignmentsExperimentSet-method (AlignmentsExperimentSet-class), 4
- borders(), 42
- c, AlignmentsExperimentSet-method (AlignmentsExperimentSet-class), 4
- checkConfigFile, 28
- checkFileWriteAccess, 28
- checkPrimers, 29
- checkTarget, 29
- cigarsToEvents, 30
- comb\_along, 31
- cumsumw, 31
- decode, 32
- defGR, 32
- experimentData, 33
- experimentData, AlignmentsExperimentSet-method (AlignmentsExperimentSet-class), 4
- experimentData<-, 34
- experimentData<-, AlignmentsExperimentSet-method (AlignmentsExperimentSet-class), 4
- extractEvents, 34
- extractEvents, AlignmentsExperimentSet-method (AlignmentsExperimentSet-class), 4
- findEOP, 12, 35, 36, 37
- findLQR, 35, 36, 37
- findPD, 12, 35, 36, 37
- flipRanges, 38
- fortify(), 41
- fwdReads, 38
- fwdReads, AlignmentsExperimentSet-method (AlignmentsExperimentSet-class), 4
- fwdReads<-, 39
- fwdReads<-, AlignmentsExperimentSet-method (AlignmentsExperimentSet-class), 4
- fwdReadsType, 39
- fwdReadsType, AlignmentsExperimentSet-method (AlignmentsExperimentSet-class), 4
- fwdReadsType<-, 40
- fwdReadsType<-, AlignmentsExperimentSet-method (AlignmentsExperimentSet-class), 4
- geom\_bezier, 40
- get\_left\_primer, 45
- get\_right\_primer, 45
- get\_seq, 46
- getEventInfo, 43
- getEvents, 44
- ggplot(), 41
- goodAvgQuality, 46

- goodBaseQuality, 47  
 GRanges, 7, 13, 30, 33, 35, 37, 43, 44, 54  
 grid::arrow(), 42  
  
 IRanges, 31, 33, 69  
 is\_hdr\_strict\_by\_id, 47  
  
 layer(), 42  
 length, AlignmentsExperimentSet-method  
     (AlignmentsExperimentSet-class),  
     4  
 lookupAlignment, 10, 48  
 lookupAlignment, AlignmentsExperimentSet-method  
     (AlignmentsExperimentSet-class),  
     4  
  
 makeAlignment, 49  
 metaplot\_deletions, 50, 52, 53, 55, 56,  
     58–60, 62  
 metaplot\_insertions, 51, 51, 53, 55, 56,  
     58–60, 62  
 metaplot\_mismatches, 51, 52, 52, 55, 56,  
     58–60, 62  
  
 names, AlignmentsExperimentSet-method  
     (AlignmentsExperimentSet-class),  
     4  
 nucleotideSubstitutionMatrix, 9, 18, 21,  
     49  
  
 pairToEvents, 53  
 pairwiseAlignment, 44  
 PairwiseAlignmentsSingleSubject, 6, 39,  
     40, 43, 63, 65, 66, 68  
 plot\_amplicon, 54  
 plot\_cuts, 51–53, 54, 56, 58–60, 62  
 plot\_deletions, 51–53, 55, 55, 58–60, 62  
 plot\_height, 57  
 plot\_heterogeneity, 51–53, 55, 56, 57,  
     59–62  
 plot\_insertions, 51–53, 55, 56, 58, 58, 60,  
     62  
 plot\_mismatches, 51–53, 55, 56, 58, 59, 59,  
     62  
 plot\_variants, 51–53, 55, 56, 58–60, 60  
 plotAlignments, 62  
  
 readCounts, 62  
  
 readCounts, AlignmentsExperimentSet-method  
     (AlignmentsExperimentSet-class),  
     4  
 readCounts<-, 63  
 readCounts<-, AlignmentsExperimentSet-method  
     (AlignmentsExperimentSet-class),  
     4  
 readFastq, 9, 17, 21, 49  
 register, 6, 34  
 revComp, 64  
 rveReads, 64  
 rveReads, AlignmentsExperimentSet-method  
     (AlignmentsExperimentSet-class),  
     4  
 rveReads<-, 65  
 rveReads<-, AlignmentsExperimentSet-method  
     (AlignmentsExperimentSet-class),  
     4  
 rveReadsType, 65  
 rveReadsType, AlignmentsExperimentSet-method  
     (AlignmentsExperimentSet-class),  
     4  
 rveReadsType<-, 66  
 rveReadsType<-, AlignmentsExperimentSet-method  
     (AlignmentsExperimentSet-class),  
     4  
  
 stat\_bezier (geom\_bezier), 40  
  
 unassignedCount, 66  
 unassignedCount, AlignmentsExperimentSet-method  
     (AlignmentsExperimentSet-class),  
     4  
 unassignedData, 67  
 unassignedData, AlignmentsExperimentSet-method  
     (AlignmentsExperimentSet-class),  
     4  
 unassignedData<-, 68  
 unassignedData<-, AlignmentsExperimentSet-method  
     (AlignmentsExperimentSet-class),  
     4  
 upperGroups, 68  
  
 writeAlignments, 69  
 writeAlignments, AlignmentsExperimentSet-method  
     (AlignmentsExperimentSet-class),  
     4