

Package ‘mzR’

February 24, 2024

Type Package

Title parser for netCDF, mzXML, mzData and mzML and mzIdentML files
(mass spectrometry data)

Version 2.36.0

Author Bernd Fischer, Steffen Neumann, Laurent Gatto, Qiang Kou, Johannes Rainer

Description mzR provides a unified API to the common file formats and parsers available for mass spectrometry data. It comes with a subset of the proteowizard library for mzXML, mzML and mzIdentML. The netCDF reading code has previously been used in XCMS.

License Artistic-2.0

LazyLoad yes

Depends R (>= 4.0.0), Rcpp (>= 0.10.1), methods, utils

Imports Biobase, BiocGenerics (>= 0.13.6), ProtGenerics (>= 1.17.3),
ncdf4

Suggests msdata (>= 0.15.1), RUnit, mzID, BiocStyle (>= 2.5.19),
knitr, XML, rmarkdown

VignetteBuilder knitr

LinkingTo Rcpp, Rhdf5lib (>= 1.1.4)

RcppModules Pwiz, Ident

SystemRequirements C++11, GNU make

URL <https://github.com/sneumann/mzR/>

BugReports <https://github.com/sneumann/mzR/issues/>

biocViews ImmunoOncology, Infrastructure, DataImport, Proteomics,
Metabolomics, MassSpectrometry

RoxygenNote 6.0.1

git_url <https://git.bioconductor.org/packages/mzR>

git_branch RELEASE_3_18

git_last_commit 1764563

git_last_commit_date 2023-10-24

Repository Bioconductor 3.18

Date/Publication 2024-02-23

Maintainer Steffen Neumann <sneumann@ipb-halle.de>

R topics documented:

copyWriteMSData	2
isolationWindow-methods	4
metadata	4
mzR-class	6
openMSfile	8
peaks	9
pwiz.version	12
writeMSData	13

Index	15
--------------	-----------

copyWriteMSData	<i>Write MS spectrum data to a MS file copying metadata from the originating file</i>
-----------------	---------------------------------------------------------------------------------------

Description

Copy general information from the originating MS file and write this, along with the provided spectra data, to a new file. The expected workflow is the following: data is first loaded from an MS file, e.g. using [peaks](#) and [header](#) methods, processed in R and then saved again to an MS file providing the (eventually) manipulated spectra and header data with arguments `header` and `data`.

Usage

```
copyWriteMSData(object, file, original_file, header, backend =
  "pwiz", outformat = "mzml", rtime_seconds = TRUE, software_processing)
```

Arguments

<code>object</code>	list containing for each spectrum one matrix with columns <code>mz</code> (first column) and <code>intensity</code> (second column). See also peaks for the method that reads such data from an MS file.
<code>file</code>	character(1) defining the name of the file.
<code>original_file</code>	character(1) with the name of the original file from which the spectrum data was first read.
<code>header</code>	data.frame with the header data for the spectra. Has to be in the format as the data.frame returned by the header method.
<code>backend</code>	character(1) defining the backend that should be used for writing. Currently only "pwiz" backend is supported.

outformat character(1) the format of the output file. One of "mzml" or "mzxml".
rtime_seconds logical(1) whether the retention time is provided in seconds or minutes (defaults to TRUE).
software_processing list of character vectors (or single character vector). Each character vector providing information about the software that was used to process the data with optional additional description of processing steps. The length of each character vector has to be ≥ 3 : the first element being the name of the software, the second string its version and the third element the MS CV ID of the software (or "MS:-1" if not known). All additional elements are optional and represent the MS CV ID of each processing step performed with the software.

Note

copyWriteMSData supports at present copying data from mzXML and mzML and exporting to mzML. Copying and exporting to mzXML can fail for some input files.

The intention of this function is to copy data from an existing file and save it along with eventually modified data to a new file. To write new MS data files use the [writeMSData](#) function instead.

Author(s)

Johannes Rainer

See Also

[writeMSData](#) for a function to save MS data to a new mzML or mzXML file.

Examples

```

## Open a MS file and read the spectrum and header information
library(msdata)
fl <- system.file("threonine", "threonine_i2_e35_pH_tree.mzXML",
  package = "msdata")
ms_fl <- openMSfile(fl, backend = "pwiz")

## Get the spectra
pks <- spectra(ms_fl)
## Get the header
hdr <- header(ms_fl)

## Modify the spectrum data adding 100 to each intensity.
pks <- lapply(pks, function(z) {
  z[, 2] <- z[, 2] + 100
  z
})

## Copy metadata and additional information from the originating file
## and save it, along with the modified data, to a new mzML file.
out_file <- tempfile()
copyWriteMSData(pks, file = out_file, original_file = fl,
  header = hdr)

```

isolationWindow-methods

Returns the ion selection isolation window

Description

The methods return matrices of lower (column low) and upper (column high) isolation window offsets. Matrices are returned as a list of length equal to the number of input files (provided as file names of raw mass spectrometry data objects, see below). By default (i.e when `unique. = TRUE`), only unique offsets are returned, as they are expected to be identical for all spectra per acquisition. If this is not the case, a message is displayed.

Methods

`signature(object = "character", unique. = "logical", simplify = "logical")` Returns the isolation window for the file object. By default, only unique isolation windows are returned per file (`unique = TRUE`); if set to `FALSE`, a matrix with as many rows as there are MS2 spectra. If only one file is passed as input and `simplify` is set to `TRUE` (default), the resulting list of length 1 is simplified to a matrix.

`signature(object = "mzRpwiz", unique. = "logical", simplify = "logical")` As above for `mzRpwiz` objects.

Author(s)

Laurent Gatto <lg390@cam.ac.uk> based on the functionality from the `msPurity:::get_isolation_offsets` function.

Examples

```
library("msdata")
f <- msdata::proteomics(full.names = TRUE,
  pattern = "TMT_Erwinia_1uLSike_Top10HCD_isol2_45stepped_60min_01.mzML.gz")
isolationWindow(f)

rw <- openMSfile(f)
isolationWindow(rw)
str(isolationWindow(rw, unique = FALSE))
```

Description

Accessors to the analytical setup metadata of a run. `runInfo` will show a summary of the experiment as a named list, including `scanCount`, `lowMZ`, `highMZ`, `dStartTime`, `dEndTime` and `startTimeStamp`. Note that `startTimeStamp` can only be extracted from *mzML* files using the *pwiz* backend or from *CDF* files. A NA is reported if its value is not available. The `instrumentInfo` method returns a named list including instrument manufacturer, model, ionisation technique, analyzer and detector. `mzRpwis` will give more additional information including information on sample, software using and original source file. These individual pieces of information can also be directly accessed by the specific methods. `mzidInfo` is used for the `mzR` object created from a `mzid` file. It returns basic information on this `mzid` file including file provider, creation date, software, database, enzymes and spectra data format. The `mzidInfo` will return the scoring results in identification. It will return different results for different searching software used.

Usage

```
runInfo(object)
chromatogramsInfo(object)
analyzer(object)
detector(object)
instrumentInfo(object)
ionisation(object)
softwareInfo(object)
sampleInfo(object)
sourceInfo(object)
model(object)
mzidInfo(object)
modifications(object, ...)
psms(object, ...)
substitutions(object)
database(object, ...)
enzymes(object)
tolerance(object, ...)
score(x, ...)
para(object)
specParams(object)
```

Arguments

<code>object</code>	An instantiated <code>mzR</code> object.
<code>x</code>	An instantiated <code>mzR</code> object.
<code>...</code>	Additional arguments, currently ignored.

Author(s)

Steffen Neumann, Laurent Gatto and Qiang Kou

See Also

See for example [peaks](#) to access the data for the spectra in a "`mzR`" class.

Examples

```
library(msdata)

file <- system.file("microtofq/MM8.mzML", package = "msdata")
mz <- openMSfile(file)
fileName(mz)
instrumentInfo(mz)
runInfo(mz)
close(mz)

file <- system.file("cdf/ko15.CDF", package = "msdata")
mz <- openMSfile(file, backend = "netCDF")
fileName(mz)
instrumentInfo(mz)
runInfo(mz)
close(mz)

file <- system.file("mzid", "Tandem.mzid.gz", package="msdata")
mzid <- openIDfile(file)
softwareInfo(mzid)
enzymes(mzid)
```

mzR-class

Class mzR and sub-classes

Description

The class `mzR` is the main class for the common mass spectrometry formats. It is a virtual class and thus not supposed to be instantiated directly.

The sub-classes implement specific APIs to access the underlying data and metadata in the files. Currently `mzRpwiz` is available. `mzRpwiz` uses `Proteowizard` to access the relevant information in `mzData`, `mzXML` and `mzML` files. `mzRident` is used as an interface to `mzIdentML` files.

IMPORTANT: New developers that need to access and manipulate raw mass spectrometry data are advised against using this infrastructure directly. They are invited to use the corresponding `MSnExp` (with *on disk* mode) from the `MSnbase` package instead. The latter supports reading multiple files at once and offers access to the spectra data (*m/z* and intensity) as well as all the spectra metadata using a coherent interface. The `MSnbase` infrastructure itself used the low level classes in `mzR`, thus offering fast and efficient access.

Objects from the Class

`mzR` is a virtual class, so instances cannot be created.

Objects can be created by calls of the form `new("mzRpwiz", ...)`, but more often they will be created with [openMSfile](#).

After creating an `mzR` object, one can write it into a new file. `mzXML`, `mzML`, `mgf` formats are supported.

Slots

fileName: Object of class character storing the original filename used when the instance was created.

backend: One of the implemented backends or NULL.

.__classVersion__: Object of class "Versioned", from Biobase.

Extends

Class "[Versioned](#)", directly.

Methods

For methods to access raw data (spectra and chromatograms), see [peaks](#).

Methods currently implemented for mzR

fileName signature(object = "mzR"): ...

Methods currently implemented for mzRpwiz

analyzer signature(object = "mzRpwiz"): ...

detector signature(object = "mzRpwiz"): ...

instrumentInfo signature(object = "mzRpwiz"): ...

ionisation signature(object = "mzRpwiz"): ...

length signature(x = "mzRpwiz"): ...

manufacturer signature(object = "mzRpwiz"): ...

model signature(object = "mzRpwiz"): ...

runInfo signature(object = "mzRpwiz"): ...

chromatogramsInfo signature(object = "mzRpwiz"): ...

Methods currently implemented for mzRident

mzidInfo signature(object = "mzRident"): ...

psms signature(object = "mzRident"): ...

modifications signature(object = "mzRident"): ...

substitutions signature(object = "mzRident"): ...

database signature(x = "mzRident"): ...

enzymes signature(object = "mzRident"): ...

sourceInfo signature(object = "mzRident"): ...

tolerance signature(object = "mzRident"): ...

score signature(object = "mzRident"): ...

para signature(object = "mzRident"): ...

specParams signature(object = "mzRident"): ...

Author(s)

Steffen Neumann, Laurent Gatto, Qiang Kou

References

Proteowizard: <http://proteowizard.sourceforge.net/>

Examples

```
library(msdata)
filepath <- system.file("microtofq", package = "msdata")
file <- list.files(filepath, pattern="MM14.mzML",
  full.names=TRUE, recursive = TRUE)
mzml <- openMSfile(file)
close(mzml)

## using the pwiz backend
mzml <- openMSfile(file, backend = "pwiz")
```

openMSfile	<i>Create and check mzR objects from netCDF, mzXML, mzData or mzML files.</i>
------------	-------------------------------------------------------------------------------

Description

The openMSfile constructor will create a new format-specific mzR object, open 'filename' file and all header information is loaded as a Rcpp module and made accessible through the pwiz slot of the resulting object.

The openIDfile constructor will create a new format-specific mzR object, open 'filename' file and all information is loaded as a Rcpp module. The mzid format is supported through pwiz backend. Only mzIdentML 1.1 is supported.

Usage

```
openMSfile(filename, backend = NULL, verbose = FALSE)

isInitialized(object)

fileName(object, ...)

openIDfile(filename, verbose = FALSE)
```


Arguments

filename	Path name of the netCDF, mzData, mzXML or mzML file to read/write.
backend	A character(1) specifying which backend API to use. Currently 'netCDF' and 'pwiz' are supported. If backend = NULL (the default), the function tries to determine the backend to be used based on either the file extension of the file content.
object	An instantiated mzR object.
verbose	Enable verbose output.
...	Additional arguments, currently ignored.

Author(s)

Steffen Neumann, Laurent Gatto, Qiang Kou

Examples

```
library(msdata)
filepath <- system.file("microtofq", package = "msdata")
file <- list.files(filepath, pattern="MM14.mzML",
                  full.names=TRUE, recursive = TRUE)
mz <- openMSfile(file)
fileName(mz)
runInfo(mz)
close(mz)

## Not run:
## to use another backend
mz <- openMSfile(file, backend = "pwiz")
mz

## End(Not run)

file <- system.file("mzid", "Tandem.mzid.gz", package="msdata")
mzid <- openIDfile(file)
softwareInfo(mzid)
enzymes(mzid)
```

peaks

Access the raw data from an mzR object.

Description

Access the MS raw data. The `peaks`, `spectra` (can be used interchangeably) and `peaksCount` functions return the (m/z, intensity) pairs and the number peaks in the spectrum/spectra. `peaks` and `spectra` return a single matrix if `scans` is a numeric of length 1 and a list of matrices if several scans are asked for or no `scans` argument is provided (i.e all spectra in the object are returned). `peaksCount` will return a numeric of length n.

The `header` function returns a `data.frame` containing `seqNum`, `acquisitionNum`, `msLevel`, `peaksCount`, `totIonCurrent`, `retentionTime` (in seconds), `basePeakMZ`, `basePeakIntensity`, `collisionEnergy`, `ionisationEnergy`, `lowM`, `highMZ`, `precursorScanNum`, `precursorMZ`, `precursorCharge`, `precursorIntensity`, `mergedScan`, `mergedResultScanNum`, `mergedResultStartScanNum`, `mergedResultEndScanNum`, `filterString`, `spectrumId`, `centroided` (logical whether the data of the spectrum is in centroid mode or profile mode; only for `pwiz` backend), `injectionTime` (ion injection time, in milliseconds), `ionMobilityDriftTime` (in milliseconds), `isolationWindowTargetMZ`, `isolationWindowLowerOffset`, `isolationWindowUpperOffset`, `scanWindowLowerLimit` and `scanWindowUpperLimit`. If multiple scans are queried, a `data.frame` is returned with the scans reported along the rows. For missing or not defined spectrum variables NA is reported.

The `get3Dmap` function performs a simple resampling between `lowMz` and `highMz` with `reMz` resolution. A matrix of dimensions `length(scans)` times `seq(lowMz, highMz, reMz)` is returned.

The `chromatogram` (`chromatograms`) accessors return chromatograms for the MS file handle. If a single index is provided, as `data.frame` containing the retention time (1st columns) and intensities (2nd column) is returned. The name of the former is always `time`, while the latter will depend on the run parameters.

If more than 1 or no chromatogram indices are provided, then a list of chromatograms is returned; either those passed as argument or all of them. By default, the first (and possibly only) chromatogram is the total ion count, which can also be accessed with the `tic` method.

The `nChrom` function returns the number of chromatograms, including the total ion chromatogram.

The `chromatogramHeader` returns (similar to the `header` function for spectra) a `data.frame` with metadata information for the individual chromatograms. The `data.frame` has the columns: `"chromatogramId"` (the ID of the chromatogram as specified in the file), `"chromatogramIndex"` (the index of the chromatogram within the file), `"polarity"` (the polarity for the chromatogram, 0 for negative, +1 for positive and -1 for not set), `"precursorIsolationWindowTargetMZ"` (the isolation window m/z of the precursor), `"precursorIsolationWindowLowerOffset"`, `"precursorIsolationWindowUpperOffset"` (lower and upper offset for the isolation window m/z), `"precursorCollisionEnergy"` (collision energy), `"productIsolationWindowTargetMZ"`, `"productIsolationWindowLowerOffset"` and `"productIsolationWindowUpperOffset"` (definition of the m/z isolation window for the product).

Note that access to chromatograms is only supported in the `pwiz` backend.

Usage

```
header(object, scans, ...)
```

```
peaksCount(object, scans, ...)
```

```
## S4 method for signature 'mzRpwiz'
peaks(object, scans)
## S4 method for signature 'mzRnetCDF'
peaks(object, scans)
```

```
## S4 method for signature 'mzRpwiz'
spectra(object, scans) ## same as peaks
## S4 method for signature 'mzRnetCDF'
spectra(object, scans)
```

```

get3Dmap(object, scans, lowMz, highMz, resMz, ...)

## S4 method for signature 'mzRpwiz'
chromatogram(object, chrom)

## S4 method for signature 'mzRpwiz'
chromatograms(object, chrom) ## same as chromatogram

## S4 method for signature 'mzRpwiz'
chromatogramHeader(object, chrom)

tic(object, ...)

nChrom(object)

```

Arguments

object	An instantiated mzR object.
scans	A numeric specifying which scans to return. Optional for the header, peaks, spectra and peaksCount methods. If omitted, the requested data for all peaks is returned.
lowMz, highMz	Numerics defining the m/z range to be returned.
resMz	a numeric defining the m/z resolution.
chrom	For chromatogram, chromatograms and chromatogramHeader: numeric specifying the index of the chromatograms to be extracted from the file. If omitted, data for all chromatograms is returned.
...	Other arguments. A scan parameter can be passed to peaks.

Details

The column `acquisitionNum` in the `data.frame` returned by the header method contains the index during the scan in which the signal from the spectrum was measured. The `pwiz` backend extracts this number from the spectrum's ID provided in the `mzML` file. In contrast, column `seqNum` contains the index of each spectrum within the file and is thus consecutively numbered. Spectra from files with multiple MS levels are linked to each other *via* their `acquisitionNum`: column `precursorScanNum` of an e.g. MS level 2 spectrum contains the `acquisitionNum` of the related MS level 1 spectrum.

Note

Spectrum identifiers are only specified in `mzML` files, thus, for all other file types the column `"spectrumId"` of the result `data.frame` returned by header contains `"scan="` followed by the acquisition number of the spectrum. Also, only the `pwiz` backend supports extraction of the spectra's IDs from `mzML` files. Thus, only `mzML` files read with `backend = "pwiz"` provide the spectrum IDs defined in the file. The content of the spectrum identifier depends on the vendor and the instrument acquisition settings and is reported here as a character, in its raw form, without further parsing.

Author(s)

Steffen Neumann and Laurent Gatto

See Also

[instrumentInfo](#) for metadata access and the "mzR" class.

[writeMSData](#) and [copyWriteMSData](#) for functions to write MS data in *mzML* or *mzXML* format.

Examples

```
library(msdata)
filepath <- system.file("microtofq", package = "msdata")
file <- list.files(filepath, pattern="MM14.mzML",
                  full.names=TRUE, recursive = TRUE)
mz <- openMSfile(file)
runInfo(mz)
colnames(header(mz))
close(mz)

## A shotgun LCMSMS experiment
f <- proteomics(full.names = TRUE,
                pattern = "TMT_Erwinia_1uLSike_Top10HCD_isol2_45stepped_60min_01.mzML.gz")
x <- openMSfile(f, backend = "pwiz")
x
nChrom(x)
head(tic(x))
head(chromatogram(x, 1L)) ## same as tic(x)
str(chromatogram(x)) ## as a list

p <- peaks(x) ## extract all peak information
head(peaks(x, scan=4)) ## extract just peaks from the 4th scan

## An MRM experiment
f <- proteomics(full.names = TRUE, pattern = "MRM")
x <- openMSfile(f, backend = "pwiz")
x
nChrom(x)
head(tic(x))
head(chromatogram(x, 1L)) ## same as tic(x)
str(chromatogram(x, 10:12))

## get the header information for the chromatograms
ch <- chromatogramHeader(x)
head(ch)
```

Description

Get the version number of pwiz backend.

Usage

```
pwiz.version()
```

```
writeMSData
```

```
Write MS spectrum data to an MS file
```

Description

writeMSData exports the MS spectrum data provided with parameters header and data to an MS file in mzML or mzXML format.

Usage

```
## S4 method for signature 'list,character'
writeMSData(object, file, header,
            backend = "pwiz", outformat = "mzml", rtime_seconds = TRUE,
            software_processing)
```

Arguments

object	list containing for each spectrum one matrix with columns mz (first column) and intensity (second column). See also peaks for the method that reads such data from an MS file.
file	character(1) defining the name of the file.
header	data.frame with the header data for the spectra. Has to be in the format as the data.frame returned by the header method.
backend	character(1) defining the backend that should be used for writing. Currently only "pwiz" backend is supported.
outformat	character(1) the format of the output file. One of "mzml" or "mzxml".
rtime_seconds	logical(1) whether the retention time is provided in seconds or minutes (defaults to TRUE).
software_processing	list of character vectors (or single character vector). Each character vector providing information about the software that was used to process the data with optional additional description of processing steps. The length of each character vector has to be ≥ 3 : the first element being the name of the software, the second string its version and the third element the MS CV ID of the software (or "MS:-1" if not known). All additional elements are optional and represent the MS CV ID of each processing step performed with the software.

Author(s)

Johannes Rainer

See Also

[copyWriteMSData](#) for a function to copy general information from a MS data file and writing eventually modified MS data from that originating file.

Examples

```
## Open a MS file and read the spectrum and header information
library(msdata)
fl <- system.file("threonine", "threonine_i2_e35_pH_tree.mzXML",
  package = "msdata")
ms_fl <- openMSfile(fl, backend = "pwiz")

## Get the spectra
pks <- spectra(ms_fl)
## Get the header
hdr <- header(ms_fl)

## Modify the spectrum data adding 100 to each intensity.
pks <- lapply(pks, function(z) {
  z[, 2] <- z[, 2] + 100
  z
})

## Write the data to a mzML file.
out_file <- tempfile()
writeMSData(object = pks, file = out_file, header = hdr)
```

Index

- * **classes**
 - mzR-class, 6
- * **methods**
 - isolationWindow-methods, 4
- analyzer (metadata), 4
- analyzer, mzRnetCDF-method (mzR-class), 6
- analyzer, mzRp wiz-method (mzR-class), 6
- chromatogram (peaks), 9
- chromatogram, mzRnetCDF-method (peaks), 9
- chromatogram, mzRp wiz-method (peaks), 9
- chromatogramHeader (peaks), 9
- chromatogramHeader, mzRnetCDF-method (peaks), 9
- chromatogramHeader, mzRp wiz-method (peaks), 9
- chromatograms (peaks), 9
- chromatograms, mzRnetCDF-method (peaks), 9
- chromatograms, mzRp wiz-method (peaks), 9
- chromatogramsInfo (metadata), 4
- chromatogramsInfo, mzRp wiz-method (mzR-class), 6
- class:mzR (mzR-class), 6
- class:mzRident (mzR-class), 6
- class:mzRnetCDF (mzR-class), 6
- class:mzRp wiz (mzR-class), 6
- close (mzR-class), 6
- close, mzRnetCDF-method (mzR-class), 6
- close, mzRp wiz-method (mzR-class), 6
- copyWriteMSData, 2, 12, 14
- database (metadata), 4
- database, mzRident-method (mzR-class), 6
- detector (metadata), 4
- detector, mzRnetCDF-method (mzR-class), 6
- detector, mzRp wiz-method (mzR-class), 6
- enzymes (metadata), 4
- enzymes, mzRident-method (mzR-class), 6
- fileName (openMSfile), 8
- fileName, mzR-method (mzR-class), 6
- get3Dmap (peaks), 9
- get3Dmap, mzRp wiz-method (peaks), 9
- header, 2, 10, 13
- header (peaks), 9
- header, mzRnetCDF, missing-method (peaks), 9
- header, mzRnetCDF, numeric-method (peaks), 9
- header, mzRp wiz, missing-method (peaks), 9
- header, mzRp wiz, numeric-method (peaks), 9
- instrumentInfo, 12
- instrumentInfo (metadata), 4
- instrumentInfo, mzRnetCDF-method (mzR-class), 6
- instrumentInfo, mzRp wiz-method (mzR-class), 6
- ionisation (metadata), 4
- ionisation, mzRnetCDF-method (mzR-class), 6
- ionisation, mzRp wiz-method (mzR-class), 6
- isInitialized (openMSfile), 8
- isInitialized, mzRnetCDF-method (mzR-class), 6
- isolationWindow
 - (isolationWindow-methods), 4
- isolationWindow, character-method (isolationWindow-methods), 4
- isolationWindow, mzRp wiz-method (isolationWindow-methods), 4
- isolationWindow-methods, 4
- length (mzR-class), 6
- length, mzRident-method (mzR-class), 6
- length, mzRnetCDF-method (mzR-class), 6

- length, mzRpwis-method (mzR-class), 6
- manufacturer (metadata), 4
- manufacturer, mzRnetCDF-method (mzR-class), 6
- manufacturer, mzRpwis-method (mzR-class), 6
- metadata, 4
- model (metadata), 4
- model, mzRnetCDF-method (mzR-class), 6
- model, mzRpwis-method (mzR-class), 6
- modifications (metadata), 4
- modifications, mzRident-method (mzR-class), 6
- mzidInfo (metadata), 4
- mzidInfo, mzRident-method (mzR-class), 6
- mzR, 5, 12
- mzR-class, 6
- mzRident-class (mzR-class), 6
- mzRnetCDF-class (mzR-class), 6
- mzRpwis-class (mzR-class), 6

- nChrom (peaks), 9

- openIDfile (openMSfile), 8
- openMSfile, 6, 8

- para (metadata), 4
- para, mzRident-method (mzR-class), 6
- peaks, 2, 5, 7, 9, 13
- peaks, mzRnetCDF-method (peaks), 9
- peaks, mzRpwis-method (peaks), 9
- peaksCount (peaks), 9
- peaksCount, mzRpwis, missing-method (peaks), 9
- peaksCount, mzRpwis, numeric-method (peaks), 9
- psms (metadata), 4
- psms, mzRident-method (mzR-class), 6
- pwiz.version, 12

- runInfo (metadata), 4
- runInfo, mzRnetCDF-method (mzR-class), 6
- runInfo, mzRpwis-method (mzR-class), 6

- sampleInfo (metadata), 4
- sampleInfo, mzRpwis-method (mzR-class), 6
- score (metadata), 4
- score, mzRident-method (mzR-class), 6
- softwareInfo (metadata), 4
- softwareInfo, mzRident-method (mzR-class), 6
- softwareInfo, mzRpwis-method (mzR-class), 6
- sourceInfo (metadata), 4
- sourceInfo, mzRident-method (mzR-class), 6
- sourceInfo, mzRpwis-method (mzR-class), 6
- specParams (metadata), 4
- specParams, mzRident-method (mzR-class), 6
- spectra (peaks), 9
- spectra, mzRnetCDF-method (peaks), 9
- spectra, mzRpwis-method (peaks), 9
- substitutions (metadata), 4
- substitutions, mzRident-method (mzR-class), 6

- tic (peaks), 9
- tic, mzRpwis-method (peaks), 9
- tolerance (metadata), 4
- tolerance, mzRident-method (mzR-class), 6

- Versioned, 7

- writeMSData, 3, 12, 13
- writeMSData, list, character-method (writeMSData), 13